



(11) **EP 1 400 927 A1**

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 158(3) EPC

(43) Date of publication:
24.03.2004 Bulletin 2004/13

(51) Int Cl.7: **G06T 7/20, H04N 7/16**

(21) Application number: **02743725.0**

(86) International application number:
PCT/JP2002/006386

(22) Date of filing: **26.06.2002**

(87) International publication number:
WO 2003/003308 (09.01.2003 Gazette 2003/02)

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

- **ISHIBASHI, Junichi, SONY CORPORATION**
Tokyo 141-0001 (JP)
- **NAGANO, Takahiro, SONY CORPORATION**
Tokyo 141-0001 (JP)
- **FUJIWARA, Naoki, SONY CORPORATION**
Tokyo 141-0001 (JP)
- **MIYAKE, Toru, SONY CORPORATION**
Tokyo 141-0001 (JP)
- **WADA, Seiji, SONY CORPORATION**
Tokyo 141-0001 (JP)

(30) Priority: **27.06.2001 JP 2001195592**

(71) Applicant: **Sony Corporation**
Tokyo 141-0001 (JP)

(74) Representative:
Robinson, Nigel Alexander Julian et al
D. Young & Co.,
21 New Fetter Lane
London EC4A 1DA (GB)

(72) Inventors:
• **KONDO, Tetsujiro, SONY CORPORATION**
Tokyo 141-0001 (JP)
• **SAWAO, Takashi, SONY CORPORATION**
Tokyo 141-0001 (JP)

(54) **COMMUNICATION APPARATUS AND METHOD**


(57) The present invention makes it possible to process at high speed the foreground component image and the background component image of picked up images on a network platform.

A client computer 27 outputs information specifying image data desired to separate to a separation server 11. The separation server 11 obtains the specified image data from a storage server 18 and outputs it to a motion detecting server 12 to perform motion detection processing.

Thereafter, the image data, motion vector and positional information are output to an area specifying

server 13. The area specifying server 13 generates area information of the image data and outputs the area information to a mixture ratio calculating server 14 in addition to the image data, the motion vector and the positional information. The mixture ratio calculating server 14 calculates a mixture ratio on the basis of the image data, the motion vector, the positional information and the area information, and a foreground/background image separation server 15 separates foreground and background of the input image on the basis of such information. The present invention may be employed in a business model for image processing.

FIG. 1



EP 1 400 927 A1

BEST AVAILABLE COPY

Description

Technical Field

5 [0001] The present invention relates to a communication system and a method thereof, and more particularly, to a communication system and a method for distributing image processing to a plurality of servers on a network to perform separated or isolated image processing desired by a user, wherein the communication system and the method make it possible to improve the speed of image processing on a network platform at reduced costs.

10 Background Art

[0002] In general, techniques for synthesizing images desired by a user on a network are widely known.

[0003] Synthesized image is usually generated by overlapping and joining a number of pre-existing images such as images having already been stored in a server connected through a network or images having been made available from digital still cameras. In some cases, the synthesized image may be generated by a texture mapping.

15 [0004] However, there are problems in that synthesized images generated by using the above conventional methods give rise to the occurrences of motion blur. For example, motion blur commonly occurs with a moving body that cannot be accurately adjusted into the synthesized images. Consequently, synthesizing processes are performed with low accuracy and unnatural appearances are frequently generated in the synthesized images.

20 [0005] Additionally, if one server performs synthesizing process in a multiple bundle task, a significant duration of time is required for the process. For example, even when the same background images are to be overlapped, the overlapping process is repeated as many times as the number of images desired. This poses a problem to users in that when the processing services are charged by time, the cost can be a considerable burden.

25 DISCLOSURE OF INVENTION

[0006] In view of the foregoing, it is an object of the present invention to provide a communication system and a method for distributing image processing characterized by having multiple tasks to a plurality of servers on a network to perform separated or isolated image processing desired by a user, wherein the communication system and the method make it possible to improve the speed of image processing on a network platform at reduced costs.

30 [0007] A first communication apparatus of the present invention comprises a separating means for separating a predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time, into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; a requested information input means for inputting requested information of a user; and an encoded data output means for outputting encoded data generated when the image is separated into a foreground component image and a background component image by the separating means on the basis of the requested information input by the requested information input means.

40 [0008] A charging means may be further comprised for performing a charge processing in accordance with the requested information.

[0009] The charging means may generate charge information including a user ID, a communication system ID and cost information corresponding to the requested information in accordance with the requested information.

45 [0010] The charging means may perform a charge processing with respect to a financial account of the user on the basis of the charge information.

[0011] The charging means may perform the charge processing by deducting the number of points corresponding to the cost information from the number of points of each user used in the charge processing.

[0012] The encoded data output means may output the encoded data in a way obtainable only to a user having finished the charge processing after the charge processing has been finished by the charging means.

50 [0013] The requested information input means may input a predetermined image data in addition to the requested information of a user. The encoded data output means may output the encoded data as a significant information generated when the image is separated into the foreground component image and the background component image by the separating means on the basis of the requested information input by the requested information input means and the predetermined image data, in a way obtainable only to the user having finished the charge processing after the charge processing has been finished by the charging means.

55 [0014] An area information generating means for generating area information for discerning any of a foreground area having foreground object components constituting the foreground object of the predetermined image data, a background area having background object components constituting the background object of the predetermined image

data and a mixed area in which the foreground area and the background area are mixed may be further comprised. The significant information may include the area information and the encoded data output means may output the encoded data as the area information generated when the image is separated into the foreground component image and the background component image by the separating means on the basis of the requested information input by the requested information input means and the predetermined image data, in a way obtainable only to the user after the charge processing has been finished by the charging means.

[0015] A mixture ratio generating means for generating a mixture ratio indicating a ratio in which the foreground area and the background area are mixed in the mixed area of the predetermined image data may be further comprised. The significant information may include the mixture ratio and the encoded data output means may output the encoded data as the mixture ratio generated when the image is separated into the foreground component image and the background component image by the separating means on the basis of the requested information input by the requested information input means and the predetermined image data, in a way obtainable only to the user after the charge processing has been finished by the charging means.

[0016] The separating means may separate a predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming a predetermined image integrated over time, into a foreground component image having foreground object components constituting the foreground object and a background component image having background object components constituting the background object on the basis of the area information and the mixture ratio. The significant information may include the foreground component image and the background component image and the encoded data output means may output the requested information input by the requested information input means and the encoded data as the foreground component image and the background component image generated when the image is separated into the foreground component image and the background component image by the separating means, in a way obtainable only to the user after the charge processing has been finished by the charging means.

[0017] The requested information input means may input an image data ID for discerning a predetermined image data in addition to the requested information of a user, and the encoded data output means may output the encoded data as the significant information generated when the predetermined image is separated into the foreground component image and the background component image by the separating means on the basis of the requested information input by the requested information input means and the predetermined image data corresponding to the image data ID, in a way obtainable only to the user after the charge processing has been finished by the charging means.

[0018] An area information generating means for generating area information for discerning any of a foreground area having foreground object components constituting the foreground object of the predetermined image data corresponding to the image data ID, a background area having background object components constituting the background object of the predetermined image data corresponding to the image data ID and a mixed area in which the foreground area and the background area are mixed may be further comprised. The significant information may include the area information and the encoded data output means may output the encoded data as the area information generated when the predetermined image is separated into the foreground component image and the background component image by the separating means on the basis of the requested information input by the requested information input means and the predetermined image data, in a way obtainable only to the user after the charge processing has been finished by the charging means.

[0019] A mixture ratio generating means for generating a mixture ratio of the mixed area in the predetermined image data corresponding to the image data ID may be further comprised. The significant information may include the mixture ratio and the encoded data output means may output the encoded data as the mixture ratio generated when the predetermined image is separated into the foreground component image and the background component image by the separating means on the basis of the requested information input by the requested information input means and the predetermined image data corresponding to the image data ID, in a way obtainable only to the user after the charge processing has been finished by said charging means.

[0020] The separating means may separate a predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time, into a foreground component image having foreground object components constituting the foreground object and a background component image having background object components constituting the background object on the basis of the area information and the mixture ratio. The significant information may include the foreground component image and the background component image and the encoded data output means may output the requested information input by the requested information input means and the encoded data as the foreground component image and the background component image generated when a predetermined image is separated into the foreground component image and the background component image by the separating means, in a way obtainable only to a user after the charge processing has been finished by the charging means.

[0021] A first communication method of the present invention comprises: a separating step of separating a predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time, into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; a requested information input step of inputting requested information of a user; and an encoded data output step of outputting encoded data generated when an image is separated into the foreground component image and the background component image in the separating step on the basis of the requested information input in the requested information input step.

[0022] A program of a first recording medium of the present invention comprises: a separation control step of controlling separation of an image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time, into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; a requested information input control step of controlling input of requested information of a user; and an encoded data output control step of controlling output of encoded data generated when an image is separated into the foreground component image and the background component image in the separation control step on the basis of the requested information input in the requested information input control step.

[0023] A first program of the present invention makes a computer perform: a separation control step of controlling separation of a predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time, into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; a requested information input control step of controlling input of requested information of a user; and an encoded data output control step of controlling output of encoded data generated when an image is separated into the foreground component image and the background component image in the separation control step on the basis of the requested information input in said requested information input control step.

[0024] In the first communication system, the method thereof and the first program, an image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time is separated into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; requested information of a user is input; and encoded data generated when an image is separated into the foreground component image and the background component image on the basis of the requested information input is output.

Brief Description of the Drawings

[0025]

FIG. 1 is a configuration view of an embodiment of an image processing system to which the present invention is applied;

FIG. 2 is a configuration view of a separation server in FIG. 1;

FIG. 3 is a configuration view of a camera terminal unit in FIG. 1;

FIG. 4 is a functional view of the separation server in FIG. 1;

FIG. 5 is another functional view of the separation server in FIG. 1;

FIG. 6 is a functional view of a motion detecting server in FIG. 1;

FIG. 7 is another functional view of the motion detecting server in FIG. 1;

FIG. 8 is a functional view of an area specifying server in FIG. 1;

FIG. 9 is another functional view of the area specifying server in FIG. 1;

FIG. 10 is a functional view of a mixture ratio calculating server in FIG. 1;

FIG. 11 is another functional view of the mixture ratio calculating server in FIG. 1;

FIG. 12 is a functional view of a foreground/background image separating server in FIG. 1;

FIG. 13 is another functional view of the foreground/background image separating server in FIG. 1;

FIG. 14 is a functional view of a motion blur adjusting server in FIG. 1;

FIG. 15 is another functional view of the motion blur adjusting server in FIG. 1;

FIG. 16 is a functional view of an encoding server in FIG. 1;

FIG. 17 is another functional view of the encoding server in FIG. 1;
 FIG. 18 is a functional view of a storage server in FIG. 1;
 FIG. 19 is another functional view of the storage server in FIG. 1;
 FIG. 20 is a functional view of a synthesizing server in FIG. 1;
 5 FIG. 21 is another functional view of the synthesizing server in FIG. 1;
 FIG. 22 is a functional view of a correcting server in FIG. 1;
 FIG. 23 is another functional view of the correcting server in FIG. 1;
 FIG. 24 is a functional view of a purchasing server in FIG. 1;
 FIG. 25 is a functional view of a selling server in FIG. 1;
 10 FIG. 26 is a functional view of a retrieving server in FIG. 1;
 FIG. 27 is a block diagram showing the separation server;
 FIG. 28 is a diagram illustrating image pickup by a sensor;
 FIG. 29 is a diagram illustrating an arrangement of pixels;
 FIG. 30 is a diagram illustrating operation of a detecting element;
 15 FIG. 31A is a diagram illustrating an image obtained by picking up an image of an object corresponding to a moving foreground and an object corresponding to a stationary background;
 FIG. 31B is another diagram illustrating an image obtained by picking up an image of an object corresponding to a moving foreground and an object corresponding to a stationary background;
 FIG. 32 is a diagram illustrating background area, foreground area, mixed area, covered background area and
 20 uncovered background area;
 FIG. 33 is a modeling diagram in which pixel values of pixels adjacent to each other in a row are expanded in time direction in picking up an image of an object corresponding to a stationary foreground and an object corresponding to a stationary background;
 FIG. 34 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is
 25 divided into a time interval;
 FIG. 35 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 36 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 30 FIG. 37 is a diagram illustrating an example in which pixels of foreground area, background area and mixed area are extracted;
 FIG. 38 is a diagram illustrating relationship of pixels and a model in which pixel values are expanded in the time direction;
 FIG. 39 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is
 35 divided into a time interval;
 FIG. 40 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 41 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 40 FIG. 42 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 43 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 44 is a flowchart illustrating a process of adjusting the amount of motion blur.
 45 FIG. 45 is a block diagram illustrating a configuration example of an area specifying unit 103;
 FIG. 46 is a diagram illustrating an image when an object corresponding to foreground is being moved;
 FIG. 47 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 48 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is
 50 divided into a time interval;
 FIG. 49 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 50 is a diagram illustrating conditions of an area determination;
 FIG. 51A is a diagram illustrating an example of an area specification result in the area specifying unit 103;
 55 FIG. 51B is a diagram illustrating an example of an area specification result in the area specifying unit 103;
 FIG. 51C is a diagram illustrating an example of an area specification result in the area specifying unit 103;
 FIG. 51D is a diagram illustrating an example of an area specification result in the area specifying unit 103;
 FIG. 52 is a diagram illustrating an example of an area specification result in the area specifying unit 103;

FIG. 53 is a flowchart illustrating an area specification processing;
 FIG. 54 is a block diagram of another example of a configuration of the area specifying unit 103;
 FIG. 55 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 5 FIG. 56 is a diagram illustrating an example of a background image;
 FIG. 57 is a block diagram illustrating a configuration of a binary object image extracting portion 302;
 FIG. 58A is a diagram illustrating calculation of correlation value;
 FIG. 58B is a diagram illustrating calculation of correlation value;
 FIG. 59A is a diagram illustrating calculation of correlation value;
 10 FIG. 59B is a diagram illustrating calculation of correlation value;
 FIG. 60 is a diagram illustrating an example of a binary object image;
 FIG. 61 is a block diagram illustrating a configuration of a time change detector 303;
 FIG. 62 is a diagram illustrating a determination in an area determining portion 342;
 FIG. 63 is a diagram illustrating an example of a determination in the time change detector 303;
 15 FIG. 64 is a flowchart illustrating an area specification processing in the area determining unit 103;
 FIG. 65 is a flowchart illustrating details of the area specification processing;
 FIG. 66 is a block diagram of another configuration of the area specifying unit 103;
 FIG. 67 is a block diagram illustrating a configuration of a robust processing portion 361;
 FIG. 68 is a diagram illustrating motion compensation in a motion compensator 381;
 20 FIG. 69 is a diagram illustrating motion compensation in the motion compensator 381;
 FIG. 70 is a flowchart illustrating the area specification processing;
 FIG. 71 is a flowchart illustrating details of a robust processing;
 FIG. 72 is a block diagram illustrating an example of a configuration of a mixture ratio calculating unit 104;
 FIG. 73 is a diagram illustrating an example of an ideal mixture ratio α ;
 25 FIG. 74 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 75 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 76 is a diagram illustrating an approximation using correlation of foreground components;
 30 FIG. 77 is a diagram illustrating the relationship of C, N and P;
 FIG. 78 is a block diagram illustrating a configuration of an estimated mixture ratio processor 401;
 FIG. 79 is a diagram illustrating an example of an estimated mixture ratio;
 FIG. 80 is a block diagram illustrating another configuration of the mixture ratio calculator 104;
 FIG. 81 is a flowchart illustrating a mixture ratio calculation processing;
 35 FIG. 82 is a flowchart illustrating an estimated mixture ratio calculation processing;
 FIG. 83 is a diagram illustrating a linear line approximation of the mixture ratio α ;
 FIG. 84 is a diagram illustrating a plane approximation of the mixture ratio α ;
 FIG. 85 is a diagram illustrating correspondence of pixels in a plurality frames when the mixture ratio α is calculated;
 FIG. 86 is a block diagram illustrating another configuration of the mixture ratio estimating processor 401;
 40 FIG. 87 is a diagram illustrating an example of an estimated mixture ratio;
 FIG. 88 is a flowchart illustrating the mixture ratio estimation processing by using a model corresponding to a covered background area;
 FIG. 89 is a block diagram illustrating an example of a configuration of a foreground/background separator 105;
 FIG. 90A is a diagram showing an input image, a foreground component image and a background component image;
 45 FIG. 90B is a diagram showing an input image, a foreground component image and a background component image;
 FIG. 91 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 50 FIG. 92 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 93 is a modeling diagram in which pixel values are expanded in the time direction and shutter time which is divided into a time interval;
 FIG. 94 is a block diagram illustrating an example of a configuration of a separating portion 601;
 55 FIG. 95A is a diagram showing an example of a foreground component image and a background component image separated;
 FIG. 95B is a diagram showing an example of a foreground component image and a background component image separated;

FIG. 96 is a flowchart illustrating a foreground/background separation processing;
 FIG. 97 is a block diagram showing an example of a configuration of a motion blur adjusting unit 106;
 FIG. 98 is a diagram illustrating a unit of processing;
 FIG. 99 is a modeling diagram in which pixel values of a foreground component image are expanded in the time
 5 direction and shutter time which is divided into a time interval;
 FIG. 100 is a modeling diagram in which pixel values of a foreground component image are expanded in the time
 direction and shutter time which is divided into a time interval;
 FIG. 101 is a modeling diagram in which pixel values of a foreground component image are expanded in the time
 direction and shutter time which is divided into a time interval;
 10 FIG. 102 is a modeling diagram in which pixel values of a foreground component image are expanded in the time
 direction and shutter time which is divided into a time interval;
 FIG. 103 is a diagram showing another configuration of the motion blur adjusting unit 106;
 FIG. 104 is a flowchart illustrating a process of adjusting the amount of motion blur contained in a foreground
 component image in the motion blur adjusting unit (106);
 15 FIG. 105 is a block diagram showing another example of the configuration of the motion blur adjusting unit 106;
 FIG. 106 is a diagram showing an example of a model in which the relationship of pixel values and foreground
 components is specified;
 FIG. 107 is a diagram illustrating a calculation of a foreground component;
 FIG. 108 is a diagram illustrating a calculation of a foreground component;
 20 FIG. 109 is a flowchart illustrating the motion blur elimination processing of a foreground;
 FIG. 110 is a block diagram showing another configuration of a function of the separation server;
 FIG. 111 is a diagram showing a configuration of a synthesizer 1001;
 FIG. 112 is a block diagram showing another configuration of a function of the separation server;
 FIG. 113 is a block diagram showing a configuration of a mixture ratio calculator 1101;
 25 FIG. 114 is a block diagram showing a configuration of a foreground/background separator 1102;
 FIG. 115 is a block diagram showing another configuration of a function of the separation server;
 FIG. 116 is a diagram showing a configuration of a synthesizer 1201;
 FIG. 117 is a flowchart illustrating a separating service;
 FIG. 118 is a flowchart illustrating a charge processing;
 30 FIG. 119 is a diagram illustrating a charge processing;
 FIG. 120 is a flowchart illustrating another example of the charge processing;
 FIG. 121 is a flowchart illustrating a motion detecting service;
 FIG. 122 is a flowchart illustrating an area specifying service;
 FIG. 123 is a flowchart illustrating a mixture ratio calculating service;
 35 FIG. 124 is a flowchart illustrating a foreground/background separating service;
 FIG. 125 is a flowchart illustrating a motion blur adjusting service;
 FIG. 126 is a diagram illustrating an encoding server;
 FIG. 127 is a flowchart illustrating an encoding service;
 FIG. 128 is a diagram illustrating a compressing ability by a means of the encoding processing;
 40 FIG. 129 is a diagram illustrating another example of the encoding server;
 FIG. 130 is a flowchart illustrating a synthesizing service;
 FIG. 131 is a diagram illustrating an encrypting motion blur adding unit;
 FIG. 132 is a diagram illustrating an encrypting motion blur eliminating unit;
 FIG. 133 is a diagram illustrating a process of adding an encrypting motion blur;
 45 FIG. 134 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 135 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 136 is a flowchart illustrating an encryption processing;
 FIG. 137 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 138 is a diagram illustrating a process of adding an encrypting motion blur;
 50 FIG. 139 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 140 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 141 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 142 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 143 is a diagram illustrating a process of adding an encrypting motion blur;
 55 FIG. 144 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 145 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 146 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 147 is a diagram illustrating a process of adding an encrypting motion blur;

FIG. 148 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 149 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 150 is a diagram illustrating a process of adding an encrypting motion blur;
 FIG. 151 is a flowchart illustrating an encrypting service;
 FIG. 152 is a diagram illustrating a correcting server;
 FIG. 153A is a diagram illustrating an adjusting process;
 FIG. 153B is a diagram illustrating an adjusting process;
 FIG. 153C is a diagram illustrating an adjusting process;
 FIG. 153D is a diagram illustrating an adjusting process;
 FIG. 154 is a flowchart illustrating an adjusting process;
 FIG. 155 is a flowchart illustrating a purchasing service;
 FIG. 156 is a flowchart illustrating a selling service;
 FIG. 157 is a flowchart illustrating a charging service;
 FIG. 158 is a diagram illustrating the retrieving server;
 FIG. 159 is a flowchart illustrating a retrieving service; and
 FIG. 160 is a diagram illustrating a retrieving service.

Best Mode for Carrying Out the Invention

[0026]

FIG. 1 is a drawing showing an embodiment of an image processing system according to the present invention.

The image processing system of the present invention is constructed such that a separation server 11, a motion detecting server 12, an area specifying server 13, a mixture ratio calculating server 14, a foreground/background image separating server 15, a motion blur adjusting server 16, an encoding server 17, storage servers 18-1, 18-2, a synthesizing server 19, a correcting server 20, a purchasing server 21, a selling server 22, a retrieving server 23, an account charge server 24, a financial transaction server (for customer) 25, a financial transaction server (for provider) 26, client computers 27 and camera terminal units 28-1 - 28-n are connected over a network 1 such as the Internet to mutually exchange data. The separation server 11, the motion detecting server 12, the area specifying server 13, the mixture ratio calculating server 14, the foreground/background image separating server 15, the motion blur adjusting server 16, the encoding server 17, the synthesizing server 19, the correcting server 20, the purchasing server 21, the selling server 22, the retrieving server 23, the account charge server 24 and the financial transaction servers (for customer and for provider) 25, 26 are managed or administrated by a provider who provides separating service, motion detecting service, area specifying service, mixture ratio calculating service, foreground/background separating service, motion blur adjusting service, encoding service, synthesizing service, correcting service, purchasing service, selling service, retrieval service, charging service and financial transaction services (for client and provider), respectively. Further, in the following description, the storage servers 18-1, 18-2 or the camera terminal units 28-1 to 28-n are simply named the storage server 18 or the camera terminal unit 28 when there is no need to distinguish them. Further, it is true of other servers and units.

FIG. 2 is a configuration view of the separation server 11 of the present invention.

A CPU (Central Processing Unit) 41 performs various kinds of processing in accordance with programs stored in a ROM (Read Only Memory) 42 or a storage unit 48. Data or programs executed by CPU 41 are stored in a RAM (Random Access Memory) 43 as needed. These CPU 41, ROM 42 and RAM 43 are connected to one another via a bus 44.

An input/output interface 45 is connected to CPU 41 via bus 44. An input unit 46 including a keyboard, a mouse, microphone, etc. and an output unit 47 including a display, speakers, etc. are connected to the input/output interface 45. The CPU 41 performs various kinds of processing according to instructions input from the input unit 46. The CPU 41 outputs images, voices, etc. obtained as a result of processing to the output unit 47.

The storage unit 48 connected to the input/output interface 45 comprises, for example, a hard disk and stores programs executed by CPU 41 or various kinds of data. A communication unit 49 communicates with external devices via the Internet or other networks.

Further, programs may be obtained through the communication unit 49 and be stored in a storage unit 48.

When a magnetic disk 61, an optical disk 62, an optical magnetic disk 63, a semiconductor memory, etc. are mounted, a drive 50 connected to the input/output interface 45 drives them to obtain programs or data stored therein. The obtained programs or data are transferred and stored in the storage unit 48 as needed.

Further, since the basic configuration of the motion detecting server 12, the area specifying server 13, the mixture ratio calculating server 14, the foreground/background image separating server 15, the motion blur adjusting server 16, the encoding server 17, the storage servers 18-1, 18-2, the synthesizing server 19, the correcting

server 20, the purchasing server 21, the selling server 22, the retrieving server 23, the account charge server 24, the financial transaction server (for customer) 25, the financial transaction server (for provider) 25 and the client computers 27 are the same as that of the separation server 11, the description thereof will be omitted.

FIG. 3 is a drawing showing a configuration of the camera terminal unit 28 of the present invention. The camera terminal unit 28 is constructed such that a sensor 76a and a GPS (Global Positioning System) 76b are provided in an input unit 76, an LCD (Liquid Crystal Display) 77a is provided in an output unit 77 and the other structures are the same as that of the separation server 11. That is, a CPU 71, a ROM 72, a RAM 73, a bus 74, an input/output interface 75, an input unit 76, an output unit 77, a storage unit 78, a communication unit 79, a drive 80, a magnetic disk 91, an optical disk 92, an optical magnetic disk 93 and a semiconductor memory 94 of the camera terminal unit 28 correspond to the CPU 41, the ROM 42, the RAM 43, the bus 44, the input/output interface 45, the input unit 46, the output unit 47, the storage unit 48, the communication unit 49, the drive 50, the magnetic disk 61, the optical disk 62, the optical magnetic disk 63 and the semiconductor memory 64 of the separation server 11, respectively.

The sensor 76a is an image pickup element and outputs the picked up image to the input unit 76. The GPS 76b detects positional information on earth (latitude and longitude) based on signals transmitted from a stationary satellite (not shown) and outputs the detected positional information to the input unit 76. The LCD 77a displays the image output from the output unit 77.

[0027] Next, referring to FIGs. 4 and 5, the separation server 11 will be described.

[0028] As shown in FIG. 4, the separation server 11 separates an image input from, for example, the client computers 27 via the network 1, into a foreground component image and a background component image by means of the method to be mentioned later, generates ID for the input image, the foreground component image and the background component image and then, outputs them to the client computers 27, stores them in its own storage unit, outputs them to the storage server 18 to be stored, or outputs them to other servers on the network to be stored via the network 1.

Here, the foreground component image means an image having a moving component of the input image and the background component image means an image of stationary part not having the moving component. At this time, a charge processor 11a makes the account charge server 24 perform charge processing for the cost of the separation processing via the network 1. Further, as shown in FIG. 5, if an image ID specifying an image is input in place of an image, the separation server 11 accesses the retrieving server 23 to be described later or the storage server 18 on the network 1 or retrieves its own storage unit (for example, the storage unit 78 of FIG. 3) to read the image data corresponding to the input image ID and separates the image data into a foreground component image and a background component image. Thereafter, the separation server 11 generates ID for each image, which is stored in its own storage unit, or outputs them to other servers on the network 1 so as to perform their respective processing.

[0029] Further, in the following description, the image ID is explained as an example of image specifying information. However, any other information capable of specifying an image, for example, positional information of image to be described later may be used as the image specifying information.

[0030] Next, referring to the FIGs. 6 and 7, the motion detecting server 12 will be explained.

[0031] As shown in FIG. 6, an object extracting unit 12a of the motion detecting server 12 extracts, for example, an image object of image input from the client computer 27, etc. and outputs them to a motion detector 12b. The motion detector 12b detects the motion vector and the positional information of the input image object and then, outputs them to the client computers 27, stores them in its own storage unit or outputs them to other servers on the network 1 so as to perform their respective processing. At this time, a charge processor 12c makes the account charge server 24 perform the charge processing of cost for detecting the motion vector and the positional information of each image object via the network 1. An image that is a target of image pickup and corresponds to an object in the real world is referred to as an object in this specification.

[0032] Also, as shown in FIG. 7, if an image ID specifying an image is input instead of the image, the motion detecting server 12 accesses the retrieving server 23 to be described later or the storage server 18 on the network 1 or retrieves its own storage unit (for example, the storage unit 78 of FIG. 3) to read out the image data corresponding to the input image ID and then, performs the same processing as mentioned above.

[0033] Next, referring to FIGs. 8 and 9, the area specifying server 13 will be explained.

[0034] As shown in FIG. 8, the area specifying server 13 specifies the foreground area, the background area, the mixed area with respect to each pixel of the input image on the basis of an image input from the client computer 27 via the network 1, and object specifying information specifying object of the input image, generates information (hereinafter, referred to as area information) specifying which pixel is included of the foreground area, the background area and the mixed area and then, outputs it to the client computer 27, stores it in its own storage unit or outputs it to other servers on the network 1 so as to perform their respective processing. At this time, a charge processor 13a makes the account charge server 24 perform the charge processing of cost for the area specification processing via the network 1. Further, as shown in FIG. 9, if an image ID specifying an image is input instead of the image, the area specifying

[0044] As shown in FIG. 18, the storage server 18 is connected via the network 1, stores the image transmitted from various kinds of servers, and outputs an image positional information corresponding to the stored image along with an image ID. For example, the client computer 27 can access via the network 1 and call out the desired image using the image positional information. That is, as shown in FIG. 19, for example, the client computer 27 can access the storage server 18 on the network 1 on the basis of the image positional information and read out the desired image by specifying the image ID corresponding to the desired image. Further, the image positional information and the image ID are explained separately in this specification but the image positional information may be a part of the image ID. In this case, the image positional information and the server on the network 1 in which the image positional information is stored (memorized or processed) can be recognized from the image ID. Further, the storage server 18 may store the motion vector, the positional information, the mixture ratio and the amount of motion blur as well as the image data.

[0045] Next, referring to FIGs. 20 and 21, the synthesizing server 19 will be explained.

[0046] As shown in FIG. 20, the synthesizing server 19 synthesizes images A and B by using two images A, B input from, for example, the client computer 27, etc., the motion vector, the positional information, the mixture ratio and the amount of motion blur to generate a synthesized image A+B and then, outputs them to the client computer 27, stores it in its own storage unit or outputs it to other servers on the network so as to perform their respective processing via the network 1. In this case, the images A, B are synthesized by treating one of the images as the foreground component image and the other as the background component image. At this time, a charge processor 19a makes the account charge server 24 perform the charge processing of cost for the synthesizing process via the network 1.

Further, as shown in FIG. 21, if an image A ID and an image B ID specifying the image A and B are input instead of the images A and B, the synthesizing server 19 accesses the retrieving server 23 to be described later, the storage server 18 on the network or retrieves its own storage unit (for example, the storage unit 78 of FIG. 3) to call out the images corresponding to the input image A ID and image B ID and then, performs the same processing as mentioned above.

[0047] Next, referring to FIGs. 22 and 23, the correcting server 20 will be explained.

[0048] As shown in FIG. 22, the correcting server 20 corrects the image input from, for example, the client computer 27, etc. on the basis of the motion vector, the positional information, the mixture ratio and the amount of motion blur, generates and outputs the corrected image to the client computer 27, to store its own storage unit or to other servers on the network 1 so as to perform their respective processing. At this time, the charge processor 20a makes the account charge server 24 perform the charge processing of cost for the correction processing via the network 1. Further, as shown in FIG. 23, if an image ID specifying the image is input instead of the image, the correcting server 20 accesses the retrieving server 23 to be described later or the storage server 18 or retrieves its own storage unit (for example, the storage unit 78 of FIG. 3) to call out the image corresponding to the input image ID and then, performs the same processing as mentioned above.

[0049] Next, referring to FIG. 24, the purchasing server 21 will be explained.

[0050] As shown in FIG. 24, if an image ID specifying an image desired to be purchased is input from, for example, the client computer 27, etc. by a user who wants to purchase the image, the purchasing server 21 accesses the separation server 11, the storage server 18, the synthesizing server 19 or the correcting server 20 on the network 1 to call out the corresponding image and outputs that image to, for example, the client computer 27 via the network. At this time, the charge processor 21a makes the account charge server 24 perform the charge processing of cost for the purchasing processing via the network 1.

[0051] Next, referring to FIG. 25, the selling server 22 will be explained.

[0052] As shown in FIG. 25, if an image which may be a separated image, a synthesized image or a corrected image generated, for example, by means of the separation server 11, the synthesizing server 19 or the correcting server 20 is input via the network 1 by a user who wants to sell the image, the selling server 22 stores the image in the separation server 11, the storage server 18, the synthesizing server 19 or the correcting server 20 on the network 1, and the charge processor 22a makes the account charge server 24 perform the charge processing of cost for the sold image via the network 1 (in this case, the provider of processing of the selling service make the user desiring the sale perform the payment processing of the processing fee corresponding to the sold image).

[0053] Next, referring to FIG. 26, the retrieving server 26 will be explained.

[0054] The retrieving server 26 retrieves an image which is being picked up or has been picked up by the camera terminal units 28-1 to 28-n on the network 1 on the basis of information specifying the features of an image desired by a user from the client computer 27 and the physical positional information of the camera terminal units 28-1 to 28-n to output it to, for example, the client computer 27 as the requested image. At this time, the charge processor 23a makes the account charge server 24 perform the charge processing of cost for the retrieval process via the network 1.

[0055] Further, in this specification, encoding means to convert the image data into data of the foreground component image, the background component image, the motion vector, the positional information, the amount of motion blur and the mixture ratio information, and the data thereof is referred to as encoded data.

[0056] FIG. 27 is a block diagram showing the separation server 11.

[0057] Further, it does not matter whether each function of the separation server 11 is implemented by hardware or software. That is, each block diagram of the present invention may be considered as a block diagram of hardware or as a functional block diagram of software.

[0058] The input image supplied to the separation server 11 is supplied to an object extracting unit 101, an area specifying unit 103, a mixture ratio calculator 104 and a foreground/background separator 105.

[0059] The object extracting unit 101 roughly extracts an image object corresponding to the foreground object of the input image and supplies the extracted image object to the motion detector 102. The object extracting unit 101 detects, for example, the outline of the image object corresponding to the foreground object of the input image and roughly extracts the image object corresponding to the foreground object.

[0060] The object extracting unit 101 roughly extracts an image object corresponding to the background object of the input image and supplies the extracted image object to the motion detector 102. The object extracting unit 101 roughly extracts the image object corresponding to the background object on the basis of, for example, the difference between the input image and the image object corresponding to the extracted foreground object.

[0061] Further, for example, the object extracting unit 101 may roughly extract the image object corresponding to the foreground object and the image object corresponding to the background object on the basis of the difference between the background image stored in an internally provided background memory and the input image.

[0062] The motion detector 102 calculates a motion vector for a roughly extracted image object corresponding to the foreground object by using techniques such as a block matching method, an equally-dividing method, a phase correlating method or a pixel recursive method to supply the calculated motion vector and the positional information of the motion vector (information specifying positions of pixels corresponding to the motion vector) to the area specifying unit 103 and the motion blur adjusting unit 106. The motion vector output from the motion detector 102 includes information corresponding to the amount of movement v .

[0063] Further, for example, the motion detector 102 may output the motion vector of each image object to the motion blur adjusting unit 106 along with the pixel positional information specifying pixels of image object.

[0064] The amount of movement v which indicates the positional variation of the image corresponding to the moving object is expressed in units of pixel interval. For example, when the object image corresponding to the foreground is moved and displayed at a position that is separated by 4 pixels in a frame following a reference frame, the amount of movement v of the object image corresponding to the foreground is 4.

[0065] Further, the object extracting unit 101 and the motion detector 102 are required for adjusting the amount of motion blur corresponding to the moving object.

[0066] The area specifying unit 103 specifies the foreground area, the background area or the mixed area for each pixel of the input image and supplies information indicating the foreground area, the background area or the mixed area for each pixel, to the mixture ratio calculator 104, the foreground/background separator 105 and the motion blur adjusting unit 106.

[0067] The mixture ratio calculator 104 calculates a mixture ratio corresponding to pixels in the mixed area on the basis of the input image and the area information supplied from the area specifying unit 103 and supplies the calculated mixture ratio to the foreground/background separator 105.

[0068] The mixture ratio α is a value indicating a ratio of image component (hereinafter, referred to as background component) corresponding to the background object in pixel values as shown in equation (3) to be described later.

[0069] The foreground/background separator 105 separates the input image into a foreground component image having only the image component (hereinafter, referred to as foreground component) corresponding to the foreground object and a background component image having only the background component on the basis of the area information supplied from the area specifying unit 103 and the mixture ratio α supplied from the mixture ratio calculator 104 to supply the foreground component image to the motion blur adjusting unit 106 and the selector 107. Further, it may be considered that the separated foreground component image is the final output. Compared to the conventional methods where only the foreground and background are specified and separated without considering the mixed area, more accurate foreground and background can be obtained.

[0070] The motion blur adjusting unit 106 determines a unit of processing which specifies one or more pixels in the foreground component image, based on the amount of movement v known from the motion vector and the area information. The unit of processing is a data specifying a group of pixels that is a target of motion blur adjusting process.

[0071] The motion blur adjusting unit 106 adjusts the amount of motion blur in the foreground component image by removing the motion blur in the foreground component image, decreasing the amount of motion blur, increasing the amount of motion blur, etc. based on the amount of motion blur input to the separation server 11, the foreground component image supplied from the foreground/background separator 105, the motion vector and the positional information thereof supplied from the motion detector 102 and the unit of processing, and outputs the foreground component image of which the amount of motion blur is adjusted to the selector 107. The motion vector and the positional information thereof may not be used.

[0072] Here, the motion blur means distortion included in an image corresponding to a moving object, generated by

the motion of object in real society which is a target of picking up an image and by picking up characteristics of sensors.

[0073] The selector 107 selects the foreground component image supplied from the foreground/background separator 105 or the foreground component image supplied from the motion blur adjusting unit 106 of which the amount of motion blur is adjusted, based on, for example, a selection signal corresponding to a selection made by a user and then, outputs the selected foreground component image.

[0074] Next, with reference to FIGs. 28 through 43, an input image supplied to the separation server 11 will be described.

[0075] FIG. 28 is a diagram illustrating an image taken by a sensor 76a. The sensor 76a comprises, for example, a CCD video camera, etc having a CCD (Charge Coupled Device) area sensor that is a solid state image pickup device.

An object 112 corresponding to a foreground in a real world is moved, for example, horizontally from left to right in the drawing between the sensor and an object 111 corresponding to a background in a real world.

[0076] The sensor 76a picks up the image of the object 112 corresponding to the foreground along with the object corresponding to the background. The sensor 76a outputs the picked up in a frame unit. For example, the sensor 76a outputs an image having 30 frames per second. The exposure time of the sensor 76a may be set to 1/30 second. The exposure time means a time interval which starts at the point of converting the input light into charges and ends at the point when the input light has converted into charges. Hereinafter, the exposure time is referred to as a shutter time.

[0077] FIG. 29 is a diagram illustrating an arrangement of pixels. In FIG. 29, 'A' through 'I' indicate the respective pixels. The pixels are arranged on a plane corresponding to an image. A detection element corresponding to one pixel is arranged on the sensor 76a. When the sensor 76a picks up an image, the detection element outputs a pixel value corresponding to one pixel, constituting the image. For example, a position of the detection element in X direction corresponds to a horizontal position on an image and a position of the detection element in Y direction corresponds to a vertical position on an image.

[0078] As shown in FIG. 30, for example, the CCD detection element converts the input light into a charge for the time interval corresponding to the shutter time and stores the converted charge. The amount of charge is approximately proportional to the intensity of input light and time interval when light is input. The detection element adds the charge converted from the input light to the charge already stored for the time interval corresponding to the shutter time. That is, the detection element integrates the input light for the time interval corresponding to the shutter time to store the amount of charge corresponding to the integrated light. The detection element can be mentioned to have integration effect with time.

[0079] The charge stored in the detection element is converted into a voltage value by means of a circuit not shown and the voltage value is converted into a pixel value such as digital data, etc. to be output. Therefore, each pixel value output from the sensor 76a has a value projected to one-dimensional space as a result of integrating some portion having spatial extension of an object corresponding to foreground or background with respect to the shutter time.

[0080] The separation server 11 extracts any significant information, for example, mixture ratio α , hidden in the output signal by means of storing operation of such sensor 76a. The separation server 11 adjusts the amount of distortion, for example, the amount of motion blur resulting from the mixture of the same image object of the foreground. Further, the separation server 11 adjusts the amount of distortion resulting from the mixture of image object of the foreground and image object of the background.

[0081] FIG. 31A through 31D are diagrams showing an image obtained by taking picture of an object corresponding to a moving foreground and an object corresponding to a stationary background. FIG. 31A shows an image obtained by taking picture of an object corresponding to a moving foreground and an object corresponding to a stationary background. In the example shown in FIG. 31A, the object corresponding to the foreground moves horizontally from left to right with respect to the screen.

[0082] FIG. 31B is a model diagram in which the pixel values corresponding to one line of the image shown in FIG. 31A are expanded in the time direction. The horizontal direction in FIG. 31B corresponds to the spatial direction X in FIG. 31A.

[0083] The pixel values of pixels in the background area comprise only the components of the background, that is, the components of the image corresponding to the background object. The pixel values of pixels in the foreground area comprise only the components of the foreground, that is, the components of the image corresponding to the foreground object.

[0084] The pixel values of pixels in the mixed area comprise the components of the background and the components of the foreground. Since the pixel values of pixels in the mixed area comprise the components of the background and the components of the foreground, the mixed area can be mentioned as a distortion area. Further, the mixed area is classified into a covered background area and an uncovered background area.

[0085] The covered background area is a mixed area corresponding to a front end portion in a direction in which the foreground object moves in respect to the foreground area and is an area in which the background components is hidden behind the foreground with time elapsing.

[0086] In contrast, the uncovered background area is a mixed area corresponding to the rear end portion in a direction

in which the foreground object moves in respect to the foreground area and is an area in which the background components appear with time elapsing.

[0087] As such, the image including the foreground area, the background area, the covered background area or the uncovered background area is input to the area specifying unit 103, the mixture ratio calculator 104 and the foreground/background separator 105 as the input image.

[0088] FIG. 32 is a diagram illustrating the background area, the foreground area, the mixed area, the covered background area, and the uncovered background area like above. When an image corresponds to the image shown in FIG. 31A and 31B, the background area is a stationary portion, the foreground area is a moving portion, the covered background area of the mixed area is a portion being changed from the background to the foreground and the uncovered background area of the mixed area is a portion being changed from the foreground to the background.

[0089] FIG. 33 is a model diagram in which the pixel values of pixels being adjacent in a row are expanded in the time direction in the image obtained by picking up an image of an object corresponding to the stationary foreground and an object corresponding to the stationary background. For example, as pixels being adjacent in a row, pixels being adjacent to a line of screen can be selected.

[0090] Pixel values of F01 to F04 shown in FIG. 33 are pixel values of pixels corresponding to a stationary foreground object. Pixel values of B01 to B04 shown in FIG. 33 are pixel values of pixels corresponding to a stationary background object.

[0091] The vertical direction in FIG. 33 corresponds to time and time elapses from the upper side to the lower side in the drawing. The Position at the upper side of the rectangle in FIG. 33 corresponds to a time when the sensor 76a starts to convert of the input light to charges and the position at the lower side of the rectangle in FIG. 33 corresponds to time when the sensor 76a finishes converting the input light into charges. That is, the distance from the upper side to the lower side of the rectangle in FIG. 33 corresponds to a shutter time.

[0092] Now, a case of when the shutter time equals to the frame interval will be explained as an example.

[0093] The horizontal direction in FIG. 33 corresponds to the spatial direction x shown in FIG. 31A. More specifically, in the example shown in FIG. 33, the distance from the left side of rectangle indicated by "F01" to the right side of rectangle indicated by "B04" in FIG. 33 corresponds to 8 times of a pixel pitch, that is, intervals of 8 pixels being continuous.

[0094] When the object of foreground and the object of background are stationary, light to be input to the sensor 76a is not varied for a time interval corresponding to a shutter time.

[0095] Here, the time interval corresponding to the shutter time is divided into two or more equivalent lengths. For example, if a virtual division number is 4, the model diagram shown in FIG. 33 can be shown as the model diagram shown in FIG. 9. The virtual division number is established according to the amount of movement v for the shutter time of the object corresponding to the foreground. For example, if the amount of movement v is defined as 4, the virtual division number is set at 4 and the time interval corresponding to the shutter time is divided into 4 intervals.

[0096] The uppermost row in the drawing corresponds to a first divided time interval after the shutter is opened. The second row from the uppermost in the drawing corresponds to a second divided time interval after the shutter is opened. The third row from the uppermost in the drawing corresponds to a third divided time interval after the shutter is opened. The fourth row from the uppermost in the drawing corresponds to a fourth divided time interval after the shutter is opened.

[0097] Now, the time interval by which the shutter time is divided according to the amount of movement v is referred to as shutter time/v.

[0098] When the object corresponding to the foreground is stationary, since light input to the sensor 76a is not varied, the foreground component F01/v has the same value the pixel value F01 divided by the virtual division number. Similarly, when the object corresponding to the foreground is stationary, the foreground component F02/v has the same value as the pixel value F02 divided by the virtual division number, the foreground component F03/v has the same value as the pixel value F03 divided by the virtual division number and the foreground component F04/v has the same value as the pixel value F04 divided by the virtual division number.

[0099] When the object corresponding to the background is stationary, since light input to the sensor 76a is not varied, the background component B01/v has the same value as the pixel value B01 divided by the virtual division number. Similarly, when the object corresponding to the background is stationary, the background component B02/v has the same value as the pixel value B02 divided by the virtual division number, the background component B03/v has the same value as the pixel value B03 divided by the virtual division number and the background component B04/v has the same value as the pixel value B04 divided by the virtual division number.

[0100] That is, when an object corresponding to the foreground is stationary, since light input to the sensor 76a is not varied for the time interval corresponding to the shutter time, the foreground component F01/v corresponding to a first shutter time/v after the shutter is opened, the foreground component F01/v corresponding to a second shutter time/v after the shutter is opened, the foreground component F01/v corresponding to a third shutter time/v after the shutter is opened and the foreground component F01/v corresponding to a fourth shutter time/v after the shutter is

opened all have the same value. $F02/v$ to $F04/v$ have also the same relation as $F01/v$.

[0101] When an object corresponding to the background is stationary, since light input to the sensor 76a is not varied for the time interval corresponding to the shutter time, the background component $B01/v$ corresponding to a first shutter time/ v after the shutter is opened, the background component $B01/v$ corresponding to a second shutter time/ v after the shutter is opened, the background component $B01/v$ corresponding to a third shutter time/ v after the shutter is opened and the background component $B01/v$ corresponding to a fourth shutter time/ v after the shutter is opened all have the same value. $B02/v$ to $B04/v$ have the same value as $B01/v$.

[0102] Next, a case of when an object corresponding to the foreground is moving and the object corresponding to the background is stationary will be explained.

[0103] FIG. 35 is a model diagram in which when an object corresponding to the foreground is moving toward the right side in the drawing, the pixel values of pixels in a line including the covered background area are developed in the time direction. In FIG. 35, the amount of movement v of the foreground is 4. Since one frame corresponds to a short time, it can be supposed that the object corresponding to the foreground is a rigid body and is moving at a uniform speed. In FIG. 35, an image of the object corresponding to the foreground is moving to be displayed at position displaced by 4 pixels in a frame following a reference frame.

[0104] In FIG. 35, the pixels from the leftmost to the fourth from the leftmost belong to the foreground. In FIG. 35, the pixels from the fifth from the leftmost to the seventh from the leftmost belong to the mixed area that is the covered background area. In FIG. 35, the rightmost pixel belongs to the background area.

[0105] Since the object corresponding to the foreground is moving to cover the object corresponding to the background with time elapsing, the components included in the pixel values of pixels belonging to the covered background area is changed from the background components to the foreground components at certain time point of the time interval corresponding to the shutter time.

[0106] For example, the pixel values M of which edge is a bold line in FIG. 35 is expressed as equation (1).

$$M = B02/v + B02/v + F07/v + F06/v \quad (1)$$

[0107] For example, since the fifth pixel from the leftmost includes the background component corresponding to a first shutter time/ v and the foreground component corresponding to a third shutter time/ v , the mixture ratio α of the fifth pixel from the leftmost is $1/4$. Since the sixth pixel from the leftmost includes the background component corresponding to a second shutter time/ v and the foreground component corresponding to the second shutter time/ v , the mixture ratio α of the sixth pixel from the leftmost is $1/2$. Since the seventh pixel from the leftmost includes the background component corresponding to the third shutter time/ v and the foreground component corresponding to the first shutter time/ v , the mixture ratio α of the seventh pixel from the leftmost is $3/4$.

[0108] Since it can be supposed that the object corresponding to the foreground is a rigid body and the foreground image is moving at a uniform speed to be displayed at a position displaced to the right by 4 pixels in a next frame, for example, the foreground component $F07/v$, of the fourth pixel from the leftmost in FIG. 35, corresponding to the first shutter time/ v after the shutter is opened is the same as the foreground component of the fifth pixel from the leftmost in FIG. 35, corresponding to the second shutter time/ v after the shutter is opened. Similarly, the foreground component $F07/v$ is the same as the foreground component of the sixth pixel from the leftmost in FIG. 35 corresponding to the third shutter time/ v after the shutter is opened and the foreground component of the seventh pixel from the leftmost in FIG. 35 corresponding to the fourth shutter time/ v after the shutter is opened, respectively.

[0109] Since it can be supposed that the object corresponding to the foreground is a rigid body and the foreground image is moving at a uniform speed to be displayed at a position displaced to the right by 4 pixels in a next frame, for example, the foreground component $F06/v$ of the third pixel from the leftmost in FIG. 35 corresponding to the first shutter time/ v after the shutter is opened is the same as the foreground component of the fourth pixel from the leftmost in FIG. 35 corresponding to the second shutter time/ v after the shutter is opened. Similarly, the foreground component $F06/v$ is the same as the foreground component of the fifth pixel from the leftmost in FIG. 35 corresponding to the third shutter time/ v after the shutter is opened and the foreground component of the sixth pixel from the leftmost in FIG. 35 corresponding to the fourth shutter time/ v after the shutter is opened, respectively.

[0110] Since it can be supposed that the object corresponding to the foreground is a rigid body and the foreground image is moving at a uniform speed to be displayed at a position displaced to the right by 4 pixels in a next frame, for example, the foreground component $F05/v$ of the second pixel from the leftmost in FIG. 35 corresponding to the first shutter time/ v after the shutter is opened is the same as the foreground component of the third pixel from the leftmost in FIG. 35 corresponding to the second shutter time/ v after the shutter is opened. Similarly, the foreground component $F05/v$ is the same as the foreground component of the fourth pixel from the leftmost in FIG. 35 corresponding to the third shutter time/ v after the shutter is opened and the foreground component of the fifth pixel from the leftmost in FIG. 35 corresponding to the fourth shutter time/ v after the shutter is opened, respectively.

[0111] Since it can be supposed that the object corresponding to the foreground is a rigid body and the foreground image is moving at a uniform speed to be displayed at a position displaced to the right by 4 pixels in a next frame, for example, the foreground component F_{04}/v of the leftmost pixel in FIG. 35 corresponding to the first shutter time v after the shutter is opened is the same as the foreground component of the second pixel from the leftmost in FIG. 35 corresponding to the second shutter time v after the shutter is opened. Similarly, the foreground component F_{04}/v is the same as the foreground component of the third pixel from the leftmost in FIG. 35 corresponding to the third shutter time v after the shutter is opened and the foreground component of the fourth pixel from the leftmost in FIG. 35 corresponding to the fourth shutter time v after the shutter is opened, respectively.

[0112] The foreground area corresponding to a moving object may be mentioned as a distortion area because it includes the motion blur as described by the above.

[0113] FIG. 36 is a model diagram in which when the foreground is moving toward the right side in the drawing, the pixel values of pixels in a line including the uncovered background area are expanded in the time direction. In FIG. 36, the amount of movement v of the foreground is 4. Since one frame corresponds to a short time, it can be supposed that an object corresponding to the foreground is a rigid body and is moving at a uniform speed. In FIG. 36, an image of the object corresponding to the foreground is moving toward the right side by 4 pixels in a next frame.

[0114] In FIG. 36, pixels from the leftmost to the fourth from the leftmost belong to the background area. In FIG. 36, pixels from the fifth from the leftmost to the seventh from the leftmost belong to the mixed area that is the uncovered background area. In FIG. 36, the rightmost pixel belongs to the background area.

[0115] Since the object corresponding to the foreground covering the object corresponding to the background is moving to be displaced from the object corresponding to the background with time elapsing, the components included in the pixel values of pixels belonging to the uncovered background area is changed from the foreground components to the background components at certain time point of the time interval corresponding to the shutter time.

[0116] For example, the pixel values M' of which edge is a bold line in FIG. 36 is expressed as equation (2).

$$M' = F_{02}/v + F_{01}/v + B_{26}/v + B_{26}/v \quad (2)$$

[0117] For example, since the fifth pixel from the leftmost includes the background component corresponding to a third shutter time v and the foreground component corresponding to a first shutter time v , the mixture ratio α of the fifth pixel from the leftmost is $3/4$. Since the sixth pixel from the leftmost includes the background component corresponding to a second shutter time v and the foreground component corresponding to the second shutter time v , the mixture ratio α of the sixth pixel from the leftmost is $1/2$. Since the seventh pixel from the leftmost includes the background component corresponding to the first shutter time v and the foreground component corresponding to the third shutter time v , the mixture ratio α of the seventh pixel from the leftmost is $1/4$.

[0118] More generalizing combining equation (1) and equation (2), the pixel value M can also be expressed by equation (3).

$$M = \alpha \cdot B + \sum_i F_i/v \quad (3)$$

[0119] Here, α is a mixture ratio. B is a pixel value of the background and F_i/v is a foreground component.

[0120] Since it can be supposed that the object corresponding to the foreground is a rigid body and is moving at a uniform speed and the amount of movement v is 4, for example, the foreground component F_{01}/v of the fifth pixel from the leftmost in FIG. 36 corresponding to the first shutter time v after the shutter is opened is the same as the foreground component of the sixth pixel from the leftmost in FIG. 36 corresponding to the second shutter time v after the shutter is opened. Similarly, the foreground component F_{01}/v is the same as the foreground component of the seventh pixel from the leftmost in FIG. 36 corresponding to the third shutter time v after the shutter is opened and the foreground component of the eighth pixel from the leftmost in FIG. 36 corresponding to the fourth shutter time v after the shutter is opened, respectively.

[0121] Since it can be supposed that the object corresponding to the foreground is a rigid body and is moving at a uniform speed and the virtual division number is 4, for example, the foreground component F_{02}/v of the sixth pixel from the leftmost in FIG. 36 corresponding to the first shutter time v after the shutter is opened is the same as the foreground component of the seventh pixel from the leftmost in FIG. 36 corresponding to the second shutter time v after the shutter is opened. Similarly, the foreground component F_{02}/v is the same as the foreground component of the eighth pixel from the leftmost in FIG. 36 corresponding to the third shutter time v after the shutter is opened.

[0122] Since it can be supposed that the object corresponding to the foreground is a rigid body and is moving at an

uniform speed and the amount of movement v is 4, for example, the foreground component $F03/v$ of the seventh pixel from the leftmost in FIG. 36 corresponding to the first shutter time/ v after the shutter is opened is the same as the foreground component of the eighth pixel from the leftmost in FIG. 36 corresponding to the second shutter time/ v after the shutter is opened.

[0123] In the explanations of FIG. 34 to 36, it has been explained that the virtual division number is 4, however the virtual division number corresponds to the amount of movement v . The amount of movement v usually corresponds to the moving speed of an object corresponding to the foreground. For example, when an object corresponding to the foreground is moving to be displayed at position 4 pixels to the right in a frame following a reference frame, the amount of movement v is defined as 4. In accordance to the amount of movement v , the virtual division number is set at 4. Similarly, for example, when an object corresponding to the foreground is moving to be displayed at a position 6 pixels to the right in a frame following a reference frame, the amount of movement v is defined as 6 and the virtual division number is set at 6.

[0124] FIGS. 37 and 38 show a relationship between the foreground area, the background area, the mixed area having the covered background area and the uncovered background area and the foreground component or the background component corresponding to the divided shutter time.

[0125] FIG. 37 shows an example in which the pixels of the foreground area, the background area and the mixed area are extracted from an image including the foreground corresponding to the object moving in front of the stationary background. In an example shown in FIG. 37, an object A corresponding to the foreground is moving horizontally with respect to the screen.

[0126] A frame $\#n+1$ is a frame next to a frame $\#n$ and a frame $\#n+2$ is a frame next to the frame $\#n+1$.

[0127] A model in which the pixels of the foreground area, the background area and the mixed area extracted from one of the frame $\#n$ to the frame $\#n+2$ and the pixel values of the extracted pixels are expanded in the time direction with the amount of movement v being 4 is shown in FIG. 38.

[0128] Since the object A corresponding to the foreground is moving, the pixel values of the foreground area comprise 4 different foreground components according to intervals of a shutter time/ v . For example, the leftmost pixel in the foreground area shown in FIG. 38 comprises $F01/v$, $F02/v$, $F03/v$ and $F04/v$. That is, the pixels of the foreground area include the motion blur.

[0129] Since an object corresponding to the background is stationary, the light corresponding to the background input to the sensor 76a for the time interval corresponding to the shutter time does not change. In this case, the pixel values of the background area do not include the motion blur.

[0130] The pixel values of pixels belonging to the mixed area containing the covered background area or the uncovered background area is comprised the foreground components and the background components.

[0131] Next, a model will be explained that when an image corresponding to an object is moving, the pixel values of pixels are adjacent in one row in a plurality of frames and are at the same positions in the frames are expanded in the time direction. For example, when the image corresponding to the object is moving horizontally with respect to the screen, the pixels being in one line on the screen can be selected as pixels being adjacent in one row.

[0132] FIG. 39 is a model diagram in which the pixel values of pixels are expanded in the time direction, wherein the pixel values of pixels which are adjacent in one row in 3 frames of an image obtained by picking up an image of an object corresponding to the stationary background and are at the same positions in the frames. A frame $\#n$ is a frame following a frame $\#n-1$ and a frame $\#n+1$ is a frame following the frame $\#n$. Other frames are referred in the same manner.

[0133] The pixel values of $B01$ to $B12$ shown in FIG. 39 are the pixel values corresponding to the object of the stationary background. Since the object corresponding to the background is stationary, the pixel values of the corresponding pixels do not changed in the frame $\#n-1$ to the frame $\#n+1$. For example, a pixel in the frame $\#n$ and a pixel in the frame $\#n+1$ corresponding to the position of pixel having the pixel value of $B05$ in the frame $\#n-1$ have the same pixel value of $B05$, respectively.

[0134] FIG. 40 is a model diagram in which the pixel values of pixels are expanded in the time direction, wherein the pixel values of pixels are adjacent in one row in 3 frames of an image obtained by picking up an image of an object corresponding to the foreground moving toward the right side in the drawing along with an object corresponding to the stationary background and are at the same positions in the frames. The model shown in FIG. 40 includes the covered background area.

[0135] In FIG. 40, since it can be supposed that the object corresponding to the foreground is a rigid body and is moving at an uniform speed and the foreground image is moving to be displayed displaced to the right by 4 pixels in a next frame, the amount of movement v of the foreground is defined as 4 and the virtual division number is set at 4.

[0136] For example, the foreground component of the leftmost pixel of a frame $\#n-1$ in FIG. 40 corresponding to a first shutter time/ v after the shutter is opened is $F12/v$, and the foreground component of the second pixel from the leftmost in FIG. 40 corresponding to a second shutter time/ v after the shutter is opened is also $F12/v$. Similarly, the foreground component of the third pixel from the leftmost in FIG. 40 corresponding to a third shutter time/ v after the

shutter is opened and the foreground component of the fourth pixel from the leftmost in FIG. 40 corresponding to a fourth shutter time/v after the shutter is opened are F12/v.

[0137] The foreground component of the leftmost pixel of the frame #n-1 in FIG. 40 corresponding to the second shutter time/v after the shutter is opened is F11/v, and the foreground component of the second pixel from the leftmost in FIG. 40 corresponding to the third shutter time/v after the shutter is opened is also F11/v. The foreground component of the third pixel from the leftmost in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened is F11/v.

[0138] The foreground component of the leftmost pixel of the frame #n-1 in FIG. 40 corresponding to the third shutter time/v after the shutter is opened is F10/v, and the foreground component, of the second pixel from the leftmost in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened is also F10/v. The foreground component of the leftmost pixel of the frame #n-1 in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened is F09/v.

[0139] Since an object corresponding to the background is stationary, the background component of the second pixel from the leftmost of the frame #n-1 in FIG. 40 corresponding to the first shutter time/v after the shutter is opened is B01/v. The background components of the third pixel from the leftmost of the frame #n-1 in FIG. 40 corresponding to the first and the second shutter time/v after the shutter is opened are B02/v. The background components of the fourth pixel from the leftmost of the frame #n-1 in FIG. 40 corresponding to the first to third shutter time/v after the shutter is opened are B03/v.

[0140] In the frame #n-1 of FIG. 40, the leftmost pixel corresponds to the foreground area and the second to fourth pixels from the leftmost belong to the mixed area that is the covered background area.

[0141] The fifth to twelfth pixels from the leftmost of the frame #n-1 in FIG. 40 belong to the background area and the pixel values thereof are B04 to B11, respectively.

[0142] The first to fifth pixels from the leftmost of a frame #n in FIG. 40 belong to the foreground area. In the foreground area of the frame #n, the foreground component of the shutter time/v is one of F05/v to F12/v.

[0143] Since it can be supposed that the object corresponding to the foreground is a rigid body and is moving at a uniform speed and the foreground image is moving to be displayed displaced to the right by 4 pixels in a next frame, the foreground component of the fifth pixel from the leftmost of the frame #n in FIG. 40 corresponding to the first shutter time/v after the shutter is opened is F12/v, and the foreground component of the sixth pixel from the leftmost in FIG. 40 corresponding to the second shutter time/v after the shutter is opened is also F12/v. Similarly, the foreground component of the seventh pixel from the leftmost in FIG. 40 corresponding to the third shutter time/v after the shutter is opened and the foreground component of the eighth pixel from the leftmost in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened are F12/v.

[0144] The foreground component of the fifth pixel from the leftmost of the frame #n in FIG. 40 corresponding to the second shutter time/v after the shutter is opened is F11/v, and the foreground component of the sixth pixel from the leftmost in FIG. 40 corresponding to the third shutter time/v after the shutter is opened is also F11/v. The foreground component of the seventh pixel from the leftmost in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened is F11/v.

[0145] The foreground component of the fifth pixel from the leftmost of the frame #n in FIG. 40 corresponding to the third shutter time/v after the shutter is opened is F10/v, and the foreground component of the sixth pixel from the leftmost in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened is also F10/v. The foreground component of the fifth pixel from the leftmost of the frame #n in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened is F09/v.

[0146] Since the object corresponding to the background is stationary, the background component of the sixth pixel from the leftmost of the frame #n in FIG. 40 corresponding to the first shutter time/v after the shutter is opened is B05/v. The background components of the seventh pixel from the leftmost of the frame #n in FIG. 40 corresponding to the first and the second shutter time/v after the shutter is opened are B06/v. The background components of the eighth pixel from the leftmost of the frame #n in FIG. 40 corresponding to the first to third shutter time/v after the shutter is opened are B07/v.

[0147] In the frame #n in FIG. 40, the sixth to eighth pixels from the leftmost belong to the mixed area that is the covered background area.

[0148] The ninth to twelfth pixels from the leftmost of the frame #n in FIG. 40 belong to the background area and the pixel values thereof are B08 to B11, respectively.

[0149] The first to ninth pixels from the leftmost of a frame #n+1 in FIG. 40 belong to the foreground area. In the foreground area of the frame #n+1, the foreground component corresponding to the shutter time/v is one of F01/v to F12/v.

[0150] Since it can be supposed that the object corresponding to the foreground is a rigid body and is moving at a uniform speed and the foreground image is moving to be displayed displaced to the right by 4 pixels in a next frame, the foreground component of the ninth pixel from the leftmost of the frame #n+1 in FIG. 40 corresponding to the first shutter time/v after the shutter is opened is F12/v, and the foreground component of the tenth pixel from the leftmost

in FIG. 40 corresponding to the second shutter time/v after the shutter is opened is also F12/v. The foreground component of the eleventh pixel from the leftmost in FIG. 40 corresponding to the third shutter time/v after the shutter is opened and the foreground component of the twelfth pixel from the leftmost in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened are F12/v.

5 [0151] The foreground component of the ninth pixel from the leftmost of the frame #n+1 in FIG. 40 corresponding to the second shutter time/v after the shutter is opened is F11/v, and the foreground component of the tenth pixel from the leftmost in FIG. 40 corresponding to the third shutter time/v after the shutter is opened is also F11/v. The foreground component, of the eleventh pixel from the leftmost in FIG. 40, corresponding to the fourth shutter time/v after the shutter is opened is F11/v.

10 [0152] The foreground component of the ninth pixel from the leftmost of the frame #n+1 in FIG. 40 corresponding to the third shutter time/v after the shutter is opened is F10/v, and the foreground component of the tenth pixel from the leftmost in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened is also F10/v. The foreground component of the ninth pixel from the leftmost of the frame #n+1 in FIG. 40 corresponding to the fourth shutter time/v after the shutter is opened is F09/v.

15 [0153] Since the object corresponding to the background is stationary, the background component of the tenth pixel from the leftmost of the frame #n+1 in FIG. 40 corresponding to the first shutter time/v after the shutter is opened is B09/v. The background components of the eleventh pixel from the leftmost of the frame #n+1 in FIG. 40 corresponding to the first and the second shutter time/v after the shutter is opened are B10/v. The background components of the twelfth pixel from the leftmost of the frame #n+1 in FIG. 40 corresponding to the first to third shutter time/v after the shutter is opened are B11/v.

20 [0154] In the frame #n+1 of FIG. 40, the tenth to twelfth pixels from the leftmost belong to the mixed area that is the covered background area.

[0155] FIG. 41 is a model diagram of an image obtained by extracting the foreground components from the pixel values shown in FIG. 40.

25 [0156] FIG. 42 is a model diagram in which the pixel values of pixels are expanded in the time direction, wherein the pixel values of pixels are adjacent in one row in 3 frames of an image obtained by picking up an image of an object corresponding to the foreground moving toward the right side in the drawing along with the stationary background and are at the same positions in the frames. In FIG. 42, the uncovered background area is included.

[0157] In FIG. 42, it can be supposed that the object corresponding to the foreground is a rigid body and is moving at a uniform speed. Since the object corresponding to the foreground is moving to be displayed displaced to the right by 4 pixels in a next frame, the amount of movement v of the foreground is defined as 4.

30 [0158] For example, the foreground component of the leftmost pixel of a frame #n-1 in FIG. 42 corresponding to a first shutter time/v after the shutter is opened is F13/v, and the foreground component of the second pixel from the leftmost in FIG. 42 corresponding to a second shutter time/v after the shutter is opened is also F13/v. The foreground component of the third pixel from the leftmost in FIG. 42 corresponding to a third shutter time/v after the shutter is opened and the foreground component of the fourth pixel from the leftmost in FIG. 42 corresponding to a fourth shutter time/v after the shutter is opened are F13/v.

35 [0159] The foreground component of the second pixel from the leftmost of the frame #n-1 in FIG. 42 corresponding to the first shutter time/v after the shutter is opened is F14/v, and the foreground component of the third pixel from the leftmost in FIG. 42 corresponding to the second shutter time/v after the shutter is opened is also F14/v. The foreground component of the third pixel from the leftmost in FIG. 42 corresponding to the first shutter time/v after the shutter is opened is F15/v.

40 [0160] Since an object corresponding to the background is stationary, the background components of the leftmost pixel of the frame #n-1 in FIG. 42 corresponding to the second to fourth shutter time/v after the shutter is opened are B25/v. The background components of the second pixel from the leftmost of the frame #n-1 in FIG. 42 corresponding to the third and fourth shutter time/v after the shutter is opened are B26/v. The background component of the third pixel from the leftmost of the frame #n-1 in FIG. 42 corresponding to the fourth shutter time/v after the shutter is opened is B27/v.

45 [0161] In the frame #n-1 of FIG. 42, the first, second and third pixels from the leftmost belong to the mixed area that is the uncovered background area.

[0162] The fourth to twelfth pixels from the leftmost in the frame #n-1 in FIG. 42 belong to the foreground. The foreground components of the frame are one of F13/v to F24/v.

[0163] The first, second, third and fourth pixels from the leftmost in the frame #n in FIG. 42 belong to the background area and the pixel values thereof are B25 to B28, respectively.

50 [0164] Since it can be supposed that the object corresponding to the foreground is a rigid body and is moving at a uniform speed and the foreground image is moving to be displayed displaced to the right by 4 pixels in a next frame, the foreground component of the fifth pixel from the leftmost of the frame #n in FIG. 42 corresponding to the first shutter time/v after the shutter is opened is F13/v, and the foreground component of the sixth pixel from the leftmost in FIG.

42 corresponding to the second shutter time/v after the shutter is opened is also F13/v. The foreground component of the seventh pixel from the leftmost in FIG. 42 corresponding to the third shutter time/v after the shutter is opened and the foreground component of the eighth pixel from the leftmost in FIG. 42 corresponding to the fourth shutter time/v after the shutter is opened are F13/v.

[0165] The foreground component of the sixth pixel from the leftmost of the frame #n in FIG. 42 corresponding to the first shutter time/v after the shutter is opened is F14/v, and the foreground component of the seventh pixel from the leftmost in FIG. 42 corresponding to the second shutter time/v after the shutter is opened is also F14/v. The foreground component of the eighth pixel from the leftmost in FIG. 42 corresponding to the first shutter time/v after the shutter is opened is F15/v.

[0166] Since the object corresponding to the background is stationary, the background components of the fifth pixel from the leftmost of the frame #n in FIG. 42 corresponding to the second to the fourth shutter time/v after the shutter is opened are B29/v. The background components of the sixth pixel from the leftmost of the frame #n in FIG. 42 corresponding to the third and the fourth shutter time/v after the shutter is opened are B30/v. The background components of the seventh pixel from the leftmost of the frame #n in FIG. 42 corresponding to the fourth shutter time/v after the shutter is opened are B31/v.

[0167] In the frame #n of FIG. 42, the fifth to seventh pixels from the leftmost belong to the mixed area that is the uncovered background area.

[0168] The eighth to twelfth pixels from the leftmost of the frame #n in FIG. 42 belong to the foreground area. In the foreground area of the frame #n, the values corresponding to the shutter time/v are one of F13/v to F20/v.

[0169] The leftmost to eighth pixels from the leftmost of a frame #n+1 in FIG. 42 belong to the background area, and the pixel values thereof are B25 to B32, respectively.

[0170] Since it can be supposed that the object corresponding to the foreground is a rigid body and is moving at an uniform speed and the foreground image is moving to be displayed displaced to the right by 4 pixels in a next frame, the foreground component of the ninth pixel from the leftmost of the frame #n+1 in FIG. 42 corresponding to the first shutter time/v after the shutter is opened is F13/v, and the foreground component of the tenth pixel from the leftmost in FIG. 42 corresponding to a second shutter time/v after the shutter is opened is also F13/v. The foreground component of the eleventh pixel from the leftmost in FIG. 42 corresponding to the third shutter time/v after the shutter is opened and the foreground component of the twelfth pixel from the leftmost in FIG. 42 corresponding to the fourth shutter time/v after the shutter is opened are F13/v.

[0171] The foreground component of the tenth pixel from the leftmost of the frame #n+1 in FIG. 42 corresponding to the first shutter time/v after the shutter is opened is F14/v, and the foreground component of the eleventh pixel from the leftmost in FIG. 42 corresponding to the second shutter time/v after the shutter is opened is also F14/v. The foreground component of the twelfth pixel from the leftmost in FIG. 42, corresponding to the first shutter time/v after the shutter is opened is F15/v.

[0172] Since the object corresponding to the background is stationary, the background components of the ninth pixel from the leftmost of the frame #n+1 in FIG. 42 corresponding to the second to the fourth shutter time/v after the shutter is opened are B33/v. The background components of the tenth pixel from the leftmost of the frame #n+1 in FIG. 42 corresponding to the third and the fourth shutter time/v after the shutter is opened are B34/v. The background component of the eleventh pixel from the leftmost of the frame #n+1 in FIG. 42 corresponding to the fourth shutter time/v after the shutter is opened is B35/v.

[0173] In the frame #n+1 of FIG. 42, the ninth to eleventh pixels from the leftmost belong to the mixed area that is the uncovered background area.

[0174] The twelfth pixel from the leftmost of the frame #n+1 in FIG. 42 belongs to the foreground. In the foreground area of the frame #n+1, the foreground components corresponding to the shutter time/v are one of F13/v to F16/v.

[0175] FIG. 43 is a model diagram of an image obtained by extracting the foreground components from the pixel values shown in FIG. 42.

[0176] Returning to FIG. 27, the area specifying unit 103 generates flags indicating which of the foreground area, the background area, the covered background area or the uncovered background area correspond to the respective pixels, using a plurality of pixel values, and then, supplies them to the mixture ratio calculator 104 and the motion blur adjusting unit 106 as the area information.

[0177] The mixture ratio calculator 104 calculates the mixture ratios α for each pixel included in the mixed area on the basis of the pixel values from a plurality of frames and the area information, and supplies the calculated mixture ratio α to the foreground/background separator 105.

[0178] The foreground/background separator 105 extracts the foreground component image having only the foreground components on the basis of the pixel values from a plurality of frames, the area information and the mixture ratio α and supplies it to the motion blur adjusting unit 106.

[0179] The motion blur adjusting unit 106 adjusts the amount of motion blur included in the foreground component image on the basis of the foreground component image supplied from the foreground/background separator 105, the

[0199] The area determining portion 203-2 supplies the stationary area determining flag to which "1" or "0" is set as described by the above to the frame memory storing determining flag 204.

[0200] When the stationary/moving determination supplied from the stationary/moving determining portion 202-2 indicates motion status and the stationary/moving determination supplied from the stationary/moving determining portion 202-3 indicates motion status, the area determining portion 203-2 determines that the pixel being a target of the area specification in the frame #n belongs to the moving area and sets "1" indicating that the pixel belongs to the moving area to the moving area determining flag corresponding to the pixel of which area is determined.

[0201] When the stationary/moving determination supplied from the stationary/moving determining portion 202-2 indicates stationary status or the stationary/moving determination supplied from the stationary/moving determining portion 202-3 indicates stationary status, the area determining portion 203-2 determines that the pixel being a target of the area specification in the frame #n does not belong to the moving area and sets "0" indicating that the pixel does not belong to the moving area to the moving area determining flag corresponding to the pixel of which area is determined.

[0202] The area determining portion 203-2 supplies the moving area determining flag to which "1" or "0" is set as described by the above to the frame memory storing determining flag 204.

[0203] When the stationary/moving determination supplied from the stationary/moving determining portion 202-3 indicates motion status and the stationary/moving determination supplied from the stationary/moving determining portion 202-4 indicates stationary status, the area determining portion 203-3 determines that the pixel being a target of the area specification in the frame #n belongs to the covered background area and sets "1" indicating that the pixel belongs to the covered background area to the covered background area determining flag corresponding to the pixel of which area is determined.

[0204] When the stationary/moving determination supplied from the stationary/moving determining portion 202-3 indicates stationary status or the stationary/moving determination supplied from the stationary/moving determining portion 202-4 indicates motion status, the area determining portion 203-2 determines that the pixel being a target of the area specification in the frame #n does not belong to the covered background area and sets "0" indicating that the pixel does not belong to the covered background area to the covered background area determining flag corresponding to the pixel of which area is determined.

[0205] The area determining portion 203-3 supplies the covered background area determining flag to which "1" or "0" is set as described by the above to the frame memory storing determining flag 204.

[0206] The frame memory storing determining flag 204 stores the uncovered background area determining flag supplied from the area determining portion 203-1, the stationary area determining flag supplied from the area determining portion 203-2, the moving area determining flag supplied from the area determining portion 203-2 and the covered background area determining flag supplied from the area determining portion 203-3, respectively.

[0207] The frame memory storing determining flag 204 supplies the uncovered background area determining flag, the stationary area determining flag, the moving area determining flag and the covered background area determining flag stored therein to a synthesizer 205. The synthesizer 205 generates the area information indicating that each pixel belongs to any of the uncovered background area, the stationary area, the moving area and the covered background area on the basis of the uncovered background area determining flag, the stationary area determining flag, the moving area determining flag and the covered background area determining flag supplied from the frame memory storing determining flag 204 and then supplies it to the frame memory storing determining flag 206.

[0208] The frame memory storing determining flag 206 stores the area information supplied from the synthesizer 205 and outputs the stored area information.

[0209] Next, referring to FIGs. 46 to 50, an example of processing by the area specifying unit 103 will be explained.

[0210] When the object corresponding to the foreground is moving, the position on the screen of the image corresponding to the object varies every frame. As shown in FIG. 46, the image corresponding to the object located at a position indicated by $Y_n(x, y)$ in the frame #n is located at $Y_{n+1}(x, y)$ in the frame #n+1.

[0211] FIG. 22 is a model diagram in which the pixel values of pixels being adjacent in a row in the moving direction of the image corresponding to the foreground object are expanded in the time direction. For example, when the moving direction of the image corresponding to the foreground object is horizontal on the screen, the model diagram in FIG. 47 shows a model in which the pixel values of pixels being adjacent in one line are developed in the time direction.

[0212] In FIG. 47, the lines in the frame #n are the same as those in the frame #n+1.

[0213] The foreground components corresponding to the object included in the second to the thirteenth pixels from the leftmost in the frame #n are included in the sixth to the seventeenth pixels from the leftmost in the frame #n+1.

[0214] In the frame #n, pixels belonging to the covered background area are the eleventh to thirteenth pixels from the leftmost and pixels belonging to the uncovered background area are the second to fourth pixels from the leftmost. In the frame #n+1, pixels belonging to the covered background area are the fifteenth to seventeenth pixels from the leftmost and pixels belonging to the uncovered background area are the sixth to eighth pixels from the leftmost.

[0215] In the example shown in FIG. 47, since the foreground components included in the frame #n is moved by 4

pixels in the frame #n+1, the amount of movement v is defined as 4. The virtual division number is set at 4 corresponding to the amount of movement v .

[0216] Next, variation of the pixel values of pixels belonging to the mixed area in front or back of the indicated frame will be explained.

[0217] In the frame #n that is shown in FIG. 48 and in which the background is stationary and the amount of movement v of the foreground is 4, pixels belonging to the covered background area are the fifteenth to seventeenth pixels from the leftmost. Since the amount of movement v is 4, the fifteenth to seventeenth pixels in the frame #n-1 one frame ahead include only the background components and belong to the background area. Further, the fifteenth to seventeenth pixels in the frame #n-2 further one frame ahead include only the background components and belong to the background area.

[0218] Here, since the object corresponding to the background is stationary, the pixel value of the fifteenth pixel from the leftmost in the frame #n-1 is not changed from the pixel value of the fifteenth pixel from the leftmost in the frame #n-2. Similarly, the pixel value of the sixteenth pixel from the leftmost in the frame #n-1 is not changed from the pixel value of the sixteenth pixel from the leftmost in the frame #n-2 and the pixel value of the seventeenth pixel from the leftmost in the frame #n-1 is not changed from the pixel value of the seventeenth pixel from the leftmost in the frame #n-2.

[0219] That is, since pixels in the frame #n-1 and the frame #n-2 corresponding to the pixels belonging to the covered background area in the frame #n comprised only the background components and the pixel values thereof are not changed, the absolute value of the difference thereof is almost 0. Therefore, the stationary/moving determination on the pixels in the frame #n-1 and the frame #n-2 corresponding to pixels belonging to the mixed area in the frame #n is determined to be stationary by the stationary/moving determining portion 202-4.

[0220] Since pixels belonging to the covered background area in the frame #n include the foreground components, the pixel values thereof are different from those in the case of including only the background components in the frame #n-1. Therefore, the stationary/moving determination on the pixels belonging to the mixed area in the frame #n and pixels in the corresponding frame #n-1 is determined to be moving by the stationary/moving determining portion 202-3.

[0221] Like the above, when the stationary/moving determination result indicating motion status is supplied from the stationary/moving determining portion 202-3 and the stationary/moving determination result indicating stationary status is supplied from the stationary/moving determining portion 202-4, the area determining portion 203-3 determines that the corresponding pixel belongs to the covered background area.

[0222] In the frame #n that is shown in FIG. 49 and in which the background is stationary and the amount of movement v of the foreground is 4, the pixels belonging to the uncovered background area are the second to fourth pixels from the leftmost. Since the amount of movement v is 4, the second to fourth pixels in the frame #n+1 one frame behind include only the background components and belong to the background area. Further, the second to fourth pixels in the frame #n+2 further one frame behind include only the background components and belong to the background area.

[0223] Here, since the object corresponding to the background is stationary, the pixel value of the second pixel from the leftmost in the frame #n+2 is not changed from the pixel value of the second pixel from the leftmost in the frame #n+1. Similarly, the pixel value of the third pixel from the leftmost in the frame #n+2 is not changed from the pixel value of the third pixel from the leftmost in the frame #n+1 and the pixel value of the fourth pixel from the leftmost in the frame #n+2 is not changed from the pixel value of the fourth pixel from the leftmost in the frame #n+1.

[0224] That is, since pixels in the frame #n+1 and the frame #n+2 corresponding to the pixels belonging to the uncovered background area in the frame #n comprised only the background components and the pixel values thereof are not changed, the absolute value of the difference thereof is almost 0. Therefore, the stationary/moving determination on the pixels in the frame #n+1 and the frame #n+2 corresponding to pixels belonging to the mixed area in the frame #n is determined to be stationary by the stationary/moving determining portion 202-1.

[0225] Since pixels belonging to the uncovered background area in the frame #n include the foreground components, the pixel values thereof are different from those in the case of including only the background components in the frame #n+1. Therefore, the stationary/moving determination on the pixels belonging to the mixed area in the frame #n and pixels in the corresponding frame #n+1 is determined to be moving by the stationary/moving determining portion 202-2.

[0226] Like the above, when the stationary/moving determination result indicating motion status is supplied from the stationary/moving determining portion 202-2 and the stationary/moving determination result indicating stationary status is supplied from the stationary/moving determining portion 202-1, the area determining portion 203-1 determines that the corresponding pixel belongs to the uncovered background area.

[0227] FIG. 50 shows determination conditions of the area specifying unit 103 in the frame #n. When it is determined that a pixel in the frame #n-2 located at the same position as the position in the image of a pixel that is a target of determination in the frame #n and a pixel in the frame #n-1 located at the same position as the position in the image of the pixel that is a target of determination in the frame #n, are stationary and when it is determined that a pixel in the frame #n-1 located at the same position as the position in the image of the pixel that is a target of determination in the frame #n and the pixel in the frame #n are moving, the area specifying unit 103 determines that the pixel that is a target of determination in the frame #n belongs to the covered background area.

the pixel in the frame #n-2 and the pixel in the frame #n-1 located at the same position and if it is determined to be stationary, the procedure proceeds to step S209. The stationary/moving determining portion 202-3 determines whether it is moving or not for the pixel in the frame #n-1 and the pixel in the frame #n located at the same position.

[0242] In step S209, when it is determined to be moving for the pixel in the frame #n-1 and the pixel in the frame #n located at the same position, the procedure proceeds to step S210 and the area determining portion 203-3 sets "1" indicating the pixel belongs to the covered background area to the covered background area determining flag corresponding to the pixel of which area is determined. The area determining portion 203-3 supplies the covered background area determining flag to the frame memory storing determining flag 204 and the procedure proceeds to step S211.

[0243] When it is determined to be moving for the pixel in the frame #n-2 and the pixel in the frame #n-1 position located at the same position in step S208 or when it is determined to be stationary for the pixel in the frame #n-1 and the pixel in the frame #n position located at the same position in step S209, since the pixel in the frame #n does not belong to the covered background area, the processing in step S210 is skipped and the procedure proceeds to step S211.

[0244] In step S211, the stationary/moving determining portion 202-2 determines whether it is moving or not for the pixel in the frame #n and the pixel in the frame #n+1 located at the same position and if it is determined to be moving, the procedure proceeds to step S212. The stationary/moving determining portion 202-1 determines whether it is stationary or not for the pixel in the frame #n+1 and the pixel in the frame #n+2 located at the same position.

[0245] In step S212, when it is determined to be stationary for the pixel in the frame #n+1 and the pixel in the frame #n+2 located at the same position, the procedure proceeds to step S213 and the area determining portion 203-1 sets "1" indicating the pixel belongs to the uncovered background area to the uncovered background area determining flag corresponding to the pixel of which area is determined. The area determining portion 203-1 supplies the uncovered background area determining flag to the frame memory storing determining flag 204 and the procedure proceeds to step S214.

[0246] When it is determined to be stationary for the pixel in the frame #n and the pixel in the frame #n+1 position located at the same position in step S211 or when it is determined to be moving for the pixel in the frame #n+1 and the pixel in the frame #n+2 position located at the same position in step S212, since the pixel in the frame #n does not belong to the uncovered background area, the processing in step S213 is skipped and the procedure proceeds to step S214.

[0247] In step S214, the area specifying unit 103 determines whether area specification has been performed for all the pixels in the frame #n or not and if it is determined that the area specification has not been performed for all the pixels in the frame #n, the procedure returns to step S202 and the area specifying processing is repeated for other pixels.

[0248] In step S214, if it is determined that the area specification has been performed for all the pixels in the frame #n, the procedure proceeds to step S215 and the synthesizer 205 generates the area information indicating the mixed area on the basis of the uncovered background area determining flag and the covered background area determining flag stored in the frame memory storing determining flag 204, generates the area information indicating that each pixel belongs to which of the uncovered background area, the stationary area, the moving area and the covered background area and sets the generated area information in the frame memory storing determining flag 206. Then, the processing ends.

[0249] Like the above, the area specifying unit 103 can generate the area information indicating that the each pixel included in the frame belongs to the moving area, the stationary area, the uncovered background area or the covered background area.

[0250] Further, the area specifying unit 103 may generate the area information corresponding to the mixed area by applying logical sum to the area information corresponding to the uncovered background area and covered background area and may generate the area information comprised of flags indicating that the each pixel included in the frame belongs to the moving area, the stationary area or the mixed area.

[0251] When the object corresponding to the foreground has texture, the area specifying unit 103 can specify the moving area more accurately.

[0252] The area specifying unit 103 can output the area information indicating the moving area as the area information indicating the foreground area and the area information indicating the stationary area as the area information indicating the background area.

[0253] Further, although it has been explained that the object corresponding to the background is stationary, even when the image corresponding to the background area includes motion, the area specifying processing described above can be applied. For example, when an image corresponding to the background area is moving constantly, the area specifying unit 103 shifts the whole image corresponding to this movement and processes it similarly to the case that the object corresponding to the background is stationary. Further, when an image corresponding to the background area includes other movements locally, the area specifying unit 103 selects pixels corresponding to the movements and performs the aforementioned processing.

[0254] FIG. 54 is a block diagram illustrating another example of configuration of the area specifying unit 103. The area specifying unit 103 shown in FIG. 54 does not use the motion vector. A background image generator 301 generates the background image corresponding to the input image and supplies the generated background image to a binary object image extracting portion 302. The background image generator 301 extracts, for example, an image object corresponding to the object of the background included in the input image to generate the background image.

[0255] An example of a model in which the pixel values of pixels being adjacent in a row in the moving direction of an image corresponding to the foreground object are expanded in the time direction is shown in FIG. 55. For example, when the moving direction of the image corresponding to the foreground object is horizontal on the screen, the model diagram shown in FIG. 55 shows a model in which the pixel values of pixels being adjacent in one line are expanded in the time direction.

[0256] In FIG. 55, a line in a frame #n is the same as that in a frame #n-1 and a frame #n+1.

[0257] In the frame #n, the foreground components corresponding to the object included in the sixth to seventeenth pixels from the leftmost are included in the second to thirteenth pixels from the leftmost in the frame #n-1 and in the tenth to twenty first pixels from the leftmost in the frame #n+1.

[0258] In the frame #n-1, the pixels belonging to the covered background area are the eleventh to thirteenth pixels from the leftmost and the pixels belonging to the uncovered background area are the second to fourth pixels from the leftmost. In the frame #n, the pixels belonging to the covered background area are the fifteenth to seventeenth pixels from the leftmost pixels belonging to the uncovered background area are the sixth pixels to eighth pixels. In the frame #n+1, the pixels belonging to the covered background area are the nineteenth to twenty first pixels from the leftmost and the pixels belonging to the uncovered background area are the tenth to twelfth pixels from the leftmost.

[0259] In the frame #n-1, the pixels belonging to the background area are the first pixel and the fourteenth to twenty first pixels from the leftmost. In the frame #n, the pixels belonging to the background area are the first to fifth pixels and the eighteenth to twenty first pixels from the leftmost. In frame #n+1, the pixels belonging to the background area are the first to ninth pixels from the leftmost.

[0260] An example of the background image corresponding to the example of FIG. 55 which is generated from background generator 301 is shown in FIG. 56. The background image is comprised of pixels corresponding to the background object and does not include the image components corresponding to the foreground object.

[0261] The binary object image extracting portion 302 generates the binary object image on the basis of the correlation between the background image and the input image and supplies the generated binary object image to a time change detector 303.

[0262] FIG. 57 is a block diagram showing configuration of the binary object image extracting portion 302. A correlation value calculator 321 calculates the correlation between the input image and the background image supplied from the background image generator 301 and generates and supply the correlation value to a threshold value processor 322.

[0263] The correlation value calculator 321 applies equation (4) to, for example, 3×3 blocks in the background image where X4 is centered as shown in FIG. 58A and 3×3 blocks in the input image, corresponding to the blocks in the background image, where Y4 is centered as shown in FIG. 58B to calculate the correlation value corresponding to Y4.

$$\text{CORRELATION VALUE} = \frac{\sum_{i=0}^8 (X_i - \bar{X}) \sum_{i=0}^8 (Y_i - \bar{Y})}{\sqrt{\sum_{i=0}^8 (X_i - \bar{X})^2 \cdot \sum_{i=0}^8 (Y_i - \bar{Y})^2}} \quad (4)$$

$$\bar{X} = \frac{\sum_{i=0}^8 X_i}{9} \quad (5)$$

$$\bar{Y} = \frac{\sum_{i=0}^8 Y_i}{9} \quad (6)$$

[0280] In step S302, the binary object image extracting portion 302 calculates the correlation value between the input image and the background image supplied from the background image generator 301, for example, by using calculations which were explained by referring to FIG. 58A and FIG. 58B. In step S303, the binary object image extracting portion 302 calculates the binary object image from the correlation value and the threshold value th_0 , for example, by

5 comparing the correlation value with the threshold value th_0 .
[0281] In step S304, the time change detector 303 performs the area determining processing to complete the processing.

[0282] Referring to a flowchart of FIG. 65, the details of the area determining processing corresponding to step S304 will be explained. In step S321, the area determining portion 342 of the time change detector 303 determines whether the indicated pixel in the frame # n stored in the frame memory 341 is 0 or not and if it is determined that the indicated pixel in the frame # n is 0, the procedure proceeds to step S322. Then, the area determining portion 342 determines that the noticed pixel in the frame # n belongs to the background area to complete the processing.

10 [0283] In step S321, if it is determined that the indicated pixel in the frame # n is 1, the procedure proceeds to step S323. The area determining portion 342 of the time change detector 303 determines whether the indicated pixel in the frame # n stored in the frame memory 341 is 1 and the corresponding pixel in the frame # $n-1$ is 0 or not, and if it is determined that the indicated pixel in the frame # n is 1 and the corresponding pixel in the frame # $n-1$ is 0, the procedure proceeds to step S324. Then, the area determining portion 342 determines that the indicated pixel in the frame # n belongs to the covered background area to finish the processing.

20 [0284] In step S323, if it is determined that the indicated pixel in the frame # n is 0 or the corresponding pixel in the frame # $n-1$ is 1, the procedure proceeds to step S325. The area determining portion 342 of the time change detector 303 determines whether the indicated pixel in the frame # n stored in the frame memory 341 is 1 and the corresponding pixel in the frame # $n+1$ is 0 or not, and if it is determined that the noticed pixel in the frame # n is 1 and the corresponding pixel in the frame # $n+1$ is 0, the procedure proceeds to step S326. Then, the area determining portion 342 determines that the indicated pixel in the frame # n belongs to the uncovered background area and finishes the processing.

25 [0285] In step S325, if it is determined that the indicated pixel in the frame # n is 0 or the corresponding pixel in the frame # $n+1$ is 1, the procedure proceeds to step S327. The area determining portion 342 of the time change detector 303 determines that the noticed pixel in the frame # n belongs to the foreground area and finishes the processing.

30 [0286] Like the above, the area specifying unit 103 can specify which of the foreground area, the background area, the covered background area and the uncovered background area that the pixels of the input image belong on the basis of the correlation value between the input image and the corresponding background image, and generates the area information corresponding to the specification result.

35 [0287] FIG. 66 is a block diagram showing other configuration of the area specifying unit 103. The area specifying unit 103 shown in FIG. 66 uses the motion vector supplied from the motion detector 102 and the positional information thereof. Portions equal to those in FIG. 54 are indicated by the same reference numerals and explanation thereof will be omitted.

[0288] A robust processing portion 361 generates a binary object image of which robust processing is performed on the basis of the binary object image of N frames supplied from the binary object image extracting portion 302 and outputs it to the time change detector 303.

40 [0289] FIG. 67 is a block diagram illustrating a configuration of the robust processing portion 361. A motion compensator 381 compensates for motion of the binary object image of N frames on the basis of the motion vector supplied from the motion detector 102 and the positional information thereof, and outputs the binary object image of which motion is compensated to a switch 382.

[0290] Referring to examples of FIG. 68 and FIG. 69, a motion compensation process of the motion compensator 381 will be explained. For example, when an area in a frame # n is determined, if the binary object image of a frame # $n-1$, a frame # n and a frame # $n+1$ exemplified in FIG. 68 is input, the motion compensator 381 compensates the binary object image of the frame # $n-1$ and the binary object image of the frame # $n+1$, as exemplified in FIG. 69, on the basis of the motion vector supplied from the motion detector 102 and supplies the binary object image of which motion is compensated to the switch 382.

45 [0291] The switch 382 outputs the binary object image of the first frame in which motion is compensated to the frame memory 383-1 and outputs the binary object image, of the second frame in which motion is compensated to the frame memory 383-2. Similarly, the switch 382 outputs each of the binary object images of the third to $N-1$ -th frames in which motion is compensated to one of the frame memory 383-3 to 383-($N-1$) and outputs the binary object image of the N th frame in which motion is compensated to the frame memory 383- N .

50 [0292] The frame memory 383-1 stores the binary object image of the first frame in which motion is compensated and outputs the stored binary object image to the weighting portion 384-1. The frame memory 383-2 stores the binary object image of the second frame in which motion is compensated and outputs the stored binary object image to the weighting portion 384-2.

55 [0293] Similarly, each of the frame memory 383-3 to 383-($N-1$) stores one of the binary object images of the third to

(N-1)th frames of which motion is compensated and outputs the stored binary object image to one of weighting portions 384-3 to 384-(N-1). The frame memory 383-N stores the binary object image of Nth frame of which motion is compensated and outputs the stored binary object image to the weighting portion 384-N.

[0294] The weighting portion 384-1 multiplies the binary object image of the first frame supplied from the frame memory 383-1 of which motion is compensated, by a predetermined weight w_1 to supply it to the accumulator 385. The weighting portion 384-2 multiplies the pixel value of the binary object image of the second frame supplied from the frame memory 383-2 of which motion is compensated by a predetermined weight w_2 to supply it to the accumulator 385.

[0295] Similarly, each of the weighting portion 384-3 to the weighting portion 384-(N-1) multiplies the pixel value of the binary object image of one of the third to (N-1)th frames supplied from one of the frame memories 383-3 to 383-(N-1) of which motion is compensated, by one of weight w_3 to weight $w_{(N-1)}$ to supply it to the accumulator 385. The weighting portion 384-N multiplies the pixel value of the binary object image of the Nth frame supplied from the frame memory 383-N of which motion is compensated; by a predetermined weight w_N to supply it to the accumulator 385.

[0296] The accumulator 385 accumulates the pixel values corresponding to the binary object images of the first to Nth frames respectively multiplied by one of the weights w_1 to w_N of which motions are compensated and generates the binary object image by comparing the accumulated pixel values with the predetermined threshold value th_0 .

[0297] Like the above, since the robust processing portion 361 generates the binary object images of which robust processing is performed from N binary object images and supplies it to the time change detector 303, even when noises are included in the input image, the area specifying unit 103 of which the configuration is shown in FIG. 66 can perform the area specification more accurately than the case shown in FIG. 54.

[0298] Next, referring to a flowchart of FIG. 70, the area specifying process of the area specifying unit 103 of which the configuration is shown in FIG. 66 will be explained. The steps of step S341 to step S343 are equal to those of step S301 to step S303 and thus, explanation thereof will be omitted.

[0299] In step S344, the robust processing portion 361 performs the robust processing.

[0300] In step S345, the time change detector 303 performs the area specifying process and finishes the procedure. Since the detailed process in step S345 is similar to the process explained by referring to the flowchart of FIG. 65, explanation thereof will be omitted.

[0301] Next, referring to a flowchart of FIG. 71, the details of the robust processing corresponding to the processing of step S344 in FIG. 70 will be explained. In step S361, a motion compensator 381 performs the motion compensating process for the input binary object image on the basis of the motion vector supplied from the motion detector 102 and the positional information thereof. In step S362, one of the frame memories 383-1 to 383-N stores the motion compensated binary object image supplied through the switch 382.

[0302] In step S363, the robust processing portion 361 determines whether N binary object images are stored or not and if it is determined that N binary object images are not stored, the procedure returns to step S361 and the motion compensating process for the binary object image and the storing process for the binary object image are repeated.

[0303] In step S363, if it is determined that N binary object images are stored, the procedure proceeds to step S364. Each of the weighting portions 384-1 to 384-N multiplies each of the N binary object images by one of the weights w_1 to w_N for weighting.

[0304] In step S365, an accumulator 385 accumulates the weighted N binary object images.

[0305] In step S366, the accumulator 385 generates a binary object image from the accumulated image, for example, by comparing to the predetermined threshold value th_1 and finishes the procedure.

[0306] Like the above, the area specifying unit 103 of which the configuration is shown in FIG. 66 can generate the area information on the basis of the binary object image that is robust processed.

[0307] As described above, the area specifying unit 103 can generate the area information indicating that each pixel included in the frame belongs to the moving area, the stationary area, the uncovered background area or the covered background area.

[0308] FIG. 72 is a block diagram illustrating an example of a configuration of the mixture ratio calculator 104. An estimated mixture ratio processor 401 calculates the mixture ratio of each pixel by using the calculation corresponding to a model of the covered background area on the basis of the input image and supplies the calculated estimated mixture ratio to the mixture ratio determining portion 403.

[0309] An estimated mixture ratio processor 402 calculates the mixture ratio of each pixel by using the calculation corresponding to the model of the uncovered background area on the basis of the input image and supplies the calculated estimated mixture ratio to the mixture ratio determining portion 403.

[0310] Since it is supposed that the object corresponding to the foreground is moving at a uniform speed for the shutter time, the mixture ratio α of pixel belonging to the mixed area has the following feature. That is, the mixture ratio α is linearly varied corresponding to the positional variation of a pixel. If the positional variation of a pixel is one-dimensional, the variation in mixture ratio α can be expressed by a linear line and if the positional variation of pixel is two-dimensional, the variation in mixture ratio α can be expressed by a plane.

[0311] Further, since time interval for one frame is short, it can be supposed that the object corresponding to the foreground is a rigid body and is moving at a uniform speed.

[0312] In this case, the slope of mixture ratio α is reciprocal ratio to the amount of movement v in the shutter time of the foreground.

5 [0313] An example of an ideal mixture ratio α is shown in FIG. 73. The slope l of the ideal mixture ratio α in the mixed area can be expressed as a reciprocal number of the amount of movement v .

[0314] As shown in FIG. 73, the ideal mixture ratio α is 1 in the background area, is 0 in the foreground area and is greater than 0 and less than 1 in the mixed area.

10 [0315] In the example of FIG. 74, the pixel value C06 of the seventh pixel from the leftmost in the frame #n can be expressed as equation (8) by using the pixel value P06 of the seventh pixel in the frame #n-1.

$$\begin{aligned}
 C06 &= B06/v + B06/v + F01/v + F02/v \\
 15 \quad &= P06/v + P06/v + F01/v + F02/v \\
 &= 2/v \cdot P06 + \sum_{i=1}^2 F_i/v \quad (8)
 \end{aligned}$$

20 [0316] In equation (8), the pixel value C06 is expressed as the pixel value M of pixel in the mixed area and the pixel value P06 is expressed as the pixel value B of pixel in the background area. That is, the pixel value M of pixel in the mixed area and the pixel value B of pixel in the background area can be expressed by equation (9) and equation (10), respectively.

$$25 \quad M = C06 \quad (9)$$

$$B = P06 \quad (10)$$

30 [0317] $2/v$ in equation (8) corresponds to the mixture ratio α . Since the amount of movement v is defined as 4, the mixture ratio α of the seventh pixel from the leftmost in the frame #n is 0.5.

[0318] As described above, by considering the pixel value C in the indicated frame #n as the pixel value in the mixed area and the pixel value P in the frame #n-1 ahead of the frame #n as the pixel value in the background area, the equation (3) expressing the mixture ratio α can be expressed by equation (11).

$$35 \quad C = \alpha \cdot P + f \quad (11)$$

40 f in equation (11) is sum $\sum_i F_i/v$ of the foreground components included in the indicated pixel. Variables included in equation (11) are two of the mixture ratio α and the sum f of the foreground components.

[0319] Similarly, in the uncovered background area, the amount of movement v is 4 and the virtual division number in the time direction is 4. A model in which the pixel values are expanded in the time direction is shown in FIG. 75.

45 [0320] In the uncovered background area, similar to the expressions of the aforementioned covered background area, by considering the pixel value C of pixel in the indicated frame #n as the pixel value in the mixed area and the pixel value N in the frame #n+1 behind the frame #n as the pixel value in the background area, the equation (3) expressing the mixture ratio α can be expressed by equation (12).

$$50 \quad C = \alpha \cdot N + f \quad (12)$$

[0321] Further, although it has been explained by considering that the background object is stationary, even when the background object is moving, equation (8) to equation (12) can be applied by using the pixel value of pixel at a position corresponding to the amount of movement v of the background. For example, in FIG. 74, when the amount of movement v of the object corresponding to the background is 2, the virtual division number is 2 and when the object corresponding to the background is moving toward the right side in the drawing, the pixel value B of pixel in the background area in equation (10) becomes the pixel value P04.

[0322] Since each of equation (11) and equation (12) includes two variables, the mixture ratio α cannot be obtained

by these equations. Here, since the image has a strong correlation in space, the adjacent pixels are almost equal.

[0323] Therefore, because the foreground components have a strong correlation in space, by changing the equations to derive the sum f of the foreground components from the front or next frame, the mixture ratio α is obtained.

[0324] The pixel value M_c of the seventh pixel from the leftmost in the frame # n in FIG. 76 can be expressed by equation (13).

$$M_c = \frac{2}{v} \cdot B06 + \sum_{i=11}^{12} F_i/v \quad (13)$$

[0325] $2/v$ of the first term of right side of equation (13) corresponds to the mixture ratio α . The second term of right side of equation (13) can be expressed by equation (14) using the pixel value in the next frame # $n+1$.

$$\sum_{i=11}^{12} F_i/v = \beta \cdot \sum_{i=7}^{10} F_i/v \quad (14)$$

[0326] Here, using the spatial correlation of the foreground components, equation (15) can be obtained.

$$F=F05=F06=F07=F08=F09=F10=F11=F12 \quad (15)$$

[0327] Equation (14) can be replaced with equation (16) by using equation (15).

$$\begin{aligned} \sum_{i=11}^{12} F_i/v &= \frac{2}{v} \cdot F \\ &= \beta \cdot \frac{4}{v} \cdot F \end{aligned} \quad (16)$$

[0328] Consequently, β can be expressed by equation (17).

$$\beta=2/4 \quad (17)$$

[0329] In general, if it is supposed that the foreground components corresponding to the mixed area as shown in equation (15) are equal, equation (18) can be established for all the pixels in the mixed area, in view of relation of the interior division ratio.

$$\beta=1-\alpha \quad (18)$$

[0330] If the equation (18) is established, equation (11) can be obtained as shown in equation (19).

$$\begin{aligned} C &= \alpha \cdot P + f \\ &= \alpha \cdot P + (1-\alpha) \cdot \sum_{i=7}^{7+v-1} F_i/v \\ &= \alpha \cdot P + (1-\alpha) \cdot N \end{aligned} \quad (19)$$

[0372] In this equation (23), i is an index in the spatial direction when the position of the indicated pixel is 0. 1 is slope of a linear line of the mixture ratio α . p is an intercept of the linear line of the mixture ratio α and is the mixture ratio α of the indicated pixel. In equation (23), the index i is known but the slope 1 and the intercept p are not known.

[0373] The relationship between index i , the slope 1 and the intercept p is shown in FIG. 83.

[0374] By approximating the mixture ratio α by equation (23), a plurality of different mixture ratios α for a plurality of pixels are expressed with two variables. In the example shown in FIG. 83, 5 mixture ratios for the five pixels are expressed with two variables of the slope i and the intercept p . Further, in FIG. 83, the indicated pixel is indicated by a white circle and the peripheral pixels are indicated by black circle.

[0375] If the mixture ratio α is approximated in a plane shown in FIG. 84, considering movement v corresponding to two directions, the horizontal direction and the vertical direction of the image, the equation (23) is extended into the plane and the mixture ratio α is expressed by equation (24). Further, in FIG. 84, the white circle indicates the indicated pixel.

$$\alpha = jm + kq + p \quad (24)$$

[0376] In equation (24), j is an index in the horizontal direction when the position of the indicated pixel is 0 and k is an index in the vertical direction. m is a slope of the mixture ratio α plane in the horizontal direction and q is a slope of the mixture ratio α plane in the vertical direction. p is an intercept of the mixture ratio α plane.

[0377] For example, in the frame # n shown in FIG. 74, equations (25) to (27) are established with respect to C05 to C07, respectively.

$$C05 = \alpha05 \cdot B05/v + f05 \quad (25)$$

$$C06 = \alpha06 \cdot B06/v + f06 \quad (26)$$

$$C07 = \alpha07 \cdot B07/v + f07 \quad (27)$$

[0378] If the foreground components are equal in the neighborhood, that is, F01 to F03 are equal and F01 to F03 is replaced with F_c , equation (28) can be established.

$$f(x) = (1 - \alpha(x)) \cdot F_c \quad (28)$$

[0379] In equation (28), x expresses a position of the spatial direction.

[0380] If $\alpha(x)$ is replaced with equation (24), and equation (28) can be expressed by equation (29).

$$\begin{aligned} f(x) &= (1 - (jm + kq + p)) \cdot F_c \\ &= j \cdot (-m \cdot F_c) + k \cdot (-q \cdot F_c) + ((1 - p) \cdot F_c) \\ &= js + kt + u \end{aligned} \quad (29)$$

[0381] In equation (29), $(-m \cdot F_c)$, $(-q \cdot F_c)$ and $(1 - p) \cdot F_c$ are replaced as shown in equations (30) to (32).

$$s = -m \cdot F_c \quad (30)$$

$$t = -q \cdot F_c \quad (31)$$

$$u = (1 - p) \cdot F_c \quad (32)$$

[0382] In equation (29), j is an index in the horizontal direction when position of the indicated pixel is 0 and k is an index in the vertical direction.

[0383] Like the above, since it is supposed that the object corresponding to the foreground is moving at a uniform speed for the shutter time and the components corresponding to the foreground are constant in the neighborhood, the sum of the foreground components is approximated by equation (29).

[0384] Further, when the mixture ratio α is approximated by a linear line, the sum of the foreground components can be expressed by equation (33).

$$f(x) = is + u \quad (33)$$

[0385] If substituting the mixture ratio α in equation (13) and the sum of the foreground components in equation (24) and equation (29), the pixel value M is expressed by equation (34).

$$\begin{aligned} M &= (jm + kq + p) \cdot B + js + kt + u \\ &= jB \cdot m + kB \cdot q + B \cdot p + j \cdot s + k \cdot t + u \end{aligned} \quad (34)$$

[0386] In equation (34), the six unknown variables are the slope m of the mixture ratio α plane in the horizontal direction, the slope q of the mixture ratio α plane in the vertical direction and the intercepts p , s , t and u of the mixture ratio α plane.

[0387] The pixel value M or the pixel value B is substituted in a normal equation shown in equation (34) corresponding to pixels in the neighborhood of the indicated pixel and a plurality of normal equations in which the pixel value M or the pixel value B is substituted are solved by the least square method to calculate the mixture ratio α .

[0388] For example, if the index j of the indicated pixel in the horizontal direction is 0, the index k in the vertical direction is 0 and the pixel value M or the pixel value B is substituted in the normal equation shown in equation (34) for 3x3 pixels adjacent to the indicated pixel, equations (35) to (43) are obtained.

$$M_{-1,-1} = (-1) \cdot B_{-1,-1} \cdot m + (-1) \cdot B_{-1,-1} \cdot q + B_{-1,-1} \cdot p + (-1) \cdot s + (-1) \cdot t + u \quad (35)$$

$$m_{0,-1} = (0) \cdot B_{0,-1} \cdot m + (-1) \cdot B_{0,-1} \cdot q + B_{0,-1} \cdot p + (0) \cdot s + (-1) \cdot t + u \quad (36)$$

$$M_{+1,-1} = (+1) \cdot B_{+1,-1} \cdot m + (-1) \cdot B_{+1,-1} \cdot q + B_{+1,-1} \cdot p + (+1) \cdot s + (-1) \cdot t + u \quad (37)$$

$$M_{-1,0} = (-1) \cdot B_{-1,0} \cdot m + (0) \cdot B_{-1,0} \cdot q + B_{-1,0} \cdot p + (-1) \cdot s + (0) \cdot t + u \quad (38)$$

$$M_{0,0} = (0) \cdot B_{0,0} \cdot m + (0) \cdot B_{0,0} \cdot q + B_{0,0} \cdot p + (0) \cdot s + (0) \cdot t + u \quad (39)$$

$$M_{+1,0} = (+1) \cdot B_{+1,0} \cdot m + (0) \cdot B_{+1,0} \cdot q + B_{+1,0} \cdot p + (+1) \cdot s + (0) \cdot t + u \quad (40)$$

$$M_{-1,+1} = (-1) \cdot B_{-1,+1} \cdot m + (+1) \cdot B_{-1,+1} \cdot q + B_{-1,+1} \cdot p + (-1) \cdot s + (+1) \cdot t + u \quad (41)$$

$$M_{0,+1} = (0) \cdot B_{0,+1} \cdot m + (+1) \cdot B_{0,+1} \cdot q + B_{0,+1} \cdot p + (0) \cdot s + (+1) \cdot t + u \quad (42)$$

$$M_{+1,+1} = (+1) \cdot B_{+1,+1} \cdot m + (+1) \cdot B_{+1,+1} \cdot q + B_{+1,+1} \cdot p + (+1) \cdot s + (+1) \cdot t + u \quad (43)$$

[0389] Since the index j of the indicated pixel in the horizontal direction is 0 and the index k in the vertical direction

is 0, the mixture ratio α of the indicated pixel is equal to the value when $j=0$ and $k=0$ in equation (24), that is, the intercept p .

[0390] Therefore, each value of the slope m in the horizontal direction, the slope q in the vertical direction and the intercepts p , s , t and u is calculated by using the least square method on the basis the nine equations (35) to (43) and then, the intercept p is output as the mixture ratio α .

[0391] Next, a more specific procedure for calculating the mixture ratio α by using the least square method will be explained.

[0392] If the index i and the index k are expressed by one index x , the relationship of the index i , the index k and the index x is expressed by equation (44).

$$x = (j+1) \cdot 3 + (k+1) \quad (44)$$

[0393] The slope m in the horizontal direction, the slope q in the vertical direction and the intercepts p , s , t , and u are expressed as variables w_0 , w_1 , w_2 , w_3 , w_4 and w_5 , respectively and jB , kB , B , j , k and 1 are expressed as a_0 , a_1 , a_2 , a_3 , a_4 and a_5 , respectively. Considering error ex , equations (35) to (43) can be rewritten as equation (45).

$$M_x = \sum_{y=0}^5 a_y \cdot w_y + ex \quad (45)$$

[0394] In equation (45), x is a value from integers 0 to 8.

[0395] Equation (46) can be derived from the equation (45).

$$ex = M_x - \sum_{y=0}^5 a_y \cdot w_y \quad (46)$$

[0396] Here, in order to use the least square method, the sum of squares of errors E is defined as shown by equation (47).

$$E = \sum_{x=0}^8 ex^2 \quad (47)$$

[0397] In order to minimize error, the partial differential of variable w_v and the sum of squares of errors E should be 0. Here, v is one of integers 0 to 5. Therefore, w_v is obtained to satisfy equation (48).

$$\begin{aligned} \frac{\partial E}{\partial w_v} &= 2 \cdot \sum_{x=0}^8 ex \cdot \frac{\partial ex}{\partial w_v} \\ &= 2 \cdot \sum_{x=0}^8 ex \cdot a_v = 0 \end{aligned} \quad (48)$$

[0398] If equation (46) is substituted in equation (48), equation (49) is obtained.

$$\sum_{x=0}^3 (a_v \cdot \sum_{y=0}^3 a_y \cdot w_y) = \sum_{x=0}^3 a_v \cdot M_x \quad (49)$$

5

10 [0399] By applying, for example, sweeping-out method such as Gauss-Jordan elimination method, to six equations obtained by substituting one of integers 0 to 5 in v of equation (49), w_y is calculated. As described above, w_0 is the slope m in the horizontal direction, w_1 is the slope in the vertical direction, w_2 is the intercept p , w_3 is s , w_4 is t and w_5 is u .

[0400] As described above, by applying the least square method to equations in which the pixel value M and the pixel value B are substituted, the slope m in the horizontal direction, the slope q in the vertical direction and the intercepts p , s , t and u can be obtained.

15 [0401] In explanation of equations (35) to (43), the pixel value of pixel included in the mixed area is explained as M and the pixel value of pixel included in the background area is explained as B . However, it is necessary that normal equations be established for each case that the indicated pixel is included in the covered background area or in the uncovered background area.

20 [0402] For example, when the mixture ratios α of pixels included in the covered background area in the frame # n as shown in FIG. 74 are obtained, the pixel values C04 to C08 of pixels in the frame # n and the pixel values P04 to P08 of pixels in the frame # $n-1$ are substituted in the normal equations.

[0403] When the mixture ratios α of pixels included in the uncovered background area in the frame # n as shown in FIG. 75 are obtained, the pixel values C28 to C32 of pixels in the frame # n and the pixel values N28 to N32 of pixels in the frame # $n+1$ are substituted in the normal equations.

25 [0404] Further, for example, when the mixture ratios α of pixels included in the covered background area in the frame # n as shown in FIG. 85 are calculated, equations (50) to (58) can be established. The pixel value of pixel of which the mixture ratio α is calculated is $Mc5$. Further, in FIG. 85, white circles indicate the pixels in the background and black circles indicate the pixels in the mixed area, respectively.

30

$$Mc1 = (-1) \cdot Bc1 \cdot m + (-1) \cdot Bc1 \cdot q + Bc1 \cdot p + (-1) \cdot s + (-1) \cdot t + u \quad (50)$$

$$Mc2 = (0) \cdot Bc2 \cdot m + (-1) \cdot Bc2 \cdot q + Bc2 \cdot p + (0) \cdot s + (-1) \cdot t + u \quad (51)$$

35

$$Mc3 = (+1) \cdot Bc3 \cdot m + (-1) \cdot Bc3 \cdot q + Bc3 \cdot p + (+1) \cdot s + (-1) \cdot t + u \quad (52)$$

40

$$Mc4 = (-1) \cdot Bc4 \cdot m + (0) \cdot Bc4 \cdot q + Bc4 \cdot p + (-1) \cdot s + (0) \cdot t + u \quad (53)$$

$$Mc5 = (0) \cdot Bc5 \cdot m + (0) \cdot Bc5 \cdot q + Bc5 \cdot p + (0) \cdot s + (0) \cdot t + u \quad (54)$$

45

$$Mc6 = (+1) \cdot Bc6 \cdot m + (0) \cdot Bc6 \cdot q + Bc6 \cdot p + (+1) \cdot s + (0) \cdot t + u \quad (55)$$

$$Mc7 = (-1) \cdot Bc7 \cdot m + (+1) \cdot Bc7 \cdot q + Bc7 \cdot p + (-1) \cdot s + (+1) \cdot t + u \quad (56)$$

50

$$Mc8 = (0) \cdot Bc8 \cdot m + (+1) \cdot Bc8 \cdot q + Bc8 \cdot p + (0) \cdot s + (+1) \cdot t + u \quad (57)$$

55

$$Mc9 = (+1) \cdot Bc9 \cdot m + (+1) \cdot Bc9 \cdot q + Bc9 \cdot p + (+1) \cdot s + (+1) \cdot t + u \quad (58)$$

[0405] When the mixture ratios α of pixels included in the covered background area in the frame # n are calculated, the pixel values $Bc1$ to $Bc9$ of pixels of the background area in the frame # $n-1$ corresponding to the pixels in the frame

#n are used in equations (50) to (58).

[0406] When the mixture ratios α of pixels included in the uncovered background shown in FIG. 85 are calculated, equations (59) to (67) can be established. The pixel value of pixel of which the mixture ratio α is calculated is Mu5.

$$\text{Mu1} = (-1) \cdot \text{Bu1} \cdot m + (-1) \cdot \text{Bu1} \cdot q + \text{Bu1} \cdot p + (-1) \cdot s + (-1) \cdot t + u \quad (59)$$

$$\text{Mu2} = (0) \cdot \text{Bu2} \cdot m + (-1) \cdot \text{Bu2} \cdot q + \text{Bu2} \cdot p + (0) \cdot s + (-1) \cdot t + u \quad (60)$$

$$\text{Mu3} = (+1) \cdot \text{Bu3} \cdot m + (-1) \cdot \text{Bu3} \cdot q + \text{Bu3} \cdot p + (+1) \cdot s + (-1) \cdot t + u \quad (61)$$

$$\text{Mu4} = (-1) \cdot \text{Bu4} \cdot m + (0) \cdot \text{Bu4} \cdot q + \text{Bu4} \cdot p + (-1) \cdot s + (0) \cdot t + u \quad (62)$$

$$\text{Mu5} = (0) \cdot \text{Hu5} \cdot m + (0) \cdot \text{Bu5} \cdot q + \text{Bu5} \cdot p + (0) \cdot s + (0) \cdot t + u \quad (63)$$

$$\text{Mu6} = (+1) \cdot \text{Bu6} \cdot m + (0) \cdot \text{Bu6} \cdot q + \text{Bu6} \cdot p + (+1) \cdot s + (0) \cdot t + u \quad (64)$$

$$\text{Mu7} = (-1) \cdot \text{Bu7} \cdot m + (+1) \cdot \text{Bu7} \cdot q + \text{Bu7} \cdot p + (-1) \cdot s + (+1) \cdot t + u \quad (65)$$

$$\text{Mu8} = (0) \cdot \text{Bu8} \cdot m + (+1) \cdot \text{Bu8} \cdot q + \text{Bu8} \cdot p + (0) \cdot s + (+1) \cdot t + u \quad (66)$$

$$\text{Mu9} = (+1) \cdot \text{Bu9} \cdot m + (+1) \cdot \text{Bu9} \cdot q + \text{Bu9} \cdot p + (+1) \cdot s + (+1) \cdot t + u \quad (67)$$

[0407] When the mixture ratios α of pixels included in the uncovered background area in the frame #n are calculated, the pixel values Bu1 to Bu9 of pixels of the background area in the frame #n+1 corresponding to the pixels in the frame #n are used in equations (59) to (67).

[0408] FIG. 86 is a block diagram illustrating configuration of the estimated mixture ratio processor 401. The image input to the estimated mixture ratio processor 401 is supplied to a delay circuit 501 and an adder 502.

[0409] The delay circuit 501 delays the input image by one frame and supplies it to the adder 502. When the frame #n is input to the adder 502 as the input image, the delay circuit 501 supplies the frame #n-1 to the adder 502.

[0410] The adder 502 sets the pixel values of pixels adjacent to pixel of which the mixture ratio α is calculated and the pixel values in the frame #n-1 in the normal equations. For example, the adder 502 sets the pixel values Mc1 to Mc9 and the pixel values Bc1 to Bc9 in the normal equations on the basis of equations (50) to (58). The adder 502 supplies the normal equations in which the pixel values are set to the calculator 503.

[0411] The calculator 503 solves the normal equations supplied from the adder 502 by using the elimination method, etc. to obtain the estimated mixture ratio and outputs the obtained estimated mixture ratio.

[0412] Like the above, the estimated mixture ratio processor 401 can calculate the estimated mixture ratio on the basis of the input image and supply it to the mixture ratio determining portion 403.

[0413] Further, since the estimated mixture ratio processor 402 has the configuration similar to that of the estimated mixture ratio processor 401, explanation thereof will be omitted.

[0414] FIG. 87 shows an example of the estimated mixture ratio calculated by the estimated mixture ratio processor 401. The estimated mixture ratio shown in FIG. 87 expresses the result calculated from equations generated in a unit of 7x7 pixels with respect to one line when the amount of movement v of the foreground corresponding to the object moving at a uniform speed is 11.

[0415] It can be known that the estimated mixture ratio is varied almost linearly in the mixed area as shown in FIG. 86.

[0416] Next, the mixture ratio estimating processing of the estimated mixture ratio processor 401 of which configuration is shown in FIG. 86 by using a model corresponding to the covered background area will be explained referring to FIG. 88.

[0417] In step S521, the adder 502 sets the pixel values included in the input image and the pixel values included in the image supplied from the delay circuit 501 in the normal equations corresponding to the model of the covered

background area.

[0418] In step S522, the estimated mixture ratio processor 401 determines whether setting for the target pixels is finished or not and if it is determined that the setting for the target pixels is not finished, the procedure returns to step S521 and repeats the setting processing of the pixel values in the normal equations.

[0419] In step S522, if it is determined that the setting the pixel value for the target pixels is finished, the procedure proceeds to step S523 and the calculator 173 calculates the estimated mixture ratio on the basis of the normal equations in which the pixel values are set and outputs the obtained estimated mixture ratio.

[0420] Like the above, the estimated mixture ratio processor 401 of which configuration is shown in FIG. 86 can calculate the estimated mixture ratio on the basis of the input image.

[0421] The mixture ratio estimating process using the model corresponding to the uncovered background area is similar to the process using the normal equations corresponding to the model of the uncovered background area shown in a flowchart of FIG. 88 and thus, explanation thereof will be omitted.

[0422] Further, although it has been explained that the object corresponding to the background is stationary, even when the image corresponding to the background area includes movement, the aforementioned mixture ratio obtaining processing can be applied. For example, when the image corresponding to the background is moving constantly, the estimated mixture ratio processor 401 shifts the whole image according to the movements and then, processes similarly to the case that the object corresponding to the background is stationary.

Further, when the image corresponding to the background area includes other local movements, the estimated mixture ratio processing portion 401 selects the pixels corresponding to the movements as the pixels corresponding to pixels belonging to the mixed area and then, performs the aforementioned processing.

[0423] Like the above, the mixture ratio calculator 102 can calculate the mixture ratio α that is a feature amount corresponding to each pixel on the basis of the area information supplied from the area specifying unit 101 and the input image.

[0424] By using the mixture ratio α , while the information of motion blur included in the image corresponding to the moving object is left, it is possible to separate the foreground components and the background components included in the pixel values.

[0425] Further, if an image is synthesized on the basis of the mixture ratio α , it is possible to generate image including the corrected motion blur adapted to the speed of the object moving to correspond to the images in the real world.

[0426] Next, the foreground/background separator 105 will be explained. FIG. 89 is a block diagram illustrating an example of a configuration of the foreground/background separator 105. The input image supplied to the foreground/background separator 105 is supplied to a separating portion 601, the switch 602 and the switch 604. The area information indicating the covered background area and the area information indicating the uncovered background area supplied from the area specifying unit 103, are supplied to the separating portion 601. The area information indicating the foreground area is supplied to the switch 602. The area information indicating the background area is supplied to the switch 604.

[0427] The mixture ratio α supplied from the mixture ratio calculator 104 is supplied to the separating portion 601.

[0428] The separating portion 601 separates the foreground components from the input image to supply the separated foreground components to the synthesizer 603 and separates the background components from the input image to supply the separated background components to the synthesizer 605, on the basis of the area information indicating the covered background area, the area information indicating the uncovered background area and the mixture ratio α .

[0429] When the pixels corresponding to the foreground are input, the switch 602 is closed and supplies only the pixels corresponding to the foreground included in the input image to the synthesizer 603, on the basis of the area information indicating the foreground area.

[0430] When the pixels corresponding to the background are input, the switch 604 is closed and supplies only the pixels corresponding to the background included in the input image to the synthesizer 605, on the basis of the area information indicating the background area.

[0431] The synthesizer 603 synthesizes the foreground component image on the basis of the foreground components supplied from the separating portion 601 and the pixels corresponding to the foreground supplied from the switch 602, and outputs the synthesized foreground component image. Since the foreground area and the background area are not overlapped, the synthesizer 603 applies, for example, logical sum operation to the foreground components and the pixels corresponding to the foreground to synthesize the foreground component image.

[0432] In initial process to be first performed in the process of synthesizing the foreground component image, the synthesizer 603 stores the image of which all the pixels in the built-in frame memory are 0, and in the process of synthesizing the foreground component image, the synthesizer 603 stores (overwrites) the foreground component image. Therefore, 0 is stored as the pixel values in the pixels corresponding to the background area and in the foreground component images supplied from the synthesizer 603.

[0433] The synthesizer 605 synthesizes the background component image on the basis of the background components supplied from the separating portion 601 and the pixels corresponding to the background supplied from the

$$\begin{aligned}
 C15 &= B15/v + F09/v + F08/v + F07/v \\
 &= \alpha15 \cdot B15 + F09/v + F08/v + F07/v \\
 &= \alpha15 \cdot P15 + F09/v + F08/v + F07/v
 \end{aligned} \tag{68}$$

[0447] Here, $\alpha15$ is a mixture ratio of the fifteenth pixel from the leftmost in the frame #n. P15 is a pixel value of the fifteenth pixel from the leftmost in the frame #n-1.

[0448] On the basis of equation (68), sum f15 of the foreground components of the fifteenth pixel from the leftmost in the frame #n is expressed by equation (69).

$$\begin{aligned}
 f15 &= F09/v + F08/v + F07/v \\
 &= C15 - \alpha15 \cdot P15
 \end{aligned} \tag{69}$$

[0449] Similarly, sum f16 of the foreground components of the sixteenth pixel from the leftmost in the frame #n is expressed by equation (70), and sum f17 of the foreground components of the seventeenth pixel from the leftmost in the frame #n is expressed by equation (71).

$$f16 = C16 - \alpha16 \cdot P16 \tag{70}$$

$$f17 = C17 - \alpha17 \cdot P17 \tag{71}$$

[0450] Like the above, the foreground component f_c included in the pixel value C of pixels belonging to the covered background area is calculated by equation (72).

$$f_c = C - \alpha \cdot P \tag{72}$$

[0451] P is the pixel value of the corresponding pixel in the frame one ahead.

[0452] FIG. 93 is a diagram illustrating a process of separating the foreground components from the pixels belonging to the uncovered background area. In FIG. 93, $\alpha1$ to $\alpha18$ are the mixture ratios corresponding to the respective pixels in the frame #n. In FIG. 93, the second to fourth pixels from the leftmost belong to the uncovered background area.

[0453] The pixel value C02 of the second pixel from the leftmost in the frame #n is expressed by equation (73).

$$\begin{aligned}
 C02 &= B02/v + B02/v + B02/v + F01/v \\
 &= \alpha2 \cdot B02 + F01/v \\
 &= \alpha2 \cdot N02 + F01/v
 \end{aligned} \tag{73}$$

[0454] Here, $\alpha2$ is the mixture ratio of the second pixel from the leftmost in the frame #n. N02 is the pixel value of the second pixel from the leftmost in the frame #n+1.

[0455] On the basis of equation (73), sum f02 of the foreground components of the second pixel from the leftmost in the frame #n is expressed by equation (74).

$$\begin{aligned}
 f02 &= F01/v \\
 &= C02 - \alpha2 \cdot N02
 \end{aligned} \tag{74}$$

EP 1 400 927 A1

components is 8, the number of the pixels corresponding to the unit of processing A is 12, the amount of movement v is 5 and the virtual division number is 5, subsequent equations generated by the equation generator 803 are explained. [0498] When the foreground component included in the foreground component image corresponding to the shutter time t/v lies between $F01/v$ and $F08/v$, the relations between $F01/v$ to $F08/v$ and the pixel values $C01$ to $C12$ are expressed in equations (78) to (89).

$$C01 = F01/v \quad (78)$$

$$C02 = F02/v + F01/v \quad (79)$$

$$C03 = F03/v + F02/v + F01/v \quad (80)$$

$$C04 = F04/v + F03/v + F02/v + F01/v \quad (81)$$

$$C05 = F05/v + F04/v + F03/v + F02/v + F01/v \quad (82)$$

$$C06 = F06/v + F05/v + F04/v + F03/v + F02/v \quad (83)$$

$$C07 = F07/v + F06/v + F05/v + F04/v + F03/v \quad (84)$$

$$C08 = F08/v + F07/v + F06/v + F05/v + F04/v \quad (85)$$

$$C09 = F08/v + F07/v + F06/v + F05/v \quad (86)$$

$$C10 = F08/v + F07/v + F06/v \quad (87)$$

$$C11 = F08/v + F07/v \quad (88)$$

$$C12 = F08/v \quad (89)$$

[0499] The equation generator 803 generates equations by modifying the generated equations. Equations generated by the equation generator 803 are expressed in equations (90) to (101).

$$C01 = 1 \cdot F01/v + 0 \cdot F02/v + 0 \cdot F03/v + 0 \cdot F04/v + 0 \cdot F05/v \\ + 0 \cdot F06/v + 0 \cdot F07/v + 0 \cdot F08/v \quad (90)$$

$$C02 = 1 \cdot F01/v + 1 \cdot F02/v + 0 \cdot F03/v + 0 \cdot F04/v + 0 \cdot F05/v \\ + 0 \cdot F06/v + 0 \cdot F07/v + 0 \cdot F08/v \quad (91)$$

$$C03 = 1 \cdot F01/v + 1 \cdot F02/v + 1 \cdot F03/v + 0 \cdot F04/v + 0 \cdot F05/v$$

EP 1 400 927 A1

$$+0 \cdot F06/v+0 \cdot F07/v+0 \cdot F08/v \quad (92)$$

5

$$\begin{aligned} C04=1 \cdot F01/v+1 \cdot F02/v+1 \cdot F03/v+1 \cdot F04/v+0 \cdot F05/v \\ +0 \cdot F06/v+0 \cdot F07/v+0 \cdot F08/v \end{aligned} \quad (93)$$

10

$$\begin{aligned} C05=1 \cdot F01/v+1 \cdot F02/v+1 \cdot F03/v+1 \cdot F04/v+1 \cdot F05/v \\ +0 \cdot F06/v+0 \cdot F07/v+0 \cdot F08/v \end{aligned} \quad (94)$$

15

$$\begin{aligned} C06=0 \cdot F01/v+1 \cdot F02/v+1 \cdot F03/v+1 \cdot F04/v+1 \cdot F05/v \\ +1 \cdot F06/v+0 \cdot F07/v+0 \cdot F08/v \end{aligned} \quad (95)$$

20

$$\begin{aligned} C07=0 \cdot F01/v+0 \cdot F02/v+1 \cdot F03/v+1 \cdot F04/v+1 \cdot F05/v \\ +1 \cdot F06/v+1 \cdot F07/v+0 \cdot F08/v \end{aligned} \quad (96)$$

25

$$\begin{aligned} C08=0 \cdot F01/v+0 \cdot F02/v+0 \cdot F03/v+1 \cdot F04/v+1 \cdot F05/v \\ +1 \cdot F06/v+1 \cdot F07/v+1 \cdot F08/v \end{aligned} \quad (97)$$

30

$$\begin{aligned} C09=0 \cdot F01/v+0 \cdot F02/v+0 \cdot F03/v+0 \cdot F04/v+1 \cdot F05/v \\ +1 \cdot F06/v+1 \cdot F07/v+1 \cdot F08/v \end{aligned} \quad (98)$$

35

$$\begin{aligned} C10=0 \cdot F01/v+0 \cdot F02/v+0 \cdot F03/v+0 \cdot F04/v+0 \cdot F05/v \\ +1 \cdot F06/v+1 \cdot F07/v+1 \cdot F08/v \end{aligned} \quad (99)$$

40

$$\begin{aligned} C11=0 \cdot F01/v+0 \cdot F02/v+0 \cdot F03/v+0 \cdot F04/v+0 \cdot F05/v \\ +0 \cdot F06/v+1 \cdot F07/v+1 \cdot F08/v \end{aligned} \quad (100)$$

45

$$\begin{aligned} C12=0 \cdot F01/v+0 \cdot F02/v+0 \cdot F03/v+0 \cdot F04/v+0 \cdot F05/v \\ +0 \cdot F06/v+0 \cdot F07/v+1 \cdot F08/v \end{aligned} \quad (101)$$

[0500] Equations (90) to (102) may be expressed as an equation (102).

$$C_j = \sum_{i=01}^{08} a_{ij} \cdot F_{i/v} \quad (102)$$

[0501] In equation (102), j means the position of pixel. In this example, j is one of 1 to 12. Further, i means the position of foreground value. In this example, i is one of 1 to 8. a_{ij} is 0 or 1 according to the values of i and j.

[0502] Considering an error, equation (102) is expressed as equation (103).

$$C_j = \sum_{i=01}^{08} a_{ij} \cdot F_i / v + e_j \quad (103)$$

[0503] In equation (103), e_j is an error included in indicated pixel C_j .

[0504] Equation 103 can be expressed as equation 104 again.

$$e_j = C_j - \sum_{i=01}^{08} a_{ij} \cdot F_i / v \quad (104)$$

[0505] Here, sum of the square of errors E is defined as shown in equation (105) to apply the least square method.

$$E = \sum_{j=01}^{12} e_j^2 \quad (105)$$

[0506] In order to minimize the error, the value of the partial differential by the variable F_k to the sum of the square of errors E should equal zero. F_k satisfying equation (106) is obtained.

$$\begin{aligned} \frac{\partial E}{\partial F_k} &= 2 \cdot \sum_{j=01}^{12} e_j \cdot \frac{\partial e_j}{\partial F_k} \\ &= 2 \cdot \sum_{j=01}^{12} \left\{ \left(C_j - \sum_{i=01}^{08} a_{ij} \cdot F_i / v \right) \cdot (-a_{kj} / v) \right\} = 0 \end{aligned} \quad (106)$$

[0507] In equation (106), because the amount of movement v is fixed, equation (107) can be derived.

$$\sum_{j=01}^{12} a_{kj} \cdot \left(C_j - \sum_{i=01}^{08} a_{ij} \cdot F_i / v \right) = 0 \quad (107)$$

[0508] Equation (108) is obtained by expanding and transposing equation (107).

$$\sum_{j=01}^{12} (a_{kj} \cdot \sum_{i=01}^{08} a_{ij} \cdot F_i) = v \cdot \sum_{j=01}^{12} a_{kj} \cdot C_j \quad (108)$$

[0509] Equation (108) is expanded in 8 equations obtained by substituting one of integers between 1 and 8 for k in equation (108). The obtained 8 equations can be expressed as a matrix equation, and this matrix equation is called a normal equation.

[0510] An example of a normal equation generated by the equation generator 803 based on the least square method is shown in equation (109).

$$\begin{bmatrix}
 5 & 4 & 3 & 2 & 1 & 0 & 0 & 0 \\
 4 & 5 & 4 & 3 & 2 & 1 & 0 & 0 \\
 3 & 4 & 5 & 4 & 3 & 2 & 1 & 0 \\
 2 & 3 & 4 & 5 & 4 & 3 & 2 & 1 \\
 1 & 2 & 3 & 4 & 5 & 4 & 3 & 2 \\
 0 & 1 & 2 & 3 & 4 & 5 & 4 & 3 \\
 0 & 0 & 1 & 2 & 3 & 4 & 5 & 4 \\
 0 & 0 & 0 & 1 & 2 & 3 & 4 & 5
 \end{bmatrix}
 \begin{bmatrix}
 F01 \\
 F02 \\
 F03 \\
 F04 \\
 F05 \\
 F06 \\
 F07 \\
 F08
 \end{bmatrix}
 = v \cdot
 \begin{bmatrix}
 \sum_{i=0}^8 C_i \\
 \sum_{i=0}^7 C_i \\
 \sum_{i=0}^6 C_i \\
 \sum_{i=0}^5 C_i \\
 \sum_{i=0}^4 C_i \\
 \sum_{i=0}^3 C_i \\
 \sum_{i=0}^2 C_i \\
 \sum_{i=0}^1 C_i
 \end{bmatrix}
 \quad (109)$$

[0511] If equation (109) is expressed as $A \cdot F = v \cdot C$, C , A and v are known and F is unknown. A and v are known at the time of model forming and C is already known by inputting the pixel values in adding operation.

[0512] Errors included in pixel C can be dispersed by calculating the foreground component by using the normal equation based on the least square method.

[0513] The equation generator 803 supplies the normal equation generated by the above to the adder 804.

[0514] The adder 804 sets the pixel values C included in foreground component image in the matrix equation supplied from the equation generator 803 on the basis of the unit of processing supplied from the unit of processing determining portion 801. The adder 804 supplies the matrix where the pixel values C are set to the calculator 805.

[0515] The calculator 805 calculates the foreground component F_i/v from which motion blur is eliminated through the processing based on the sweeping-out methods such as Gauss-Jordan elimination method, calculates F_i corresponding to the pixel value i of the foreground from which motion blur is eliminated, wherein i is one of integers between 0 and 8, and then outputs the foreground component image from which motion blur is eliminated, along with the calculated pixel value F_i to the motion blur adder 806 and the selector 807.

[0516] Further, as shown in FIG. 100, for making the position of the foreground component image unchanged with respect to the screen, each of $F01$ to $F08$ is set to each of $C03$ to $C10$ in the foreground component image from which motion blur is eliminated. However, it may correspond to arbitrary positions.

[0517] The motion blur adder 806 may adjust the amount of motion blur by adding the amount by which motion blur is adjusted v' which is different from the amount of movement v , for example, the amount by which motion blur is adjusted v' is half of the amount of movement v , or has no relation with the amount of movement v . For example, as shown in FIG. 101, the motion blur adder 806 calculates the foreground component F_i/v' by dividing the foreground pixel value from which motion blur is eliminated F_i with the amount by which motion blur is adjusted v' , calculates the sum of the foreground components F_i/v' , and then generates the pixel value where the amount of motion blur is adjusted. For example, when the amount by which motion blur is adjusted is 3, the pixel value $C02$ becomes $(F01)/v'$, the pixel value $C03$ becomes $(F01+F02)/v'$, the pixel value $C04$ becomes $(F01+F02+F03)/v'$ and the pixel value $C05$ becomes $(F02+F03+F04)/v'$.

[0518] The motion blur adder 806 supplies the foreground component image of which the amount of motion blur is adjusted to the selector 807.

[0519] The selector 807 selects one of the foreground component image from which motion blur is eliminated and which is supplied from the calculator 805 and the foreground component image of which the amount of motion blur is adjusted and which is supplied from the motion blur adder 806 on the basis of the selection signal selected by a user, and then outputs the selected foreground component image.

[0520] Like the above, the motion blur adjusting unit 106 is able to adjust the amount of motion blur based on the selection signal and the amount v' by which motion blur is adjusted.

[0521] Further, for example, as shown in FIG. 102, when the number of pixels corresponding to the unit of processing is 8 and the amount of movement v is 4, the motion blur adjusting unit 106 generates the matrix equation shown in equation (110).

includes the motion blur based on the motion vector and the positional information thereof.

[0533] That is, it is possible to adjust the amount of motion blur included in the pixel values which are sample data.

[0534] FIG. 105 is a block diagram showing another example of a configuration of the motion blur adjusting unit 106. The motion vector and the positional information thereof supplied from the motion detector 102 are supplied to a unit of processing determining portion 901 and a adjusting portion 905, and the area information supplied from the area specifying unit 103 is supplied to the unit of processing determining portion 901. The foreground component image supplied from the foreground/background separator 105 is supplied to calculator 904.

[0535] The unit of processing determining portion 901 generates a unit of processing based on the motion vector and positional information thereof, and the area information, and then supplies the generated unit of processing to the model forming portion 902 along with the motion vector.

[0536] The model forming portion 902 performs the model forming based on the motion vector and the input unit of processing. More specifically, the model forming portion 902 stores, for example, a plurality of models corresponding to the number of pixels included in the unit of processing, the virtual division number of the pixel value in time direction and the number of the foreground components for each pixel in advance, selects a specifying model corresponding to the pixel value and the foreground component shown in FIG. 106 on the basis of the unit of processing and the virtual division number of the pixel value in time direction.

[0537] For example, if the number of pixels corresponding to the unit of processing is 12 and the amount of movement v is 5, the model forming portion 902 selects the model, totally comprised 8 foreground components and where the number of division is 5, the leftmost pixel includes one foreground component, the second pixel from the leftmost includes two foreground components, the third pixel from the leftmost includes three foreground components, the fourth pixel from the leftmost includes four foreground components, the fifth pixel from the leftmost includes five foreground components, the sixth pixel from the leftmost includes five foreground components, the seventh pixel from the leftmost includes five foreground components, the eighth pixel from the leftmost includes five foreground components, the ninth pixel from the leftmost includes four foreground components, the tenth pixel from the leftmost includes three foreground components, the eleventh pixel from the leftmost includes two foreground components, the twelfth pixel from the leftmost includes one foreground component.

[0538] Further, the model forming portion 902 may not select one of the models stored in advance, but generates a model based on the motion vector and the unit of processing when the motion vector and the unit of processing are supplied.

[0539] The equation generator 903 generates equations based on the model supplied from the model forming portion 902.

[0540] Referring to models of the foreground component image shown in FIGs. 106 to 108, examples of the equations generated by the equation generator 903 is explained when the number of the foreground components is 8, the number of the pixels corresponding to the unit of processing is 12 and the amount of movement v is 5.

[0541] When the foreground component corresponding to (shutter time)/ v included in the foreground component image is between $F01/v$ and $F08/v$, the relationship between $F01/v$ to $F08/v$ and the pixel values $C01$ to $C12$ are expressed in equations (78) to (89) as mentioned earlier.

[0542] Paying attention to the pixel values $C12$ and $C11$, the pixel value $C12$ comprise only the foreground component $F08/v$ as shown in equation (111) and the pixel value $C11$ comprise the sum of the foreground components $F08/v$ and $F07/v$. Therefore, the foreground component $F07/v$ can be obtained from equation (112).

$$F08/v = C12 \quad (111)$$

$$F07/v = C11 - C12 \quad (112)$$

[0543] In the same manner, referring to the foreground components included in the pixel values $C10$ to $C01$, the foreground components $F06/v$ to $F01/v$ can be obtained by the equations (113) to (118).

$$F06/v = C10 - C11 \quad (113)$$

$$F05/v = C09 - C10 \quad (114)$$

$$F04/v = C08 - C09 \quad (115)$$

responding to the unit of processing are not extracted, the procedure returns to step S904 and the processing for extracting the foreground components is repeated.

[0557] In step S905, if it is determined that all the foreground components corresponding to unit of processing are extracted, the procedure proceeds to step S906, and the adjusting portion 905 corrects each of the foreground components F01/v to F08/v supplied from the calculator 904 based on the amount v of movement and then calculates the pixel values F01 to F08 from which the motion blur is eliminated.

[0558] In step S907, the motion blur adder 906 calculates the pixel values of the foreground where amount of motion blur is adjusted, the selector 907 selects either the image in which amount of movement is eliminated or the image in which amount of movement is adjusted and outputs the selected image, and then the procedure is finished.

[0559] Like the above, the motion blur adjusting unit 106 having the configuration shown in FIG. 105 can adjust motion blur by foreground image in which motion blur is included more rapidly by more simple operations.

[0560] Conventional methods for eliminating motion blur such as Wiener-filter, etc., are effective in ideal conditions, but are not effective for the quantized real images having noises. However, this method using the motion blur adjusting unit 106 having the structure shown in FIG. 105 is sufficiently effective for the quantized real images having noises and it is possible to eliminate the motion blur precisely.

[0561] As mentioned above, the separation server 11 having the structure shown in FIG. 27 can adjust the amount of motion blur belonging to the input image.

[0562] FIG. 110 is a block diagram showing another configuration of the separation server 11.

[0563] The same portions as those in FIG. 27 are given with the same reference numerals and the description thereof will be omitted adequately.

[0564] The area specifying unit 103 supplies the area information to the mixture ratio calculator 104 and the synthesizer 1001.

[0565] The mixture ratio calculator 104 supplies the mixture ratio α to the foreground/background separator 105 and the synthesizer 1001.

[0566] The foreground/background separator 105 the foreground component image to the synthesizer 1001.

[0567] The synthesizer 1001 synthesizes any background image and the foreground component image supplied from the foreground/background separator 105 based on the mixture ratio α supplied from the mixture ratio calculator 104 and the area information supplied from the area specifying unit 103, and then output the synthesized image corresponding to the background image or the foreground component image.

[0568] FIG. 111 is a drawing showing a configuration of the synthesizer 1001. The background component generator 1021 generates the background component image based on the mixture ratio α and any background image, and then supplies the generated background component image to the mixed area image synthesizing portion 1022.

[0569] The mixed area image synthesizing portion 1022 generates the mixed area synthesized image by synthesizing the background component image supplied from the background component generator 1021 and the foreground component and then supplies the generated mixed area synthesized image to the image synthesizing portion 1023.

[0570] The image synthesizing portion 1023 synthesizes the foreground component image, the mixed area synthesized image supplied from the mixed area image synthesizing portion 1022 and any background image based on the area information to generate and output the synthesized image.

[0571] Like the above, the synthesizer 1001 can synthesize the foreground component image and any background image.

[0572] The image obtained by synthesizing the foreground component image and any background image based on the feature amount of the mixture ratio α is more natural when compared to the image obtained by synthesizing only the pixels.

[0573] FIG. 112 is a block diagram showing another configuration of the separation server 11 which has adjusted the amount of motion blur. The separation server 11 shown in FIG. 27 performs the area specification and calculates of the mixture ratio α serially, while the separation server 11 shown in FIG. 112 performs the area specification and calculates of the mixture ratio α in parallel.

[0574] The same portions as those in FIG. 27 are given with the same reference numerals and the description thereof will be omitted.

[0575] The input image is supplied to the mixture ratio calculator 1101, the foreground/background separator 1102, the area specifying unit 103 and the object extracting unit 101.

[0576] The mixture ratio calculator 1101 calculates an estimated mixture ratio supposing that the pixel belongs to the covered background area and calculates an estimated mixture ratio supposing that the pixel belongs to the uncovered background area for each pixel belonging to the input image on the basis of the input image, and supplies the estimated mixture ratio for the case supposing that the pixel belongs to the covered background area and the estimated mixture ratio in the case that supposes the pixel belongs to the uncovered background area to the foreground/background separator 1102.

[0577] FIG. 113 is a block diagram showing an example of a configuration of the estimated mixture ratio calculator

1101.

[0578] An estimated mixture ratio processor 401 shown in FIG. 113 is the same as the estimated mixture ratio processor 401 shown in FIG. 72. An estimated mixture ratio processor 402 shown in FIG. 113 is the same as the estimated mixture ratio processor 402 shown in FIG. 72.

[0579] The estimated mixture ratio processor 401 calculates an estimated mixture ratio for each pixel using the calculation corresponding to a model of the covered background area based on the input image, and then outputs the calculated estimated mixture ratio.

[0580] The estimated mixture ratio processor 402 calculates an estimated mixture ratio for each pixel using the calculation corresponding to a model of the uncovered background area based on the input image, and then outputs the calculated estimated mixture ratio.

[0581] The foreground/background separator 1102 generates a foreground component image from the input image, based on the estimated mixture ratio for the case that supposes the pixel belongs to the covered background area, the estimated mixture ratio for the case that supposes the pixel belongs to the uncovered background area which are supplied from the mixture ratio calculator 1101, and based on the area information supplied from the area specifying unit 103, and then supplies the generated foreground component image to the motion blur adjusting unit 106 and the selector 107.

[0582] FIG. 114 is a block diagram showing an example of a configuration the foreground/background separator 1102.

[0583] The same portions as those in the foreground/background separator 105 shown in FIG. 89 are given with the same reference numerals and the description thereof will be omitted.

[0584] The selector 1121 selects the estimated mixture ratio for the case that supposes the pixel belongs to the covered background area or the estimated mixture ratio for the case that supposes the pixel belongs to the uncovered background area which are supplied from the mixture ratio calculator 1101, based on the area information supplied from the area specifying unit 103, and then supplies the selected estimated mixture ratio as the mixture ratio α to the separating portion 601.

[0585] The separating portion 601 extracts the foreground component and background component from the pixel values of the pixel belonging to the mixed area based on the mixture ratio and the area information supplied from the selector 1121, supplies the extracted foreground component to the synthesizer 603 and supplies the extracted background component to the synthesizer 605.

[0586] The separating portion 601 can have the same configuration shown in FIG. 94.

[0587] The synthesizer 603 synthesizes and outputs the foreground component image. The synthesizer 605 synthesizes and outputs the background component image.

[0588] The motion blur adjusting unit 106 shown in FIG. 112, which may have the same structure as the configuration shown in FIG. 27, adjusts the amount of motion blur belonging to the foreground component image supplied from the foreground/background separator 1102 based on the area information and the motion vector, and then outputs the foreground component image where the amount of motion blur is adjusted.

[0589] The selector 107 shown in FIG. 112 selects either the foreground component image supplied from the foreground/background separator 1102 or the foreground component image in which the motion blur is adjusted supplied from the motion blur adjusting unit 106 based on the selection signal corresponding the selection of a user, and then output the selected foreground component image.

[0590] Like the above, the separation server 11 having the configuration shown in FIG. 112 can adjust the amount of motion blur included in the image corresponding to the foreground object included in the input image and outputs it. The separation server 11 having the configuration shown in FIG. 112 can calculate a mixture ratio α of buried information and output the calculated mixture ratio α as the same manner in the first embodiment.

[0591] FIG. 115 is a block diagram showing another configuration of the separation server 11 for synthesizing the foreground component image and any background image. The separation server 11 shown in FIG. 110 performs the area specification and the calculation of the mixture ratio α serially. But the separation server 11 shown in FIG. 115 performs the area specification and the calculation of the mixture ratio α in parallel.

[0592] The same portions as those in FIG. 112 are given with the same reference numerals and the description thereof will be omitted.

[0593] The mixture ratio calculator 1101 shown in FIG. 115 calculates an estimated mixture ratio for the case that supposes the pixel belongs to the covered background area and an estimated mixture ratio for the case that supposes the pixel belongs to the uncovered background area for each pixel belonging to the input image on the basis of the input image, and supplies the estimated mixture ratio for the case that supposes the pixel belongs to the covered background area and the estimated mixture ratio for the case that supposes the pixel belongs to the uncovered background area to the foreground/background separator 1102 and the synthesizer 1201.

[0594] The foreground/background separator 1102 shown in FIG. 115 generates a foreground component image from the input image based on the estimated mixture ratio for the case that supposes the pixel belongs to the covered background area and the estimated mixture ratio for the case that supposes the pixel belongs to the uncovered back-

receives the foreground component image, the background component image and ID thereof transmitted from the separation server 11, stores them in its own storage unit 48 (see FIG. 2) and prints out them as needed. Further, the client computer 27 may make the separation server 11 store in its own storage unit the foreground component image and the background component image separated by the separation server 11 or output them to the storage server 18 via the network 1 so as to store them according to the instructions of a user.

[0625] In the above explanation, the separating process has been described when the service fee has been paid to the financial transaction servers 25, 26 by the account charge server 24. However, the charge processing may be performed, by storing points, such as pre-paid points, indicating that the user has previously paid the service fee to the provider of the separating service in the storage unit 48 (see FIG. 2) and deducting the points at every time the user is provided with the separating service.

[0626] Here, referring to a flowchart of FIG. 120, the charge processing using the pre-paid points will be explained.

[0627] In step S1201, the client computer 27 specifies the service and transmits the ID information and the verification information. That is, the client computer 27 performs the same processing as that in step S1101 of FIG. 117.

[0628] In step S1211, the charge processor 11a of the separation server 11 receives the ID information and the verification information. In step S1212, the charge processor 11a subtracts the points corresponding to the service fee for the separation processing from the pre-paid points which is stored in storage unit 48 corresponding to the amount of money previously paid by the user of the client computer 27 and stores it. In step S1213, the separation server 11 provides the service. That is, at this time, the separation server 11 performs the separation processing of the input image and transmits the foreground component image and the background component image separated to the client computer 27.

[0629] In step S1202, the client computer 27 receives the provided service. That is, at this time, the client computer 27, receives the foreground component image and the background component image transmitted from the separation server 11.

[0630] Further, in the above explanation, a case that the separation server 11 stores the pre-paid points in its own storage unit 48 (see FIG. 2) has been described but for example, when a card in which the pre-paid points are stored, so called a pre-paid card is used, the same processing is performed. In this case, it is required that the client computer 27 read out and transmits the pre-paid points stored in the pre-paid card in step S1201, the separation server 11 subtract the points corresponding to the service fee from the points received by the charge processing and the points subtracted is transmitted to the client computer to update the pre-paid card.

[0631] Next, referring to the flowchart of FIG. 121, the processing of the motion detecting service for obtaining the motion vector and the positional information of the image specified by the client computer 27 will be explained.

[0632] In step S1301, the client computer 27 outputs the information specifying an image to the motion detecting server 12. That is, as the information specifying the image desired by a user to be processed by the motion detecting process, the specific image or the image ID specifying the image is output to the motion detecting server 12.

[0633] In step S1311, the motion detecting server 12 obtains the specified image. That is, the motion detecting server 12 reads out and obtains the very image when an image is transmitted from the client computer 27 or the image corresponding to the image ID when the specification information is transmitted, via the network 1.

[0634] In steps S1312 and S1321, the charge processor 12c of the motion detecting server 12 and the account charge server 24 perform the charge processing. Further, the charge processing is similar to that in the separating service in FIG. 118 and FIG. 120 and thus, explanation thereof will be omitted.

[0635] In step S1313, the object extracting unit 12a of the motion detecting server 12 extracts each object from the specified image obtained, and the motion detector 12b detects the positional information and the motion vector, to transmit it to the client computer 27.

[0636] In step S1302, the client computer 27 receives and stores the positional information and the motion vector of the object transmitted from the motion detecting server 12.

[0637] Further, the client computer 27 may store the positional information and the motion vector detected by the motion detecting server 12 in its own storage unit or output them to the storage server 18 via the network 1 so as to store them, in accordance with instructions of the user.

[0638] Next, referring to the flowchart of FIG. 122, the processing of the area specifying service specifying area from the information specifying the image and object input from the client computer 27, which is performed by the area specifying server 13, will be explained.

[0639] In step S1401, the client computer 27 outputs the information specifying the image and the object to the area specifying server 13. That is, the information specifying the object is output to the area specifying server 13 along with the specific image or the image ID specifying the image as the information specifying an image desired by a user to area specify.

[0640] In step S1411, the area specifying server 13 obtains the specified image. That is, the area specifying server 13 reads out and obtains the very image when the image is transmitted from the client computer 27 and the image corresponding to the image ID when the image ID specifying an image is transmitted, via the network 1.

[0641] In steps S1412 and S1421, the charge processor 13a of the area specifying server 13 and the account charge server 24 performs the charge processing. Further, the charge processing is similar to that in the separating service in FIG. 118 and FIG. 120 and thus, explanation thereof will be omitted.

[0642] In step S1413, the area specifying server 13 performs the area specifying processing on the basis of the information specifying the object. Further, the area specifying processing is similar to the processing explained referring to the flowchart of FIG. 53 and thus, explanation thereof will be omitted.

[0643] In step S1414, the area specifying server 13 transmits the area information obtained through the processing in step S1413 to the client computer 27.

[0644] In step S1402, the client computer 27 receives and stores the area information transmitted from the area specifying server 13.

[0645] Further, the client computer 27 may store the area information obtained by the area specifying server 13 in its own storage unit or output it to the storage server 18 via the network 1 so as to store it, in accordance with instructions of the user.

[0646] Next, referring to a flowchart of FIG. 123, the processing of the mixture ratio calculating service of calculating the mixture ratio from the information specifying the image and the object and the area information input from the client computer 27, which is performed by the mixture ratio calculating server 14, will be explained.

[0647] In step S1501, the client computer 27 outputs, the information specifying the image and the object and the area information to the mixture ratio calculating server 14.

That is, as the information specifying an image of which mixture ratio is desired by a user to specify, the specific image or the image ID specifying the image, the information specifying the object and the area information are output to the mixture ratio calculating server 14.

[0648] In step S1511, the mixture ratio calculating server 14 obtains the specified image. That is, the mixture ratio calculating server 14 reads out and obtains the very image when the image is transmitted from the client computer 27 and the image corresponding to the image ID when the image ID specifying an image is transmitted, via the network 1.

[0649] In steps S1512 and S1521, the charge processor 14a of the mixture ratio calculating server 14 and the account charge server 24 performs the charge processing. Further, the charge processing is similar to that in the separating service in FIG. 118 and FIG. 120 and thus, explanation thereof will be omitted.

[0650] In step S1513, the mixture ratio calculating server 14 performs the mixture ratio calculation processing on the basis of the information specifying the object and the area information. Further, the mixture ratio calculation processing is similar to the processing explained referring to the flowchart of FIG. 81 and thus, explanation thereof will be omitted.

[0651] In step S1514, the mixture ratio calculating server 14 transmits the mixture ratio obtained through the processing in step S1513 to the client computer 27.

[0652] In step S1502, the client computer 27 receives and stores the mixture ratio transmitted from the mixture ratio calculating server 14.

[0653] Further, the client computer 27 may store the mixture ratio obtained by the mixture ratio calculating server 14 in its own storage unit or output it to the storage server 18 via the network 1 so as to store it, in accordance with instructions of the user.

[0654] Next, referring to the flowchart of FIG. 124, the processing of service for separating the foreground component image and the background component image from the information specifying the image and the object, the area information and the mixture ratio input from the client computer 27, which is performed by the foreground/background image separating server 15, will be explained.

[0655] In step S1601, the client computer 27 outputs, the information specifying the image and the object, the area information and the information of mixture ratio to the foreground/background image separating server 15. That is, as the information specifying an image desired by a user to separate into foreground and background, the concrete image or the image ID specifying the image, the information specifying the object, the area information and the information of mixture ratio are output to the foreground/background image separating server 15.

[0656] In step S1611, the foreground/background image separating server 15 obtains the specified image. That is, the foreground/background image separating server 15 reads out and obtains the very image when the image is transmitted from the client computer 27 and the image corresponding to the image ID when the image ID specifying an image is transmitted, via the network 1.

[0657] In steps S1612 and S1621, the charge processor 15a of the foreground/background image separating server 15 and the account charge server 24 performs the charge processing. Further, the charge processing is similar to that in the separating service in FIG. 118 and FIG. 120 and thus, explanation thereof will be omitted.

[0658] In step S1613, the foreground/background image separating server 15 performs the foreground/background separating processing on the basis of the information specifying the object, the area information and the mixture ratio. Further, the foreground/background separating processing is similar to the processing explained referring to the flowchart of FIG. 96 and thus, explanation thereof will be omitted.

[0659] In step S1614, the foreground/background image separating server 15 generates IDs to the foreground com-

specifying the image and the information specifying the object are output to the encoding server 17.

[0675] In step S1811, the encoding server 17 obtains the specified image. That is, the encoding server 17 reads out and obtains the very image when the image is transmitted from the client computer 27 and the image corresponding to the image ID when the image ID specifying an image is transmitted, via the network 1.

[0676] In steps S1812 and S1821, the charge processor 17a of the encoding server 17 and the account charge server 24 perform the charge processing. Further, the charge processing is similar to that in the separating service in FIG. 118 and FIG. 120 and thus, explanation thereof will be omitted.

[0677] In step S1813, the separation portion 2002 of the encoding server 17 performs the image separating processing. Further, the image separating processing is similar to the processing explained referring to step S1013 in the flowchart of FIG. 117 and thus, explanation thereof will be omitted.

[0678] In step S1814, the encoding server 17 outputs the foreground component image and the background component image obtained through the processing in step S1813 to the storage server 18 so as to store them. In step S1813, the storage server 18 stores the foreground component image and the background component image transmitted.

[0679] In step S1815, the encoding server 17 adds the motion vector and the positional information to the positional information of foreground component image and the positional information of background component image generated through the encoding processing and transmits them to the client computer 27.

[0680] In step S1802, the client computer 27 receives and stores the positional information of foreground component image, the positional information of background component image, the motion vector and the positional information transmitted from the encoding server 17.

[0681] Further, in a case of separating and encoding the input image, the encoder 2001 may add only data corresponding to the difference to the code (positional information of the image) of the image already encoded to output it when image similar to a pre-encoded image is encoded. For example, in a case of synthesizing the image shown in FIG. 128, when the encoding information of a first image including encoding information of a foreground component image 1, a foreground component image 2 and a mixture ratio 1 and the encoding information of a second image including encoding information of a foreground component image 1, a foreground component image 3 and a mixture ratio 2 are synthesized, since the foreground component image 1 is also included in any image information, the foreground component image 1 of any of the images may be omitted when synthesizing and consequently, the compression rate can be improved as much as the information of the foreground component image 1 to be omitted, compared with a case that both images are simply synthesized.

[0682] Consequently, when the first image and the second image shown in FIG. 128 are stored, if the first image is first stored, only the encoding information of the mixture ratio 2 and the foreground component image 3 that is a difference may be stored for the second image. For this reason, when the encoding information of the same image is stored repeatedly, the compression rate improves as the number of the stored images increases.

[0683] Further, the mixture ratio, the motion vector and the positional information to be encoded by the encoding server 17 may be the information specified by a user, as shown in FIG. 129. Further, as shown in FIG. 129, for the image to be encoded, the foreground component image and the background component image corresponding to the image ID specified by the user may be read out from the storage server 18 and encoded. In this case, the encoding server 17 may not be provided with the separation portion 2002.

[0684] Further, although the image ID has been employed as the information specifying image in the present invention, the image positional information may be employed instead.

[0685] Next, referring to a flowchart of FIG. 130, the processing of service for synthesizing the specified images A and B from the information specifying the images A and B input from the client computer 27, the motion vector, the mixture ratio, the positional information and the amount by which motion blur is adjusted, which is performed by the synthesizing server 19, will be explained.

[0686] In step S1901, the client computer 27 outputs the information specifying the images A and B, the motion vector, the mixture ratio, the positional information and the information of amount by which motion blur is adjusted to the synthesizing server 19. That is, as the information specifying the images A and B desired by a user to synthesize, the specific image or the image A ID and B ID (may be the aforementioned positional information of encoded images) specifying the images A and B, the motion vector, the mixture ratio, the positional information and the information of amount by which motion blur is adjusted are output to the synthesizing server 19.

[0687] In step S1911, the synthesizing server 16 obtains the specified images. That is, the synthesizing server 19 reads out and obtains the very image when the images are transmitted from the client computer 27 and the images corresponding to the image IDs when the image IDs specifying images are transmitted, via the network 1.

[0688] In steps S1912 and S1921, the charge processor 19a of the synthesizing server 19 and the account charge server 24 perform the charge processing. Further, the charge processing is similar to that in the separating service in FIG. 118 and FIG. 120 and thus, explanation thereof will be omitted. Further, the charge processing may be omitted in a case that the user accepting the encoding service has been charged by using the encoding server 16. Inversely,

in place of the user accepting the encoding service, the user accepting the synthesizing service may be charged.

[0689] In step S1913, the synthesizing server 19 performs the processing of synthesizing the images A and B on the basis of the motion vector, the mixture ratio, the positional information and the information of amount by which motion blur is adjusted.

5 [0690] In step S1914, the synthesizing server 19 generates ID for the synthesized image (A+B) obtained through the processing in step S1913 and transmits it to the client computer 27.

[0691] In step S1902, the client computer 27 receives and stores the synthesized image (A+B) transmitted from the synthesizing server 19.

10 [0692] Further, the client computer 27 may store the synthesized image (A+B) transmitted from the synthesizing server 19 in its own storage unit or output it to the storage server 18 via the network 1 so as to store it, in accordance with instructions of the user.

[0693] As described above, although the synthesizing server 20 is made to be able to synthesize a plurality of images it may generate the encrypted image by adding the motion blur of the synthesized image using the amount by which motion blur is adjusted as a key. FIG. 131 shows a configuration of the motion blur adder 2021 for encryption, provided
15 to make the synthesizing server 20 generate the encrypted image.

[0694] The input information processor 2031 of the motion blur adder for encryption 2021 outputs the input signal to be encrypted to the imaging portion 2032, outputs information of an encrypting key to the motion blur adder 2033 and outputs the image selection information for selecting image (background component image) desired to synthesize by using the signal to be encrypted as the foreground component image to the synthesizing server 20, respectively.

20 [0695] When the signal to be encrypted input from the input information processor 2031 is not image signal, the imaging portion 2032 converts the signal into the image signal to output it to the motion blur adder 2033. That is, since the encrypted signal is supposed to be image signal, the imaging portion 2032 images the signal that is not image signal in order to correspond with such processing.

[0696] The motion blur adder 2033 generates the amount by which motion blur is adjusted on the basis of the information such as speed or direction input from the input information processor 2031 and adds the motion blur to the image signal input from the imaging portion 2032 to output it to the synthesizing server 20. The synthesizing server 20 obtains the background component image on the basis of the image selection information input from the input information processor 2031 and synthesizes the image input from the motion blur adder 2033 as the foreground component image with the obtained background component image to generate and display the synthesized image. At this
30 time, the image selection information specifying the background component image may be the background component image itself and may be the positional information of background component image or ID of the background component image.

[0697] Next, referring to FIG. 132, the motion blur eliminating portion for encryption 2041 for decrypting the synthesized image encrypted by the motion blur adder for encryption 2021 provided in the synthesizing server 20 to convert it into the original signal will be explained. Further, the motion blur adder for encryption 2021 and the motion blur eliminating portion for encryption 2041 shown in FIG. 131 and FIG. 132 may be thought, for example, to be a functional
35 block diagram of software built-in to the client computer 27 and to be a block diagram of hardware. Further, the motion blur adder for encryption 2021 and the motion blur eliminating portion for encryption 2041 may be constructed as an exclusive server on the network 1.

40 [0698] The separation server 11 separates the encrypted synthesized image into the foreground component image and the background component image and outputs the foreground component image to which motion blur is added to the input information processor 2051.

[0699] When the encrypted foreground component image input from the separation server 11 and the information on speed and direction as a key for decrypting the encrypted foreground component image are input, the input information processor 2051 output them to the motion blur eliminating portion 2052. When the image is displayed in 2-dimensions of x direction and y direction, the speed and the direction of the key are set thereto, respectively.

[0700] The motion blur eliminating portion 2052 generates the amount of motion blur on the basis of the information of speed and direction input from the input information processor 2051, performs the motion blur adding processing inverse to the motion blur adding processing performed by the motion blur adder for encryption 2021 on the encrypted foreground component image, and decrypts the encrypted foreground component image to output it to the signal converter 2053. When the encrypted signal to be encrypted is not image signal, the signal converter 2053 converts the image signal input from the motion blur eliminating portion 2052 into the original signal to output it.

55 [0701] That is, the motion blur adder 2033 (see FIG. 131) and the motion blur eliminating portion 2052 performs substantially the processing similar to the motion blur adder 806 in FIG. 97 and performs the motion blur adding processing inverse to each other using the amount by which motion blur is adjusted as the encrypting key. However, they are different in that gain-up processing is further performed on the motion blur adding processing first performed in the motion blur adding processes in x direction or y direction to be described below.

[0702] Here, principles in which the image signal is encrypted by adding the motion blur will be explained. For ex-

$B6 \times 2/5 + ux2 + px3 + lx4$, the pixel value $Ky' = B7 \times 3/5 + ux3 + px4$ and the pixel value $Py' = B8 \times 4/5 + ux4$.

[0722] By performing all these processes in all the y direction, the synthesized image of which the background component image is the encrypted foreground component image shown in FIG. 150 is generated. That is, the input image of 5×5 pixels is converted into the image of 9×9 pixels (the pixels A to Y, the pixels Ax to Dx, the pixels Fx to lx, the pixels Kx to Nx, the pixels Px to Sx, the pixels Ux to Xx, the pixels Ay' to Ty', the pixels Ax' to Dx', the pixels Fx' to lx', the pixels Kx' to Nx' and the pixels Px' to Sx').

[0723] Further, since is the motion blur adding processing in the motion blur eliminating portion for encryption 2041, in the reverse of the processing by the motion blur adder for encryption 2021, explanation of the decrypting processing will be omitted.

[0724] Further, in the processing of step S2006, when encryption in the x direction is performed, the gain-up processing is performed and then, encryption in the y direction is performed. Therefore, it is necessary that after decryption in the y direction is performed, the gain is lowered, and then the decryption in the x direction is performed. Further, the order of the encryptions in the x direction and the y direction may be changed. However, since the gain-up processing is performed in the direction where the encryption is formerly performed, it is necessary that the order of decryptions should correspond to the order of encryptions.

[0725] Next, referring to the flowchart of FIG. 151, the encrypting service by the synthesizing server 19 comprising the motion blur adder for encryption 2021 shown in FIG. 131 will be explained. Further, this is a processing that the client computer 27-1 connected to the network 1 transmits the signal to be encrypted to the synthesizing server 19, which encrypts it and transmits it to the client computer 27-2. Further, the client computer 27 may be provided with a hardware having a function of the image separation processing of the separation server 11 having the motion blur eliminating portion for encryption 2041 or installed with software having such function.

[0726] In step S2101, the client computer 27-1 transmits information desired to encrypt (signal to be encrypted), information of speed and direction as the encryption key and image selection information (information selecting the background component image) to the synthesizing server 19.

[0727] In step S2111, the motion blur adder for encryption 2021 of the synthesizing server 19 encrypts the information desired to encrypt (signal to be encrypted) on the basis of the encryption key input from the client computer 27-1 and performs the encrypting processing of synthesizing the selected background component image. Further, since the encrypting processing was explained referring to the flowchart of FIG. 136, explanation thereof will be omitted.

[0728] In step S2112, the synthesizing server 19 transmits a synthesized image encrypted by adding the motion blur to the client computer 27-1.

[0729] In step S2102, the client computer 27-1 displays the synthesized image received from the synthesizing server 19 to determine whether the image is desired by the user or not and if it is determined that the image is the desired image, it is notified to the synthesizing server 19 that the image is the desired image in step S2103. In step S2113, the synthesizing server 19 determines whether the image is the desired image or not and for example, in this case, since it is notified to the synthesizing server 19 that the image is the desired image in step S2103, the procedure proceeds to step S2114.

[0730] In step S2114, the charge processor 19a of the synthesizing server 19 and the account charge server 24 perform the charge processing. Further, the charge processing is similar to that of the separating service in FIGs. 118 and 120 and thus, explanation thereof will be omitted.

[0731] In step S2115, the synthesizing server 19 transmits the synthesized image encrypted to the client computer 27-1. In step S2104, the client computer 27-1 receives the encrypted synthesized image and transmits it to the client computer 27-2.

[0732] In step S2141, the client computer 27-2 receives the encrypted synthesized image. In step S2142, the client computer 27-2 determines whether the key is input or not and repeats this processing until the encryption key is input. If the information of speed and direction as the encryption key is input in step S2142, the motion blur eliminating portion 2041 performs the motion blur processing on the basis of the speed and the direction input in step 2143. In step S2144, the image in which the motion blur is eliminated is displayed.

[0733] If it is determined that the image was not the desired image in step S2102, it is notified to the synthesizing server 19 in step S2015 that the image is not the desired image and the procedure returns to step S2101. Further, since it is determined by this processing that the image is not the desired image, the processing of the synthesizing server 19 returns to step S2111.

[0734] That is, by this processing, when the key of speed and direction specified by a user is correctly input to the client computer 27-1, an image that the encrypted image has been correctly decrypted is displayed. Further, through the same system as the aforementioned encrypting service, the decrypting service can be provided.

[0735] Next, referring to FIG. 152, the correcting server 20 will be explained.

[0736] The separation processor 11 of the correcting server 20 separates the input image (which is may be the image ID and when the image is specified by the image ID, the corresponding image retrieved from the network 1) into the foreground component image and the background component image to output the foreground component image to

21 reads out and obtains the image corresponding to the image ID transmitted from the client computer 27 via the network 1.

[0752] In steps S2312 and S2321, the charge processor 21a of the purchasing server 21 and the account charge server 24 perform the charge processing. Further, the charge processing is similar to that in the separating service in FIGs. 118 and 120 and thus, explanation thereof will be omitted.

[0753] In step S2313, the purchasing server 21 transmits the image obtained through the processing in step S2311 to the client computer 27.

[0754] In step S2302, the client computer 27 receives and stores the image transmitted from the purchasing server 21.

[0755] Also, the client computer 27 may store the image purchased by the purchasing server 21 in its own storage unit or output it to the storage server 18 so as to store it via the network 1 in accordance with instructions of a user. Further, the client computer 27 may transmit the image to another client computer 27, for example, to present it. Furthermore, another user may purchase the foreground component image, the background component image, the synthesized image, the corrected image or the like each of which is separated by the separation processing service, the synthesizing service or the correcting service.

[0756] Next, referring to a flowchart of FIG. 156, the processing of the image selling service for selling the image specified by the client computer 27, which is performed by the selling server 22, will be explained.

[0757] In step S2401, the client computer 27 outputs the information specifying the image desired to sell to the purchasing server 21. That is, the image desired by user to sell is output to the selling server 22.

[0758] In step S2411, the selling server 22 obtains the image desired to sell. That is, the selling server 22 obtains the image transmitted from the client computer 27.

[0759] In steps S2422, the selling server 22 sets a proper price on the image desired to sell. The price may be set, for example, by user in advance, or through an auction on the network 1. Further, if an image is a person, the price may be set according to whether the person is a well-known figure or not when the image is selected.

[0760] In step S2413 and S2431, the charge processor 22a of the selling server 22 and the account charge server 24 perform the charge processing.

[0761] Here, referring to the flowchart of FIG. 157, the processing of the charge will be explained. Further, the real processing of the charge is performed by the selling server 22 and the account charge server 24. But, the information needed for various processing is also output from the client computer 27 and therefore the processing of the client computer 27 will also be explained here.

[0762] In step S2501, an ID for discerning a user (who user who is selling an image) is transmitted to the selling server 22 via the network 1.

[0763] In step S2511, the selling server 22 transmits a cost and an ID for discerning the selling server 22 to the account charge server 24 on the basis of the ID information transmitted from the client computer 27.

[0764] In step S2521, the account charge server 24 requests the financial transaction server 26 having provider account to pay the cost to the financial transaction server 25 having customer account on the basis of the transmitted ID for discerning the selling server 22.

[0765] In step S2531, the financial transaction server for provider 26 transfers the cost corresponding to the amount of sale from the provider account to the financial transaction server for customer 25 having account of the customer.

[0766] Here, the flowchart of FIG. 156 will be explained again.

[0767] In step S2424, the selling server 22 notifies the end of sale to the client computer 27. In step S2402, the client computer 27 receives the notification of the end of sale.

[0768] Also, the selling server 22 may make the selling server 21 store the image sold by the user in its own storage unit or output the image to the storage server 18 so as to store it. Further, when the price is set through an auction system as mentioned above, the selling server 22 may make the image sold by the user to the client computer of a successful bidder 27.

[0769] Next, referring to the flowchart of FIG. 158, the retrieving server 23 will be explained.

[0770] The retrieving server 23 retrieves the image which has been picked up on the camera terminal unit 1 connected to the network 1 on the basis of the retrieving conditions input from the client computer 27 and output the request image. The retrieving condition is time, season, weather, area, position, subject or the like.

[0771] The control unit 2161 of the retrieving server 23 controls the whole operation of the retrieving server 23. In database 2162, position data which is obtained by GPS 76b provided with a camera terminal unit 28 corresponding to the camera ID of each camera terminal unit 28 which the retrieving server 23 recognizes, weather data, subject data or the like 2062b are stored as database. The contents of the database 2162 are obtained and updated from the camera terminal unit 28 via the network 1 by controlling the communication unit 2165 at a predetermined time interval through the control unit 2161.

[0772] The storage unit 2163 stores the image obtained from the camera terminal unit 28 on the network 1 from the communication unit 2165 or stores information needed for the processing of various images.

[0773] The requested information generator 2164 arranges the retrieving conditions input from the client computer

received by the requested information receiving means, only to the first communication apparatus after the charge processing has been finished by the first charging means and the second charging means.

[0813] The significant information may include the foreground component image and the background component image, the encoded data transmitting means may transmit the requested information received by the requested information receiving means and the encoded data as the foreground component image and the background component image generated by the separating means when the predetermined image is separated into the foreground component image and the background component image by the separating means, only to the first communication apparatus after the charge processing has been finished by the first charging means and the second charging means.

[0814] The requested information input means may input an image data ID discerning a predetermined image data in addition to the requested information of the user, and the encoded data transmitting means may transmit the encoded data as significant information generated when the separating means separates the predetermined image into the foreground component image and the background component image on the basis of the requested information and the predetermined image data corresponding to the image data ID only to the first communication apparatus after the charge processing has been finished by the first charging means and the second charging means.

[0815] The second communication apparatus may further comprise an area information generating means for generating area information discerning any of a foreground area having foreground object components constituting a foreground object of the predetermined image data corresponding to the image data ID, a background area having background object components constituting a background object of the predetermined image data corresponding to the image data ID and a mixed area in which the foreground area and the background area are mixed, wherein the significant information includes area information, and wherein the encoded data transmitting means may transmit the encoded data as area information generated by area information generating means when the separating means separates the predetermined image into the foreground component image and the background component image on the basis of the requested information and the predetermined image data corresponding to the image data ID, only to the first communication apparatus after the charge processing has been finished by the first charging means and the second charging means.

[0816] The second communication apparatus may further comprise a mixture ratio generating means for generating a mixture ratio indicating a ratio of the mixed area of the predetermined image data corresponding to the image data ID on the basis of area information, wherein the significant information includes the mixture ratio, and the encoded data transmitting means may transmit the encoded data as mixture ratio generated by the mixture ratio generating means when the separating means separates the predetermined image into the foreground component image and the background component image on the basis of the requested information and the predetermined image data corresponding to the image data ID only to the first communication apparatus after the charge processing has been finished by the first charging means and the second charging means.

[0817] The significant information may include the foreground component image and the background component image, the encoded data transmitting means may transmit the requested information and the encoded data as the foreground component image and the background component image generated by the separating means when the predetermined image corresponding to the image data ID is separated into the foreground component image and the background component image by the separating means, only to the first communication apparatus after the charge processing has been finished by the first charging means and the second charging means.

[0818] A communication method of the 1st system of the present invention is characterized in that a communication method of the first communication apparatus comprises: a requested information input step of inputting requested information of a user from among a plurality of encoded data which are generated on the basis of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a requested information transmitting step of transmitting the requested information which is input in the requested information input step to the second communication apparatus; and an encoded data receiving step of receiving the encoded data which are generated on the basis of the image data corresponding to the requested information transmitted from the second communication apparatus, and a communication method of the second communication apparatus comprises: a requested information receiving step of receiving the requested information transmitted from the first communication apparatus; a separating step of separating the predetermined image data into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; and an encoded data transmitting step of transmitting to the first communication apparatus the encoded data which are generated when the image is separated into the foreground component image and the background component image in the separating step on the basis of the requested information received in the requested information receiving step.

[0819] A program of a 2nd recording medium of the present invention is characterized in that a program controlling the first communication apparatus comprises: a requested information input control step of controlling input of requested information of a user from among a plurality of encoded data which are generated on the basis of predetermined image

data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to the second communication apparatus; and an encoded data reception control step of controlling reception of the encoded data which are generated on the basis of the image data corresponding to the requested information transmitted from the second communication apparatus, and a program controlling the second communication apparatus comprises: a requested information reception control step of controlling reception of the requested information transmitted from the first communication apparatus; a separation control step of controlling separation of the predetermined image data into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; and an encoded data transmission control step of controlling transmission of the encoded data which are generated when the image is separated into the foreground component image and the background component image in the separation control step on the basis of the requested information received in the requested information reception control step to the first communication apparatus.

[0820] A 2nd program of the present invention is characterized by making a computer for controlling the first communication apparatus perform: a requested information input control step of controlling input of requested information of a user from among a plurality of encoded data which are generated on the basis of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to the second communication apparatus; and an encoded data reception control step of controlling reception of the encoded data which are generated on the basis of the image data corresponding to the requested information transmitted from the second communication apparatus and by making a computer for controlling the second communication apparatus perform: a requested information reception control step of controlling reception of the requested information transmitted from the first communication apparatus; a separation control step of controlling separation of the predetermined image data into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; and an encoded data transmission control step of controlling transmission of the encoded data which are generated when the image is separated into the foreground component image and the background component image in the separation control step on the basis of the requested information received in the requested information reception control step, to the first communication apparatus.

[0821] A 2nd communication apparatus of the present invention is characterized by comprising: a requested information input means for inputting requested information of a user from among a plurality of encoded data which are generated on the basis of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a requested information transmitting means for transmitting the requested information which is input by the requested information input means to other communication apparatus; and an encoded data receiving means for receiving the encoded data which are generated on the basis of the image data corresponding to the requested information transmitted from other communication apparatus.

[0822] A 2nd communication method of the present invention is characterized by comprising: a requested information input step of inputting requested information of a user from among a plurality of encoded data which are generated on the basis of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a requested information transmitting step of transmitting the requested information which is input in the requested information input step to other communication apparatus; and an encoded data receiving step of receiving the encoded data which are generated on the basis of the image data corresponding to the requested information transmitted from other communication apparatus.

[0823] A program of a 3rd recording medium of the present invention is characterized by comprising: a requested information input control step of controlling input of requested information of a user from among a plurality of encoded data which are generated on the basis of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to other communication apparatus; and an encoded data reception control step of controlling reception of the encoded data which are generated on the basis of the image data corresponding to the requested information transmitted from other communication apparatus.

the basis of the charge information.

[0843] The charging means may perform the charge processing by deducting the number of points corresponding to the cost information from the number of point of each user used in the charge processing and corresponding to cash.

[0844] The output means may output the synthesized image to the communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0845] A 4th communication method of the present invention is characterized by comprising: a requested information input step of inputting the requested information of user; a synthesizing step of synthesizing a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with request information and generating a synthesized image; and a synthesized image output step of outputting the synthesized image generated in the synthesizing step.

[0846] A program of a 6th recording medium of the present invention is characterized by comprising: a requested information input control step of controlling input of the requested information of user; a synthesization control step of controlling synthesization of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with request information, to generate a synthesized image; and a synthesized image output control step of controlling output of the synthesized image generated in the synthesization control step.

[0847] A 6th program of the present invention is characterized by making a computer perform: a requested information input control step of controlling input of the requested information of user; a synthesization control step of controlling synthesization of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with request information, to generate a synthesized image; and a synthesized image output control step of controlling output of the synthesized image generated in the synthesization control step.

[0848] A 3rd communication system of the present invention is characterized in that the first communication apparatus comprises: a requested information input means for inputting request information of a user; a requested information transmitting means for transmitting the requested information which is input by the requested information input means to the second communication apparatus; and a synthesized data receiving means for receiving the synthesized data transmitted from the second communication apparatus in accordance with the requested information, and the second communication apparatus comprises: a requested information receiving means for receiving the requested information transmitted from the first communication apparatus; a synthesizing means for synthesizing a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with the requested information and generating the synthesized image; and a synthesized image transmitting means for transmitting the synthesized image generated by the synthesizing means to the first communication apparatus.

[0849] The requested information input means may input a predetermined foreground component image, a predetermined background component image and the significant information used when synthesizing the predetermined foreground component image and the predetermined background component image along with the requested information of the user, and the synthesizing means may synthesize the predetermined foreground component image and the predetermined background component image input by the requested information input means along with the requested information on the basis of the significant information and generate the synthesized image.

[0850] The requested information input means may input a predetermined foreground component image, a predetermined background component image and the mixture ratio of the mixed area where the predetermined foreground component image and the predetermined background component image are mixed as significant information used when synthesizing the predetermined foreground component image and the predetermined background component image along with the requested information of the user, and the synthesizing means may synthesize the predetermined foreground component image and the predetermined background component image input by the requested information input means along the requested information on the basis of the mixture ratio as significant information and generate

the synthesized image.

[0851] The requested information input means may input a predetermined foreground component image, a predetermined background component image, and amount of movement and moving direction of the foreground component image as significant information used when synthesizing the predetermined foreground component image and the predetermined background component image along with the requested information of the user, and the synthesizing means may adjust of the predetermined foreground component image input by the requested information input means along with the requested information on the basis of amount of movement and the moving direction of the foreground component image as significant information, synthesize the predetermined foreground component image in which the motion blur is adjusted and the predetermined background component image and generate the synthesized image.

[0852] The requested information input means may input a predetermined foreground component image, a predetermined background component image and initial positional information, amount of movement and moving direction of the foreground component image as significant information used when synthesizing the predetermined foreground component image and the predetermined background component image along with the requested information of the user, and the synthesizing means may adjust the motion blur of the predetermined foreground component image input by the requested information input means along with the requested information on the basis of amount of movement and the moving direction as significant information, calculate the mixture ratio, synthesize the predetermined foreground component image where motion blur is adjusted and the predetermined background component image using the calculated mixture ratio on the basis of the initial positional information, amount of movement and the moving direction of the foreground component image as significant information, and then generate the synthesized image.

[0853] The requested information input means may input a foreground component image ID discerning a predetermined foreground component image, a background component image ID discerning a predetermined background component image and significant information along with the requested information of the user, and the synthesizing means may synthesize the foreground component image corresponding to the foreground component image ID and the background component image corresponding to the background component image ID on the basis of the significant information in accordance with the foreground component image ID discerning the predetermined foreground component image, the background component image ID discerning the predetermined background component image, and significant information along with the requested information of the user, and generate the synthesized image.

[0854] The charging means for performing charge processing in accordance with the requested information may be further comprised.

[0855] The charging means may generate charge information including user ID, the communication apparatus ID and charge information including the cost information corresponding to the requested information in accordance with the requested information.

[0856] The charging means may perform the charge processing with respect to a financial account of the user on the basis of the charge information.

[0857] The charging means may perform the charge processing by deducting the number of points corresponding to the cost information from the number of points of each user used in the charge processing.

[0858] The output means may output the synthesized image to the communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0859] A communication method of the 3rd communication system of the present invention is characterized in that a communication method of the first communication apparatus comprises: a requested information input step of inputting request information of a user; a requested information transmitting step of transmitting the requested information which is input in the requested information input step to the second communication apparatus; and a synthesized data receiving step of receiving the synthesized data transmitted from the second communication apparatus in accordance with the requested information, and a communication method of the second communication apparatus comprises: a requested information receiving step of receiving the requested information transmitted from the first communication apparatus; a synthesizing step of synthesizing a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with the requested information and generating the synthesized image; and a synthesized image transmitting step of transmitting the synthesized image generated in the synthesizing step to the first communication apparatus.

[0860] A program of a 7th recording medium of the present invention is characterized in that a program controlling the first communication apparatus comprises: a requested information input control step of controlling input of request information of a user; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to the second communication apparatus; and a synthesized data reception control step of controlling reception of the synthesized data transmitted from the second communication apparatus in accordance with the requested information, and a program controlling the second com-

munication apparatus comprises: a requested information reception control step of controlling reception of the requested information transmitted from the first communication apparatus; a synthesization control step of controlling synthesization of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with the requested information and generating the synthesized image; and a synthesized image transmission control step of controlling transmission of the synthesized image generated in the synthesizing step to the first communication apparatus.

[0861] A 7th program of the present invention is characterized by making a computer for controlling the first communication apparatus perform: a requested information input control step of controlling input of request information of a user; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to the second communication apparatus; and a synthesized data reception control step of controlling reception of the synthesized data transmitted from the second communication apparatus in accordance with the requested information, and by making a computer for controlling the second communication apparatus perform: a requested information reception control step of controlling reception of the requested information transmitted from the first communication apparatus; a synthesization control step of controlling synthesization of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with the requested information and generating the synthesized image; and a synthesized image transmission control step of controlling transmission of the synthesized image generated in the synthesization control step to the first communication apparatus.

[0862] A 5th communication apparatus of the present invention is characterized by comprising: a requested information input means for inputting request information of a user; a requested information transmitting means for transmitting the requested information which is input by the requested information input means to other communication apparatus; and a synthesized data receiving means for receiving the synthesized data transmitted from other communication apparatus in accordance with the requested information.

[0863] A 5th communication method of the present invention is characterized by comprising: a requested information input step of inputting request information of a user; a requested information transmitting step of transmitting the requested information which is input in the requested information input step to other communication apparatus; and a synthesized data receiving step of receiving the synthesized data transmitted from other communication apparatus in accordance with the requested information.

[0864] A program of an 8th recording medium of the present invention is characterized by comprising: a requested information input control step of controlling input of request information of a user; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to other communication apparatus; and a synthesized data reception control step of controlling reception of the synthesized data transmitted from other communication apparatus in accordance with the requested information.

[0865] An 8th program of the present invention is characterized by making a computer perform: a requested information input control step of controlling input of request information of a user; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to other communication apparatus; and a synthesized data reception control step of controlling reception of the synthesized data transmitted from other communication apparatus in accordance with the requested information.

[0866] A 6th communication apparatus of the present invention is characterized by comprising: a requested information receiving means for receiving the requested information transmitted from other communication apparatus; a synthesizing means for synthesizing a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with the requested information and generating the synthesized image; and a synthesized image transmitting means for transmitting the synthesized image generated by the synthesizing means to other communication apparatus.

[0867] A 6th communication method of the present invention is characterized by comprising: a requested information receiving step of receiving the requested information transmitted from other communication apparatus; a synthesizing step of synthesizing a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels,

each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with the requested information and generating the synthesized image; and a synthesized image transmitting step of transmitting the synthesized image generated in the synthesizing step to other communication apparatus.

5 [0868] A program of a 9th recording medium of the present invention is characterized by comprising: a requested information reception control step of controlling reception of the requested information transmitted from other communication apparatus; a synthesisization control step of controlling synthesisization of a foreground component image having foreground object components constituting a foreground object and a background component image having back-
10 ground object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with the requested information and generating the synthesized image; and a synthesized image transmission control step of controlling transmission of the synthesized image generated in the synthesisization control step to other communication apparatus.

15 [0869] A 9th program of the present invention is characterized by making a computer perform: a requested information reception control step of controlling reception of the requested information transmitted from other communication apparatus; a synthesisization control step of controlling synthesisization of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element
20 having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time in accordance with the requested information and generating the synthesized image; and a synthesized image transmission control step of controlling transmission of the synthesized image generated in the synthesisization control step to other communication apparatus.

25 [0870] A 7th communication apparatus of the present invention is characterized by comprising: a requested information input means for inputting the requested information of a user; a mixture ratio estimating means for estimating a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of
30 pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separating means for separating the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesizing means for synthesizing the foreground component image separated by the separating means and any background component image, or the background
35 component image separated by the separating means and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and an output means for outputting the synthesized image synthesized by the synthesizing means.

[0871] The requested information input means may input amount of motion blur adjustment for adding motion blur to the foreground component image in addition to the requested information of the user and further comprise a motion
40 blur adding means which adds motion blur corresponding to amount by which motion blur is adjusted to the foreground component image, and the synthesizing means may synthesize the foreground component image in which motion blur is added by the motion blur adding means and any background component image in a predetermined mixture ratio and generate the synthesized image.

[0872] The requested information input means may also input any background component image in addition to the requested information of the user, and the synthesizing means may synthesize the foreground component image and
45 any background component image in a ratio estimated by the mixture ratio estimating means and generate the synthesized image.

[0873] The charging means for performing charge processing in accordance with the requested information may be further comprised.

50 [0874] The charging means may generate charge information including user ID, the communication apparatus ID and cost information corresponding to the requested information in accordance with the requested information.

[0875] The charging means may perform the charge processing with respect to a financial account of the user on the basis of the charge information.

[0876] The charging means may perform the charge processing by deducting the number of points corresponding to the cost information from the number of points of each user used in the charge processing.

55 [0877] The output means may output the synthesized image to the communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0878] The requested information input means may input a predetermined image data in addition to the requested

information of the user, and the output means may output the image synthesized by the synthesizing means to the communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0879] A 7th communication method of the present invention is characterized by comprising: a requested information input step of inputting the requested information of a user; a mixture ratio estimating step of estimating a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separating step of separating the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesizing step of synthesizing the foreground component image separated in the separating step and any background component image, or the background component image separated in the separating step and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and an output step of outputting the synthesized image synthesized in the synthesizing step.

[0880] A program of a 10th recording medium of the present invention is characterized by comprising: a requested information input control step of controlling input of the requested information of a user; a mixture ratio estimation control step of controlling estimation of a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separation control step of controlling separation of the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesization control step of controlling synthesization of the foreground component image separated in the separation control step and any background component image, or the background component image separated in the separation control step and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and an output control step of controlling output of the synthesized image synthesized in the synthesization control step.

[0881] A 10th program of the present invention is characterized by making a computer perform: a requested information input control step of controlling input of the requested information of a user; a mixture ratio estimation control step of controlling estimation of a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separation control step of controlling separation of the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesization control step of controlling synthesization of the foreground component image separated in the separation control step and any background component image, or the background component image separated in the separation control step and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and an output control step of controlling output of the synthesized image synthesized in the synthesization control step.

[0882] A 4th communication system of the present invention is characterized in that the first communication apparatus comprises: a requested information input means for inputting request information of a user; a requested information transmitting means for transmitting the requested information which is input by the requested information input means to the second transmitting apparatus; and a receiving means for receiving the synthesized image transmitted from the second communication apparatus, and the second communication apparatus comprises: a requested information receiving means for receiving the requested information which is transmitted from the first transmitting apparatus; a mixture ratio estimating means for estimating a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separating means for separating the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesizing means for synthesizing the foreground component image separated by the separating means and any background component image, or the background component image separated by the separating means and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and a synthesized image transmitting means

for transmitting the synthesized image synthesized by the synthesizing means to the first communication apparatus.

[0883] The requested information input means may input amount of motion blur adjustment for adding motion blur to the foreground component image in addition to the requested information of the user, the second communication apparatus may further comprise a motion blur adding means which adds motion blur corresponding to amount by which motion blur is adjusted to the foreground component image, and the synthesizing means may synthesize the foreground component image where motion blur is added by the motion blur adding means and any background component image in a predetermined mixture ratio and generate the synthesized image.

[0884] The requested information input means may also input any background component image in addition to the requested information of the user, the synthesizing means may synthesize the foreground component image and any background component image in a mixture ratio estimated by the mixture ratio estimating means and generate the synthesized image.

[0885] The second communication apparatus may further comprise the charging means for performing charge processing in accordance with the requested information.

[0886] The charging means may generate charge information including user ID, the second communication apparatus ID and cost information corresponding to the requested information in accordance with the requested information.

[0887] The charging means may perform the charge processing with respect to a financial account of the user on the basis of the charge information.

[0888] The charging means of the second communication apparatus may perform the charge processing by deducting the number of points corresponding to the cost information from the number of point of each user used in the charge processing.

[0889] The synthesized image transmitting means may transmit the synthesized image to the first communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0890] The requested information input means may input a predetermined image data in addition to the requested information of the user, and the output means may output the image synthesized by the synthesizing means to the first communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0891] A communication method of the 4th communication system of the present invention is characterized by a communication method of the first communication apparatus comprises: a requested information input step of inputting request information of a user; a requested information transmitting step of transmitting the requested information which is input in the requested information input step to the second transmitting apparatus; and a receiving step of receiving the synthesized image transmitted from the second communication apparatus, and a communication method of the second communication apparatus comprises: a requested information receiving step of receiving the requested information which is transmitted from the first transmitting apparatus; a mixture ratio estimating step of estimating a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separating step of separating the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesizing step of synthesizing the foreground component image separated in the separating step and any background component image, or the background component image separated in the separating step and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and a synthesized image transmitting step of transmitting the synthesized image synthesized in the synthesizing step to the first communication apparatus.

[0892] A program of an 11th recording medium of the present invention is characterized in that a program controlling the first communication apparatus comprises: a requested information input control step of controlling input of the requested information of a user; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to the second transmitting apparatus; and a reception control step of controlling reception of the synthesized image transmitted from the second communication apparatus, and a program controlling the second communication apparatus comprises: a requested information reception control step of controlling reception of the requested information which is transmitted from the first transmitting apparatus; a mixture ratio estimation control step of controlling estimation of a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separation control

step of controlling separation of the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesization control step of controlling synthesization of the foreground component image separated in the separation control step and any background component image, or the background component image separated in the separation control step and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and a synthesized image transmission control step of controlling transmission of the synthesized image synthesized in the synthesization control step to the first communication apparatus.

[0893] An 11th program of the present invention is characterized by making a computer for controlling the first communication apparatus perform: a requested information input control step of controlling input of the requested information of a user; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to the second transmitting apparatus; and a reception control step of controlling reception of the synthesized image transmitted from the second communication apparatus, and by making a computer for controlling the second communication apparatus perform: a requested information reception control step of controlling reception of the requested information which is transmitted from the first transmitting apparatus; a mixture ratio estimation control step of controlling estimation of a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separation control step of controlling separation of the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesization control step of controlling synthesization of the foreground component image separated in the separation control step and any background component image, or the background component image separated in the separation control step and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and a synthesized image transmission control step of controlling transmission of the synthesized image synthesized in the synthesization control step to the first communication apparatus.

[0894] An 8th communication apparatus of the present invention is characterized by comprising: a requested information input means for inputting request information of a user; a requested information transmitting means for transmitting the requested information which is input by the requested information input means to other communication apparatus; and a receiving means for receiving the synthesized image transmitted from other communication apparatus.

[0895] An 8th communication method of the present invention is characterized by comprising: a requested information input step of inputting request information of a user; a requested information transmitting step of transmitting the requested information which is input in the requested information input step to other communication apparatus; and a receiving step of receiving the synthesized image transmitted from other communication apparatus.

[0896] A program of a 12th recording medium of the present invention is characterized by comprising: a requested information input control step of controlling input of request information of a user; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to other communication apparatus; and a reception control step of controlling reception of the synthesized image transmitted from other communication apparatus.

[0897] A 12th program of the present invention is characterized by making a computer perform: a requested information input control step of controlling input of request information of a user; a requested information transmission control step of controlling transmission of the requested information which is input in the requested information input control step to other communication apparatus; and a reception control step of controlling reception of the synthesized image transmitted from other communication apparatus.

[0898] A 9th communication apparatus of the present invention is characterized by comprising: a requested information receiving means for receiving the requested information which is transmitted from other communication apparatus; a mixture ratio estimating means for estimating a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separating means for separating the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesizing means for synthesizing the foreground component image separated by the separating means and any background component image, or the background component image separated by the separating means and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and a synthesized image trans-

mitting means for transmitting the synthesized image synthesized by the synthesizing means to other communication apparatus.

[0899] A 9th communication method of the present invention is characterized by comprising: a requested information receiving step of receiving the requested information which is transmitted from other communication apparatus; a mixture ratio estimating step of estimating a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separating step of separating the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesizing step of synthesizing the foreground component image separated in the separating step and any background component image, or the background component image separated in the separating step and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and a synthesized image transmitting step of transmitting the synthesized image synthesized in the synthesizing step to other communication apparatus.

[0900] A program of a 13th recording medium of the present invention is characterized by comprising: a requested information reception control step of controlling reception of the requested information which is transmitted from other communication apparatus; a mixture ratio estimation control step of controlling estimation of a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separation control step of controlling separation of the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesization control step of controlling synthesization of the foreground component image separated in the separation control step and any background component image, or the background component image separated in the separation control step and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and a synthesized image transmission control step of controlling transmission of the synthesized image synthesized in the synthesization control step to other communication apparatus.

[0901] A 13th program of the present invention is characterized by making a computer perform: a requested information reception control step of controlling reception of the requested information which is transmitted from other communication apparatus; a mixture ratio estimation control step of controlling estimation of a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are mixed on the basis of the requested information; a separation control step of controlling separation of the image data into the foreground component image and the background component image on the basis of the mixture ratio; a synthesization control step of controlling synthesization of the foreground component image separated in the separation control step and any background component image, or the background component image separated in the separation control step and any foreground component image in a predetermined mixture ratio and generating the synthesized image; and a synthesized image transmission control step of controlling transmission of the synthesized image synthesized in the synthesization control step to other communication apparatus.

[0902] A 10th communication apparatus of the present invention is characterized by comprising: an image ID input means for inputting the ID discerning an image requested by a user; a storing means for storing the image having at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving means for retrieving an image corresponding to an image ID input by the image ID input means of the images stored in the storing means; an output means for outputting the image retrieved by the retrieving means to the communication apparatus of the user; and a charging means for performing charge processing in accordance with the image retrieved by the retrieving means.

[0903] A separating means may be further comprised for separating the image into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object and the storing means may store the foreground

component image and the background component image separated from the image by the separating means.

[0904] A synthesized image generating means may be further comprised for synthesizing the foreground component image having foreground object components constituting a foreground object and the background component image having background object components constituting a background object separated from the image in a predetermined mixture ratio and generating the synthesized image and the storing means may store the synthesized image generated by the synthesized image generating means.

[0905] A separating means for separating the image into the foreground component image having foreground object components constituting a foreground object and the background component image having background object components constituting a background object and a synthesized image generating means for synthesizing the foreground component image and the background component image separated by the separating means in a predetermined mixture ratio and generating the synthesized image may be further comprised, and the storing means may store the synthesized image generated by the synthesized image generating means.

[0906] The charging means may generate charge information including user ID, the communication apparatus ID and cost information corresponding to the image retrieved by the retrieving means in accordance with the image retrieved by the retrieving means.

[0907] The charging means may perform the charge processing with respect to a financial account of the user on the basis of the charge information.

[0908] The charging means may perform the charge processing by deducting the number of points corresponding to the cost information from the number of points of each user used in the charge processing.

[0909] The output means may output the synthesized image to the first communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0910] A 10th communication method of the present invention is characterized by comprising; an image ID input step of inputting the ID discerning an image requested by a user; a storing step of storing the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving step of retrieving an image corresponding to an image ID input in the image ID input step of the images stored in the storing step; an output step of outputting the image retrieved in the retrieving step to the communication apparatus of the user; and a charging step of performing charge processing according to the image retrieved in the retrieving step.

[0911] A program of a 14th recording medium of the present invention is characterized by comprising; an image ID input control step of controlling input of the ID discerning an image requested by a user; a storage control step of controlling storage of the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of an image corresponding to an image ID input in the image ID input control step of the images stored in the storage control step; an output control step of controlling output of the image retrieved in the retrieval control step to the communication apparatus of the user; and a charge control step of controlling performance of charge processing according to the image retrieved in the retrieval control step.

[0912] A 14th program of the present invention is characterized by making a computer perform; an image ID input control step of controlling input of the ID discerning an image requested by a user; a storage control step of controlling storage of the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of an image corresponding to an image ID input in the image ID input control step of the images stored in the storage control step; an output control step of controlling output of the image retrieved in the retrieval control step to the communication apparatus of the user; and a charge control step of controlling performance of charge processing according to the image retrieved in the retrieval control step.

[0913] A 5th communication system of the present invention is characterized in that a first communication apparatus comprises: an image ID input means for inputting an ID discerning an image requested by a user; an image ID transmitting means for transmitting the image ID to a second communication apparatus; and an image receiving means for receiving the image retrieved according to the image ID, and the second communication apparatus comprises: an image ID receiving means for receiving the image ID transmitted from the first communication apparatus; a storing

means for storing the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving means for retrieving the image corresponding to the image ID received by the image ID receiving means among images stored in the storing means; an output means for outputting the image retrieved by the retrieving means to the first communication apparatus; and a charging means for performing a charge processing according to the image retrieved by the retrieving means.

[0914] The second communication apparatus may further comprise a separating means for separating the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object.

[0915] The storing means may store the foreground component image and the background component image separated by the separating means.

[0916] The second communication apparatus may further comprise a synthesized image generating means for synthesizing the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object separated from the image and generating the synthesized image in a predetermined mixture ratio and the storing means may store the synthesized image generated by the synthesized image generating means.

[0917] The second communication apparatus may further comprise: a separating means for separating the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object; and a synthesized image generating means for synthesizing the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object separated by the separating means and generating the synthesized image in a predetermined mixture ratio and the storing means may store the synthesized image generated by the synthesized image generating means.

[0918] The charging means may generate charge information including a user ID, a second communication apparatus ID and cost information corresponding to the image retrieved by the retrieving means in accordance with the image retrieved by the retrieving means.

[0919] The charging means may perform the charge processing with respect to a financial account of the user on the basis of the charge information.

[0920] The charging means of the second communication apparatus may perform the charge processing by subtracting the number of points corresponding to the cost information from the number of points of each user used in the charge processing.

[0921] The output means may output the image to the first communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0922] A communication method of the 5th communication system of the present invention is characterized in that a communication method of the first communication apparatus comprises: an image ID input step of inputting an ID discerning an image requested by a user; an image ID transmitting step of transmitting the image ID to the second communication apparatus; and an image receiving step of receiving the image retrieved in accordance with the image ID, and a communication method of the second communication apparatus comprises: a storing step of storing the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving step of retrieving the image corresponding to the image ID received in the image ID receiving step among images stored in the storing step; an output step of outputting the image retrieved in the retrieving step to the first communication apparatus; and a charging step of performing a charge processing in accordance with the image retrieved in the retrieving step.

[0923] A program of a 15th recording medium of the present invention is characterized in that a program for controlling the first communication apparatus comprises: an image ID input control step of controlling input of an ID discerning an image requested by a user; an image ID transmission control step of controlling transmission of the image ID to the second communication apparatus; and an image reception control step of controlling reception of the image retrieved in accordance with the image ID, and a program for controlling the second communication apparatus comprises: a storage control step of controlling storage of the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained

by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of the image corresponding to the image ID received in the image ID reception control step among images stored in the storage control step; an output control step of controlling output of the image retrieved in the retrieval control step to the first communication apparatus; and a charge control step of controlling performance of a charge processing in accordance with the image retrieved in the retrieval control step.

[0924] A 15th program of the present invention is characterized by making a computer for controlling the first communication apparatus perform: an image ID input control step of controlling input of an ID discerning an image requested by a user; an image ID transmission control step of controlling transmission of the image ID to the second communication apparatus; and an image reception control step of controlling reception of the image retrieved in accordance with the image ID, and by making a computer for controlling the second communication apparatus perform: a storage control step of controlling storage of the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of the image corresponding to the image ID received in the image ID reception control step among images stored in the storage control step; an output control step of controlling output of the image retrieved in the retrieval control step to the first communication apparatus; and a charge control step of controlling performance of a charge processing in accordance with the image retrieved in the retrieval control step.

[0925] An 11th communication apparatus of the present invention is characterized by comprising: an image ID input means for inputting an ID discerning an image requested by a user; an image ID transmitting means for transmitting the image ID to other communication apparatus; and an image receiving means for receiving the image retrieved correspondingly to the image ID.

[0926] An 11th communication method of the present invention is characterized by comprising: an image ID input step of inputting an ID discerning an image requested by a user; an image ID transmitting step of transmitting the image ID to other communication apparatus; and an image receiving step of receiving the image retrieved correspondingly to the image ID.

[0927] A program of a 16th recording medium of the present invention is characterized by comprising: an image ID input control step of controlling input of an ID discerning an image requested by a user; an image ID transmission control step of controlling transmission of the image ID to other communication apparatus; and an image reception control step of controlling reception of the image retrieved correspondingly to the image ID.

[0928] A 16th program of the present invention is characterized by making a computer perform: an image ID input control step of controlling input of an ID discerning an image requested by a user; an image ID transmission control step of controlling transmission of the image ID to other communication apparatus; and an image reception control step of controlling reception of the image retrieved correspondingly to the image ID.

[0929] A 12th communication apparatus of the present invention is characterized by comprising: an image ID receiving means for receiving an image ID transmitted from other communication apparatus; a storing means for storing an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving means for retrieving the image corresponding to the image ID received by the image ID receiving means among images stored in the storing means; an output means for outputting the image retrieved by the retrieving means to other communication apparatus; and a charging means for performing a charge processing in accordance with the image retrieved by the retrieving means. A 12th communication method of the present invention is characterized by comprising: an image ID receiving step of receiving an image ID transmitted from other communication apparatus; a storing step of storing an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving step of retrieving the image corresponding to the image ID received in the image ID receiving step among images stored in the storing step; an output step of outputting the image retrieved in the retrieving step to other communication apparatus; and a charging step of performing a charge processing in accordance with the image retrieved in the retrieving step.

[0930] A program of a 17th recording medium of the present invention is characterized by comprising: an image ID reception control step of controlling reception of an image ID transmitted from other communication apparatus; a storage control step of controlling storage of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of the image corresponding to the image ID received in the image ID reception control step among images stored in the storage control step; an output control step of controlling output of the image retrieved in the retrieval control step to other communication apparatus; and a charge control step of controlling performance of a charge processing in accordance with the image retrieved in the retrieval control step.

[0931] A 17th program of the present invention is characterized by making a computer perform: an image ID reception control step of controlling reception of an image ID transmitted from other communication apparatus; a storage control step of controlling storage of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of the image corresponding to the image ID received in the image ID reception control step among images stored in the storage control step; an output control step of controlling output of the image retrieved in the retrieval control step to other communication apparatus; and a charge control step of controlling performance of a charge processing in accordance with the image retrieved in the retrieval control step.

[0932] A 13th communication apparatus of the present invention is characterized by comprising: an input means for inputting an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a storing means for storing the image input by the input means; and a paying means for performing a payment processing in accordance with the image stored in the storing means.

[0933] A separating means for separating the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object may be further comprised and the input means may input the foreground component image and the background component image separated by the separating means.

[0934] A synthesized image generating means for synthesizing in a predetermined mixture ratio the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object separated from the image and generating a synthesized image may be further comprised and the input means may input the synthesized image generated by the synthesized image generating means.

[0935] A separating means for separating the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object and a synthesized image generating means for synthesizing in a predetermined mixture ratio the foreground component image and the background component image separated by the separating means and generating a synthesized image may be further comprised and the input means may input the synthesized image generated by the synthesized image generating means.

[0936] A 13th communication method of the present invention is characterized by comprising: an input step of inputting an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a storing step of storing the image input in the input step; and a paying step of performing a payment processing in accordance with the image stored in the storing step.

[0937] A program of an 18th recording medium of the present invention is characterized by comprising: an input control step of controlling input of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised

of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a storage control step of controlling storage of the image input in the input control step; and a payment control step of controlling performance of a payment processing in accordance with the image stored in the storage control step.

[0938] A 18th program of the present invention is characterized by making a computer perform: an input control step of controlling input of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a storage control step of controlling storage of the image input in the input control step; and a payment control step of controlling performance of a payment processing in accordance with the image stored in the storage control step.

[0939] A 6th communication system of the present invention is characterized in that a first communication apparatus comprises: an input means for inputting an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; and an image transmitting means for transmitting the image input by the input means to a second communication apparatus, and the second communication apparatus comprises: an image receiving means for receiving the image transmitted from the first communication apparatus; a storing means for storing the image received by the image receiving means; and a paying means for performing a payment processing in accordance with the image stored in the storing means.

[0940] The first communication apparatus may further comprise a separating means for separating the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object and the input means may input the foreground component image and the background component image separated by the separating means.

[0941] The first communication apparatus may further comprise a synthesized image generating means for synthesizing in a predetermined mixture ratio the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object separated from the image and generating a synthesized image and the input means may input the synthesized image generated by the synthesized image generating means.

[0942] The first communication apparatus may further comprise a separating means for separating the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object and a synthesized image generating means for synthesizing in a predetermined mixture ratio the foreground component image and the background component image separated by the separating means and generating a synthesized image and the input means may input the synthesized image generated by the synthesized image generating means.

[0943] A communication method of the 6th communication system is characterized in that a communication method of the first communication apparatus comprises: an input step of inputting an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; and an image transmitting step of transmitting the image input in the input step to a second communication apparatus, and a communication method of the second communication apparatus comprises: an image receiving step of receiving the image transmitted from the first communication apparatus; a storing step of storing the image received in the image receiving step; and a paying step of performing a payment processing in accordance with the image stored in the storing step.

[0944] A program of the 19th recording medium of the present invention is characterized in that a program for controlling the first communication apparatus comprises: an input control step of controlling input of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; and an image transmission control step of controlling transmission of the image input in the input control step to a second communication apparatus, and a program for controlling the second communication apparatus comprises: an image reception control step of controlling reception

of the image transmitted from the first communication apparatus; a storage control step of controlling storage of the image received in the image reception control step; and a payment control step of controlling performance of a payment processing in accordance with the image stored in the storage control step.

[0945] A 19th program of the present invention is characterized by making a computer for controlling a first communication apparatus perform: an input control step of controlling input of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; and an image transmission control step of controlling transmission of the image input in the input control step to a second communication apparatus, and by making a computer for controlling the second communication apparatus perform: an image reception control step of controlling reception of the image transmitted from the first communication apparatus; a storage control step of controlling storage of the image received in the image reception control step; and a payment control step of controlling performance of a payment processing in accordance with the image stored in the storage control step.

[0946] A 14th communication apparatus of the present invention is characterized by comprising: an input means for inputting an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; and an image transmitting means for transmitting the image input by the input means to other communication apparatus.

[0947] A 14th communication method of the present invention is characterized by comprising: an input step of inputting an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; and an image transmitting step of transmitting the image input in the input step to other communication apparatus.

[0948] A program of a 20th recording medium of the present invention is characterized by comprising: an input control step of controlling input of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; and an image transmission control step of controlling transmission of the image input in the input control step to other communication apparatus.

[0949] A 20th program of the present invention is characterized by making a computer perform: an input control step of controlling input of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; and an image transmission control step of controlling transmission of the image input in the input control step to other communication apparatus.

[0950] A 15th communication apparatus of the present invention is characterized by comprising: an image receiving means for receiving an image transmitted from other communication apparatus; a storing means for storing the image received by the image receiving means; and a paying means for performing a payment processing in accordance with the image stored in the storing means.

[0951] A 15th communication method of the present invention is characterized by comprising: an image receiving step of receiving an image transmitted from other communication apparatus; a storing step of storing the image received in the image receiving step; and a paying step of performing a payment processing in accordance with the image stored in the storing step.

[0952] A program of a 21st recording medium of the present invention is characterized by comprising: an image reception control step of controlling reception of an image transmitted from other communication apparatus; a storage control step of controlling storage of the image received in the image reception control step; and a payment control step of controlling performance of a payment processing in accordance with the image stored in the storage control step.

[0953] A 21st program of the present invention is characterized by making a computer perform: an image reception

control step of controlling reception of an image transmitted from other communication apparatus; a storage control step of controlling storage of the image received in the image reception control step; and a payment control step of controlling performance of a payment processing in accordance with the image stored in the storage control step.

[0954] A 16th communication apparatus of the present invention is characterized by comprising: a retrieval request information input means for inputting retrieval request information of a user; a storing means for storing an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving means for retrieving the image corresponding to the retrieval request information input by the retrieval request information input means among images stored in the storing means; an output means for outputting a retrieval result of the retrieving means; and a charging means for performing a charge processing in accordance with the retrieval result.

[0955] The storing means may comprise a plurality of image storage units, respectively, provided with an image pickup element for picking up image for updating image picked up by the image pickup element at a predetermined time interval to store them and being capable of communication by a wire or wirelessly.

[0956] The retrieval request information may include information specifying a foreground object, the storing means may further comprise a database for indicating relationship between an ID discerning the image pickup elements provided in the plurality of image storage units and an image object stored in the corresponding image storage unit and the retrieving means may retrieve the image corresponding to the information specifying the foreground object input by the retrieval request information input means among images stored in the storing means with reference to the database.

[0957] A separating means for separating image data of the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object may be further comprised and the storing means may store the foreground component image and the background component image separated by the separating means.

[0958] A synthesized image generating means for synthesizing in a predetermined mixture ratio the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object separated from the image data of the image and generating a synthesized image may be further comprised and the storing means may store the synthesized image generated by the synthesized image generating means.

[0959] A separating means for separating image data of the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object and a synthesized image generating means for synthesizing in a predetermined mixture ratio the foreground component image and the background component image separated by the separating means and generating a synthesized image may be further comprised and the storing means may store the synthesized image generated by the synthesized image generating means.

[0960] The output means may output existence and nonexistence of the image corresponding to the retrieval request information or the retrieved image along with existence and nonexistence of the image corresponding to the retrieval request information as the retrieval result, and the charging means may perform the charge processing on the basis of the retrieval result output by the output means.

[0961] The charging means may generate charge information including a user ID, a communication apparatus ID and cost information corresponding to the retrieval request information in accordance with the retrieval request information.

[0962] The charging means may perform the charge processing based on the retrieval result output by the output means with respect to a financial account of the user on the basis of the charge information.

[0963] The charging means may perform the charge processing by subtracting the number of points corresponding to the cost information from the number of points of each user used for the charge processing.

[0964] The output means may output the retrieval result to a communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0965] A 16th communication method of the present invention is characterized by comprising: a retrieval request information input step of inputting retrieval request information of a user; a storing step of storing an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving step of retrieving image corresponding to the retrieval request information input in the retrieval request information input step among images stored in the storing

step; an output step of outputting a retrieval result of the retrieving step; and a charging step of performing a charge processing in accordance with the retrieval result.

[0966] A program of a 22nd recording medium of the present invention is characterized by comprising: a retrieval request information input control step of controlling input of a retrieval request information of a user; a storage control step of controlling storage of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of the image corresponding to the retrieval request information input in the retrieval request information input control step among images stored in the storage control step; an output control step of controlling output of a retrieval result of the retrieval control step; and a charge control step of controlling performance of a charge processing in accordance with the retrieval result.

[0967] A 22nd program of the present invention is characterized by making a computer perform: a retrieval request information input control step of controlling input of a retrieval request information of a user; a storage control step of controlling storage of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of image corresponding to the retrieval request information input in the retrieval request information input control step among images stored in the storage control step; an output control step of controlling output of a retrieval result of the retrieval control step; and a charge control step of controlling performance of a charge processing in accordance with the retrieval result.

[0968] A 7th communication system of the present invention is characterized in that a first communication apparatus comprises: a retrieval request information input means for inputting a retrieval request information of a user; a retrieval request information transmitting means for transmitting the retrieval request information to a second communication apparatus; and a retrieval result receiving means for receiving a retrieval result transmitted from the second communication apparatus, and the second communication apparatus comprises: a retrieval request information receiving means for receiving the retrieval request information transmitted from the first communication apparatus; a storing means for storing an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving means for retrieving the image corresponding to the retrieval request information received by the retrieval request information receiving means among images stored in the storing means; an retrieval result transmitting means for transmitting the retrieval result of the retrieving means to the first communication apparatus; and a charging means for performing a charge processing in accordance with the retrieval result.

[0969] The storing means may comprise a plurality of image storage units, respectively, provided with an image pickup element for picking up image for updating image picked up by the image pickup element at a predetermined time interval to store them and being capable of communication by a wire or wirelessly.

[0970] The retrieval request information may include information specifying a foreground object, the storing means may further comprise a database for indicating relationship between an ID discerning the image pickup elements provided in the plurality of image storage units and an image object stored in the corresponding image storage unit and the retrieving means may retrieve the image corresponding to the information specifying the foreground object input by the retrieval request information input means among images stored in the storing means with reference to the database.

[0971] The second communication apparatus may further comprise a separating means for separating image data of the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object and the storing means may store the foreground component image and the background component image separated by the separating means.

[0972] The second communication apparatus may further comprise a synthesized image generating means for synthesizing in a predetermined mixture ratio the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object separated from image data of the image and generating a synthesized image and the storing means may store the synthesized image generated by the synthesized image generating means.

[0973] The second communication apparatus may further comprise a separating means for separating image data of the image into the foreground component image having foreground object components constituting the foreground object and the background component image having background object components constituting the background object and a synthesized image generating means for synthesizing in a predetermined mixture ratio the foreground component image and the background component image separated by the separating means and generating a synthesized image and the storing means may store the synthesized image generated by the synthesized image generating means.

[0974] The output means may output existence and nonexistence of the image corresponding to the retrieval request information or the retrieved image along with existence and nonexistence of the image corresponding to the retrieval request information as the retrieval result and the charging means may perform the charge processing on the basis of the retrieval result output by the output means.

[0975] The charging means may generate charge information including a user ID, a communication apparatus ID and cost information corresponding to the retrieval request information in accordance with the retrieval request information.

[0976] The charging means may perform the charge processing based on the retrieval result output by the output means with respect to a financial account of the user on the basis of the charge information.

[0977] The charging means may perform the charge processing by subtracting the number of points corresponding to the cost information from the number of points of each user used for the charge processing.

[0978] The output means may output the retrieval result to a communication apparatus of the user having finished the charge processing after the charge processing has been finished by the charging means.

[0979] A communication method of the 7th communication system of the present invention is characterized in that a communication method of the first communication apparatus comprises: a retrieval request information input step of inputting retrieval request information of a user; a retrieval request information transmitting step of transmitting the retrieval request information to a second communication apparatus; and a retrieval result receiving step of receiving a retrieval result transmitted from the second communication apparatus, and a communication method of the second communication apparatus comprises: a retrieval request information receiving step of receiving the retrieval request information transmitted from the first communication apparatus; a storing step of storing an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieving step of retrieving the image corresponding to the retrieval request information received in the retrieval request information receiving step among images stored in the storing step; an retrieval result transmitting step of transmitting the retrieval result of the retrieving step to the first communication apparatus; and a charging step of performing a charge processing in accordance with the retrieval result.

[0980] A program of a 23rd recording medium of the present invention is characterized in that a program for controlling the first communication apparatus comprises: a retrieval request information input control step of controlling input of retrieval request information of a user; a retrieval request information transmission control step of controlling transmission of the retrieval request information to a second communication apparatus; and a retrieval result reception control step of controlling reception of a retrieval result transmitted from the second communication apparatus, and a program for controlling the second communication apparatus comprises: a retrieval request information reception control step of controlling reception of the retrieval request information transmitted from the first communication apparatus; a storage control step of controlling storage of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of the image corresponding to the retrieval request information received in the retrieval request information reception control step among images stored in the storage control step; an retrieval result transmission control step of controlling transmission of the retrieval result of the retrieval control step to the first communication apparatus; and a charge control step of controlling performance of a charge processing in accordance with the retrieval result.

[0981] A 23rd program of the present invention is characterized by making a computer for controlling the first communication apparatus perform: a retrieval request information input control step of controlling input of retrieval request information of a user; a retrieval request information transmission control step of controlling transmission of the retrieval request information to a second communication apparatus; and a retrieval result reception control step of controlling reception of a retrieval result transmitted from the second communication apparatus, and by making a computer for controlling the second communication apparatus perform: a retrieval request information reception control step of con-

light forming an image integrated over time; a retrieval control step of controlling retrieval of the image corresponding to the retrieval request information received in the retrieval request information reception control step among images stored in the storage control step; an retrieval result transmission control step of controlling transmission of a retrieval result of the retrieval control step to the other communication apparatus; and a charge control step of control performance of a charge processing in accordance with the retrieval result.

[0989] A 25th program of the present invention is characterized by making a computer perform: a retrieval request information reception control step of controlling reception of retrieval request information transmitted from other communication apparatus; a storage control step of controlling storage of an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a retrieval control step of controlling retrieval of the image corresponding to the retrieval request information received in the retrieval request information reception control step among images stored in the storage control step; an retrieval result transmission control step of controlling transmission of a retrieval result of the retrieval control step to the other communication apparatus; and a charge control step of control performance of a charge processing in accordance with the retrieval result.

[0990] A 19th communication apparatus of the present invention is characterized by comprising: a foreground component image discerning information input means for inputting a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input means for inputting a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; an image positional information generating means for generating a foreground component image positional information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and an output means for outputting the foreground component image positional information and the background component image positional information generated by the image positional information generating means.

[0991] A mixture ratio generating means for generating a mixture ratio of an area in which the foreground component image and the background component image are mixed from the image data that is obtained by the image pickup element having the predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming the image integrated over time, a separating means for separating the image data into the foreground component image and the background component image according to the mixture ratio, a discerning information generating means for generating the foreground component image discerning information based on the foreground component image and the background component image discerning information based on the background component image, respectively, and a discerning information supplying means for supplying the foreground component image discerning information generated by the discerning information generating means to the foreground component image discerning information input means and the background component image discerning information generated by the discerning information generating means to the background component image discerning information input means, respectively, may be further comprised.

[0992] A storing means for storing at a predetermined position the foreground component image and the background component image separated from the image data by the separating means and a positional information storing means for storing each positional information of the foreground component image and the background component image of the image data stored by the storing means may be further comprised and the image positional information generating means may generate the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information on the basis of the positional information stored by the positional information storing means and indicative of positions at which the foreground component image and the background component image are stored.

[0993] The storing means may store the foreground component image and the background component image separated from the image data by the separating means in other communication apparatus connected through a network, the positional information storing means may store each positional information on the network of the foreground component image and the background component image of the image data stored in the other communication apparatus connected via the network by the storing means, and the image positional information generating means may generate the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image dis-

cerning information on the basis of the positional information on the network of the foreground component image and the background component image of the image data stored by the positional information storing means.

[0994] The storing means may store at a predetermined position the foreground component image and the background component image separated from the image data by the separating means along with IDs corresponding to the foreground component image and the background component image, respectively.

[0995] A comparing means for comparing the respective IDs of the foreground component image and the background component image separated from the image data by the separating means with IDs of the foreground component image or the background component image previously stored by the storing means may be further comprised, and the storing means may store at a predetermined position the foreground component image and the background component image separated from the image data by the separating means along with IDs corresponding to the foreground component image and the background component image, respectively, on the basis of the comparison result of the comparing means.

[0996] When the comparison results of the comparing means are matched, the image positional information generating means may generate the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information on the basis of the positional information of the foreground component image or the background component image previously stored by the positional information storing means.

[0997] The foreground component image discerning information input means may input the foreground component image having the foreground object components constituting the foreground object of the image data as the foreground component image discerning information and the background component image discerning information input means may input the background component image having the background object components constituting the background object of the image data as the background component image discerning information.

[0998] A charging means for performing a charge processing corresponding to output of the foreground component image positional information and the background component image positional information may be further comprised.

[0999] The charging means may generate charge information including a user ID, an ID of itself and cost information corresponding to output of the foreground component image positional information and the background component image positional information.

[1000] The charging means may perform the charge processing with respect to a financial account of the user on the basis of the charge information.

[1001] The charging means may perform the charge processing by subtracting the number of points corresponding to the cost information from the number of points of each user used for the charge processing.

[1002] The output means may output the foreground component image positional information and the background component image positional information after the charge processing has been finished by the charging means, in a way that only the user can obtain them.

[1003] A 19th communication method of the present invention is characterized by comprising: a foreground component image discerning information input step of inputting a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input step of inputting a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; an image positional information generating step of generating a foreground component image positional information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and an output step of outputting the foreground component image positional information and the background component image positional information generated in the image positional information generating step.

[1004] A program of a 26th recording medium of the present invention is characterized by comprising: a foreground component image discerning information input control step of controlling input of a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input control step of controlling input of a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; an image positional information generation control step of controlling generation of a foreground component image positional information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and an output

control step of controlling output of the foreground component image positional information and the background component image positional information generated in the image positional information generation control step.

[1005] A 26th program of the present invention is characterized by making a computer perform: a foreground component image discerning information input control step of controlling input of a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input control step of controlling input of a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; an image positional information generation control step of controlling generation of a foreground component image positional information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and an output control step of controlling output of the foreground component image positional information and the background component image positional information generated in the image positional information generation control step.

[1006] A 8th communication system of the present invention is characterized in that a first communication apparatus comprises: a foreground component image discerning information input means for inputting a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input means for inputting a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; a first transmitting means for transmitting the foreground component image discerning information and the background component image discerning information to a second communication apparatus; and a positional information receiving means for receiving a foreground component image positional information and a background component image positional information transmitted from the second communication apparatus, and the second communication apparatus comprises: a foreground component image discerning information receiving means for receiving the foreground component image discerning information transmitted from the first communication apparatus; a background component image discerning information receiving means for receiving the background component image discerning information transmitted from the first communication apparatus; an image positional information generating means for generating a foreground component image positional information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and a second transmitting means for transmitting the foreground component image positional information and the background component image positional information generated by the image positional information generating means to the first communication apparatus.

[1007] The second communication apparatus may further comprise: a mixture ratio generating means for generating a mixture ratio of an area in which the foreground component image and the background component image are mixed from the image data that is obtained by the image pickup element having the predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming the image integrated over time; a separating means for separating the image data into the foreground component image and the background component image according to the mixture ratio; a discerning information generating means for generating the foreground component image discerning information on the basis of the foreground component image and the background component image discerning information on the basis of the background component image, respectively; and a discerning information supplying means for supplying the foreground component image discerning information generated by the discerning information generating means to the foreground component image discerning information input means and the background component image discerning information generated by the discerning information generating means to the background component image discerning information input means, respectively.

[1008] A storing means for storing at a predetermined position the foreground component image and the background component image separated from the image data by the separating means and a positional information storing means for storing each positional information of the foreground component image and the background component image of the image data stored by the storing means may be further comprised, and the image positional information generating means may generate the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information on the basis of the positional information stored by the positional information storing means and indicative of positions at which the foreground component image and the background component image are stored.

[1009] The storing means may store the foreground component image and the background component image separated from the image data by the separating means in other communication apparatus connected through a network, the positional information storing means may store each positional information on the network of the foreground component image and the background component image of the image data stored in the other communication apparatus connected via the network by the storing means, and the image positional information generating means may generate the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information on the basis of each positional information on the network of the foreground component image and the background component image of the image data stored by the positional information storing means.

[1010] The storing means may store at a predetermined position the foreground component image and the background component image separated from the image data by the separating means along with IDs corresponding to the foreground component image and the background component image, respectively.

[1011] The second communication apparatus may further comprise a comparing means for comparing the respective IDs of the foreground component image and the background component image separated from the image data by the separating means with IDs of the foreground component image or the background component image previously stored by the storing means, and the storing means may store at a predetermined position the foreground component image and the background component image separated from the image data by the separating means along with IDs corresponding to the foreground component image and the background component image, respectively, on the basis of the comparison result of the comparing means.

[1012] When the comparison results of the comparing means are matched, the image positional information generating means may generate the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information on the basis of the positional information of the foreground component image or the background component image previously stored by the positional information storing means.

[1013] The foreground component image discerning information input means may input the foreground component image having the foreground object components constituting the foreground object of the image data as the foreground component image discerning information and the background component image discerning information input means may input the background component image having the background object components constituting the background object of the image data as the background component image discerning information.

[1014] The second communication apparatus may further comprise a charging means for performing a charge processing corresponding to output of the foreground component image positional information and the background component image positional information.

[1015] The charging means may generate charge information including a user ID, an ID of the second communication apparatus and cost information corresponding to output of the foreground component image positional information and the background component image positional information.

[1016] The charging means may perform the charge processing with respect to a financial account of the user on the basis of the charge information.

[1017] The charging means may perform the charge processing by subtracting the number of points corresponding to the cost information from the number of points of each user used for the charge processing.

[1018] The output means may output the foreground component image positional information and the background component image positional information to the user having finished the charge processing after the charge processing has been finished by the charging means.

[1019] A communication method of the 8th communication system of the present invention is characterized in that a communication method of the first communication apparatus comprises: a foreground component image discerning information input step of inputting a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input step of inputting a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; a first transmitting step of transmitting the foreground component image discerning information and the background component image discerning information to a second communication apparatus; and a positional information receiving step of receiving a foreground component image positional information and a background component image positional information transmitted from the second communication apparatus, and a communication method of the second communication apparatus comprises: a foreground component image discerning information receiving step of receiving the foreground component image discerning information transmitted from the first communication apparatus; a background component image discerning information receiving step of receiving the background component image discerning information transmitted from the first communication apparatus;

an image positional information generating step of generating the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and a second transmitting step of transmitting the foreground component image positional information and the background component image positional information generated in the image positional information generating step to the first communication system.

[1020] A program of a 27th recording medium of the present invention is characterized in that a program for controlling the first communication apparatus comprises: a foreground component image discerning information input control step of controlling input of a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input control step of controlling input of a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; a first transmission control step of controlling transmission of the foreground component image discerning information and the background component image discerning information to a second communication apparatus; and a positional information reception control step of controlling reception of a foreground component image positional information and a background component image positional information transmitted from the second communication apparatus, and a program for controlling the second communication apparatus comprises: a foreground component image discerning information reception control step of controlling reception of the foreground component image discerning information transmitted from the first communication apparatus; a background component image discerning information reception control step of controlling reception of the background component image discerning information transmitted from the first communication apparatus; an image positional information generation control step of controlling generation of the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and a second transmission control step of controlling transmission of the foreground component image positional information and the background component image positional information generated in the image positional information generation control step to the first communication system.

[1021] A 27th program of the present invention is characterized by making a computer for controlling a first communication apparatus perform: a foreground component image discerning information input control step of controlling input of a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input control step of controlling input of a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; a first transmission control step of controlling transmission of the foreground component image discerning information and the background component image discerning information to a second communication apparatus; and a positional information reception control step of controlling reception of a foreground component image positional information and a background component image positional information transmitted from the second communication apparatus, and by making a computer for controlling the second communication apparatus perform: a foreground component image discerning information reception control step of controlling reception of the foreground component image discerning information transmitted from the first communication apparatus; a background component image discerning information reception control step of controlling reception of the background component image discerning information transmitted from the first communication apparatus; an image positional information generation control step of controlling generation of the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and a second transmission control step of controlling transmission of the foreground component image positional information and the background component image positional information generated in the image positional information generation control step to the first communication system.

[1022] A 20th communication apparatus of the present invention is characterized by comprising: a foreground component image discerning information input means for inputting a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input means for inputting a background component image discerning information indicative of a background component image having

background object components constituting a background object of the image data; a transmitting means for transmitting the foreground component image discerning information and the background component image discerning information to other communication apparatus through a network; and a positional information receiving means for receiving a foreground component image positional information and a background component image positional information transmitted from the other communication apparatus through a network.

[1023] A 20th communication method of the present invention is characterized by comprising: a foreground component image discerning information input step of inputting a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input step of inputting a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; a transmitting step of transmitting the foreground component image discerning information and the background component image discerning information to other communication apparatus through a network; and a positional information receiving step of receiving a foreground component image positional information and a background component image positional information transmitted from the other communication apparatus via the network.

[1024] A program of a 28th recording medium of the present invention is characterized by comprising: a foreground component image discerning information input control step of controlling input of a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input control step of controlling input of a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; a transmission control step of controlling transmission of the foreground component image discerning information and the background component image discerning information to other communication apparatus through a network; and a positional information reception control step of controlling reception of a foreground component image positional information and a background component image positional information transmitted from the other communication apparatus via the network.

[1025] A 28th program of the present invention is characterized by making a computer perform: a foreground component image discerning information input control step of controlling input of a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information input control step of controlling input of a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data; a transmission control step of controlling transmission of the foreground component image discerning information and the background component image discerning information to other communication apparatus through a network; and a positional information reception control step of controlling reception of a foreground component image positional information and a background component image positional information transmitted from the other communication apparatus via the network.

[1026] A 21st communication apparatus of the present invention is characterized by comprising: a foreground component image discerning information receiving means for receiving the foreground component image discerning information of image data transmitted from other communication apparatus through a network, the image data being obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information receiving means for receiving the background component image discerning information transmitted from the other communication apparatus; an image positional information generating means for generating a foreground component image positional information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and a transmitting means for transmitting the foreground component image positional information and the background component image positional information generated by the image positional information generating means to the other communication apparatus via the network.

[1027] A 21st communication method of the present invention is characterized by comprising: a foreground component image discerning information receiving step of receiving the foreground component image discerning information of image data transmitted from other communication apparatus through a network, the image data being obtained by

an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information receiving step of receiving the background component image discerning information transmitted from the other communication apparatus; an image positional information generating step of generating a foreground component image positional information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and a transmitting step of transmitting the foreground component image positional information and the background component image positional information generated in the image positional information generating step to the other communication apparatus via the network.

[1028] A program of a 29th recording medium of the present invention is characterized by comprising: a foreground component image discerning information reception control step of controlling reception of the foreground component image discerning information of image data transmitted from other communication apparatus through a network, the image data being obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information reception control step of controlling reception of the background component image discerning information transmitted from the other communication apparatus; an image positional information generation control step of controlling generation of a foreground component image positional information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and a transmission control step of controlling transmission of the foreground component image positional information and the background component image positional information generated in the image positional information generation control step to the other communication system via the network.

[1029] A 29th program of the present invention is characterized by making a computer perform: a foreground component image discerning information reception control step of controlling reception of the foreground component image discerning information of image data transmitted from other communication apparatus through a network, the image data being obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; a background component image discerning information reception control step of controlling reception of the background component image discerning information transmitted from the other communication apparatus; an image positional information generation control step of controlling generation of a foreground component image positional information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information; and a transmission control step of controlling transmission of the foreground component image positional information and the background component image positional information generated in the image positional information generation control step to the other communication system via the network.

[1030] In the 1st communication system and method and the 2nd program of the present invention, by a first communication apparatus, requested information of a user is input from among a plurality of encoded data which are generated on the basis of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; the input request information is transmitted to the second communication apparatus; and the encoded data generated on the basis of the image data corresponding to the requested information transmitted from the second communication apparatus is received, and by the second communication apparatus, the requested information transmitted from the first communication apparatus is received; the image data is separated into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; and the encoded data generated when the image is separated into the foreground component image and the background component image on the basis of the received request information is transmitted to the first communication apparatus.

[1031] In the 2nd communication apparatus and method and the 3rd program of the present invention, the request requested information of a user is input from among a plurality of encoded data which are generated on the basis of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; the input request information is transmitted to other communication apparatus; and the encoded data generated on the basis of the image data corresponding to the requested information, transmitted from other communication apparatus, is received.

[1032] In the 3rd communication apparatus and method and the 4th program of the present invention, the requested information transmitted from other communication apparatus is received; the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised

of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time is separated into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; and the encoded data generated when the image is separated into the foreground component image and the background component image on the basis of the received request information is transmitted to other communication apparatus.

[1033] In the 2nd communication system and method and the 5th program of the present invention, by the first communication apparatus, the request requested information of a user is input from among a plurality of encoded data which are generated on the basis of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; the input request information is transmitted to one of the second communication apparatus to the fourth communication apparatus; and the encoded data generated on the basis of the image data corresponding to the requested information, transmitted from the one of the second communication apparatus to the fourth communication apparatus, is received, by the second communication apparatus, the requested information transmitted from the first communication apparatus is received; the image data is separated into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; and the foreground component image and the background component image separated from the image on the basis of the received request information are transmitted as the encoded data to the first communication apparatus, by the third communication apparatus, the requested information transmitted from the first communication apparatus is received; area information discerning any of a foreground area having foreground object components constituting a foreground object of the image data, a background area having background object components constituting a background object of the predetermined image data and a mixed area in which the foreground area and the background area are mixed is generated; and the generated area information based on the received request information is transmitted as the encoded data to the first communication apparatus, and by the fourth communication apparatus, the requested information transmitted from the first communication apparatus is received; a mixture ratio indicating a ratio in which the foreground area and the background area are mixed in the mixed area of the image data is generated; and the mixture ratio generated on the basis of the received request information is transmitted to the first communication apparatus.

[1034] In the 4th communication apparatus and method and the 6th program of the present invention, the requested information of a user is input; in accordance with the requested information, a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data of a predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are synthesized and a synthesized image is generated; and the generated synthesized image is output.

[1035] In the 3rd communication system and method and the 7th program of the present invention, by the first communication apparatus, the requested information of a user is input; the input request information is transmitted to the second communication apparatus; and in accordance with the requested information, the synthesized image transmitted from the second communication apparatus is input, and by the second communication apparatus, the requested information transmitted from the first communication apparatus is received; in accordance with the requested information, a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time are synthesized and a synthesized image is generated; and the generated synthesized image is transmitted to the first communication apparatus.

[1036] In the 5th communication apparatus and method and the 8th program of the present invention, the requested information of a user is input; the input request information is transmitted to other communication apparatus; and the synthesized data transmitted from other communication apparatus in accordance with the requested information is received.

[1037] In the 6th communication apparatus and method and the 9th program of the present invention, the requested information transmitted from other communication apparatus is received; in accordance with the requested information, a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of

light forming an image integrated over time are synthesized and the synthesized image is generated; and the generated synthesized image is transmitted to other communication apparatus.

[1038] In the 7th communication apparatus and method and the 10th program of the present invention, the requested information of a user is input; in accordance with the requested information, a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object to a background component image having background object components constituting a background object of the image data are mixed is estimated, the image data being is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; on the basis of the mixture ratio, the image data is separated into the foreground component image and the background component image; the separated foreground component image and any background component image, or the separated background component image and any foreground component image are synthesized in a predetermined mixture ratio and a synthesized image is generated; and the synthesized image is output.

[1039] In the 4th communication system and method and the 11th program of the present invention, by the first communication apparatus, the requested information of a user is input; the input request information is transmitted to the second transmitting apparatus; and the synthesized image transmitted from the second communication apparatus is received, and by the second communication apparatus, the requested information transmitted from the first communication apparatus is received; a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data are mixed is estimated on the basis of the requested information, the image data being obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; the image data is separated into the foreground component image and the background component image on the basis of the mixture ratio; the separated foreground component image and any background component image or the separated background component image and any foreground component image are synthesized in a predetermined mixture ratio and the synthesized image is generated; and the synthesized image is transmitted to the first communication apparatus.

[1040] In the 8th communication apparatus and method and the 12th program of the present invention, the requested information of a user is input; the requested information is transmitted to other communication apparatus; and the synthesized image transmitted from other communication apparatus is received.

[1041] In the 9th communication apparatus and method and the 13th program of the present invention, the requested information transmitted from other communication apparatus is received; a mixture ratio indicating a ratio in which a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object of the image data are mixed is estimated on the basis of the requested information, the image data being obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; the image data is separated into the foreground component image and the background component image on the basis of the mixture ratio; the separated foreground component image and any background component image or the separated background component image and any foreground component image are synthesized in a predetermined ratio and the synthesized image is generated; and the synthesized image is transmitted to other communication apparatus.

[1042] In the 10th communication apparatus and method and the 14th program of the present invention, an ID discerning an image requested by a user is input; an image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from the image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is stored; the image corresponding to the input image ID is retrieved from among the stored images; the retrieved image is transmitted to the communication apparatus of the user; and the charge processing is performed in accordance with the retrieved image.

[1043] In the 5th communication system and method and the 15th program of the present invention, by the first communication apparatus, an ID discerning an image requested by a user is input; the image ID is transmitted to a second communication apparatus; and the image retrieved correspondingly to the image ID is received, and by the second communication apparatus, the image ID transmitted from the first communication apparatus is received; the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in

accordance with an amount of light forming an image integrated over time, is stored; the image corresponding to the received image ID is retrieved from among the stored images; the retrieved image is output to the first communication apparatus; and a charge processing is performed in accordance with the retrieved image.

[1044] In the 11th communication apparatus and method and the 16th program of the present invention, an ID discerning an image requested by a user is input; the image ID is transmitted to other communication apparatus; and the image retrieved correspondingly to the image ID is received.

[1045] In the 12th communication apparatus and method and the 17th program of the present invention, an image ID transmitted from other communication apparatus is received; the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is stored; the image corresponding to the received image ID is retrieved from among the stored images; the retrieved image is output to other communication apparatus; and a charge processing is performed in accordance with the retrieved image.

[1046] In the 13th communication apparatus and method and the 18th program of the present invention, the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is input; the input image is stored; and a payment processing is performed in accordance with the stored image.

[1047] In the 6th communication system and method and the 29th program of the present invention, by a first communication apparatus, the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is input; and the input image is transmitted to a second communication apparatus, and by the second communication apparatus, the image transmitted from the first communication apparatus is received; the received image are stored; and a payment processing is performed in accordance with the stored image. In the 14th communication apparatus and method and the 20th program of the present invention, the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is input; and the input image is transmitted to other communication apparatus.

[1048] In the 15th communication apparatus and method and the 21st program of the present invention, an image transmitted from other communication apparatus is received; the received image is stored; and a payment processing is performed in accordance with the stored image.

[1049] In the 16th communication apparatus and method and the 22nd program of the present invention, a retrieval request information of a user is input; the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is input; the image corresponding to the input retrieval request information is retrieved from among the stored images; the retrieval result is output; and a charge processing is performed in accordance with the retrieval result.

[1050] In the 7th communication system and method and the 23rd program of the present invention, by a first communication apparatus, a retrieval request information of a user is input; the retrieval request information is transmitted to a second communication apparatus; and the retrieval result transmitted from the second communication apparatus is received, and by the second communication apparatus, the retrieval request information transmitted from the first communication apparatus is received; the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is stored; the image corresponding to the received retrieval request information is retrieved from among the

stored images; the retrieval result is transmitted to the first communication apparatus; and a charge processing is performed in accordance with the retrieval result.

[1051] In the 17th communication apparatus and method and the 24th program of the present invention, retrieval request information of a user is input; the retrieval request information is transmitted to other communication apparatus; and the retrieval result transmitted from the other communication apparatus is received.

[1052] In the 18th communication apparatus and method and the 25th program of the present invention, the retrieval request information transmitted from other communication apparatus is received; the image comprised of at least one image of a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object separated from image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is stored; the image corresponding to the received retrieval request information is retrieved from among the stored images; the retrieval result is transmitted to the other communication apparatus; and a charge processing is performed in accordance with the retrieval result.

[1053] In the 19th communication apparatus and method and the 26th program of the present invention, foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is input; background component image discerning information indicative of a background component image having background object components constituting a background object of the image data is input; foreground component image positional information and background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information are generated; and the generated foreground component image positional information and the generated background component image positional information are output.

[1054] In the 8th communication system and method and the 27th program of the present invention, by a first communication apparatus, a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is input; a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data is input; the foreground component image discerning information and the background component image discerning information are transmitted to a second communication apparatus; and a foreground component image positional information and a background component image positional information transmitted from the second communication apparatus are received, and by a second communication apparatus, the foreground component image discerning information transmitted from the first communication apparatus is received; the background component image discerning information transmitted from the first communication apparatus is received; the foreground component image positional information and the background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information are generated; and the generated foreground component image positional information and the generated background component image positional information are transmitted to the first communication apparatus.

[1055] In the 20th communication apparatus and method and the 28th program of the present invention, a foreground component image discerning information indicative of a foreground component image having foreground object components constituting a foreground object of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time, is input; a background component image discerning information indicative of a background component image having background object components constituting a background object of the image data is input; the foreground component image discerning information and the background component image discerning information are transmitted to other communication apparatus through a network; a foreground component image positional information and a background component image positional information transmitted from the other communication apparatus through a network are received.

[1056] In the 21st communication apparatus and method and the 29th program of the present invention, the foreground component image discerning information of image data transmitted from other communication apparatus through a network is received, the image data being obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined for every pixels in accordance with an amount of light forming an image integrated over time; the background component image discerning information transmitted from the other communication apparatus is received; a foreground component image positional

information and a background component image positional information corresponding to the foreground component image discerning information and the background component image discerning information are generated; and the generated foreground component image positional information and the generated background component image positional information are transmitted to the other communication apparatus via the network.

5 [1057] As a result, it is possible to encrypt an image by adding motion blur to the image, and also to decrypt the encrypted image by eliminating the motion blur, that is, adding motion blur inverse to the motion blur added in the encryption process.

[1058] Further, it is possible to obtain a clear foreground component image having been eliminated with motion blur by adjusting the motion blur contained in the foreground component image, and to generate a synthesized image 10 appearing seemingly natural by combining the motion blur adjusted foreground component image with a background component image. As a result, by adjusting the motion blur in the foreground component image and by synthesizing an image by processing the resulting foreground component with a background component, it is possible to correct images more naturally.

[1059] Moreover, since the image obtained by separating, synthesizing or correcting an image on the basis of mixed state of the image, can be purchased or sold via the network 1, the separated, synthesized or corrected image can be effectively utilized by selling the images processed by the users.

[1060] Furthermore, it is possible to retrieve the images which are being photographed, or have been photographed and stored by the camera terminal units 28-1 to 28-n by a simple input of the retrieval conditions.

[1061] Moreover, by storing images in a predetermined storage server rather than in user's computer, and by reading out and utilizing the images on the basis of positional information of the storage server as needed, pre-existing image data can be called out and utilized as needed without maintaining them in their own communication apparatus, such that images can be efficiently utilized.

[1062] According to above descriptions, it is possible to encrypt image by adding motion blur to the image and decrypt the image by eliminating the motion blur. Further, it is also possible to eliminate motion blur to generate a clear image and correct an image more naturally to synthesize an image in which motion blur is adjusted by combining the motion blur adjusted foreground component with a background image. Further, it is possible to effectively utilize via the network images separated, synthesized or corrected on the basis of mixed state of the image. Moreover, it is also possible to retrieve the separated, synthesized or corrected images via the network. In addition, it is possible to call out and utilize pre-existing images without maintaining them in their own communication apparatus.

30 [1063] The recording medium having a program for performing signal processing according to the present invention may be, as shown in FIG. 2 and FIG. 3, a package medium having magnetic discs 61, 91 (including flexible discs), optical discs 62, 92 (including CD-ROM (Compact Disc-Read Only Memory) and DVD (Digital Versatile Disc), magneto-optical discs 63, 93 (including MD ((Mini-Disc)(trademark)), semiconductor memories 64, 94, etc. recorded with the program for being able to be distributed to the users as an individual component separated from a computer. To be provided to the users by having already incorporated in a computer, the above recording medium may also be a ROM 42, 72 in which the program is recorded, or a hard disc included in the storage units 48, 78.

[1064] Further, in the present specification, the steps for describing the program recorded in the recording medium comprise the processing to be performed in time sequence in the order of description and the processing to be performed simultaneously or separately, not necessarily in time sequence.

40 [1065] Furthermore, in the present specification, a system means the whole apparatus comprising a plurality of apparatuses.

Industrial Applicability

45 [1066] According to the present invention, it is possible to improve the image processing speed and to reduce cost for service by distributing the image processing to perform only the requested processing.

Claims

50 1. A communication system comprising:

separating means for separating predetermined image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object; and requested information input means for inputting requested information of a user; and

encoded data output means for outputting encoded data generated when said image is separated into said foreground component image and said background component image by said separating means, on the basis of said requested information input by said requested information input means.

- 5 2. The communication system as claimed in claim 1, further comprising charging means for performing charge processing in accordance with said requested information.
3. The communication system as claimed in claim 2, wherein, in accordance with said requested information, said charging means generates charge information including an ID of said user, an ID of said communication system,
10 and cost information corresponding to said requested information.
4. The communication system as claimed in claim 3, wherein said charging means performs the charge processing with respect to a financial account of said user on the basis of said charge information.
- 15 5. The communication system as claimed in claim 4, wherein said charging means performs the charge processing by deducting the number of points corresponding to said cost information and user used in the charge processing from the number of points of each.
- 20 6. The communication system as claimed in claim 2, wherein after said charging means has finished the charge processing, said encoded data output means outputs said encoded data to a communication apparatus of said user after finishing the charge processing.
7. The communication system as claimed in claim 6, wherein said requested information input means inputs said predetermined image data in addition to said requested information of said user; and
25 said encoded data output means outputs said encoded data as significant data generated when said predetermined image is separated into said foreground component image and said background component image by said separating means on the basis of said requested information input by said requested information input means and said predetermined image data, in a way obtainable only to said user after the charge processing by said charging means has finished.
- 30 8. The communication system as claimed in claim 7, further comprising:

an area information generating means for generating area information for discerning any of a foreground area having foreground object components constituting a foreground object of said predetermined image data, a
35 background area having background object components constituting a background object of said predetermined image data and a mixed area in which said foreground area and said background area are mixed,

wherein said significant information includes said area information, and
wherein said encoded data output means outputs said encoded data as said area information generated
40 when said predetermined image is separated into said foreground component image and said background component image by said separating means on the basis of said requested information input by said requested information input means and said predetermined image data, in a way obtainable only to said user after the charge processing by said charging means has finished.
- 45 9. The communication system as claimed in claim 7, further comprising:

a mixture ratio generating means for generating a mixture ratio indicating the ratio at which said foreground area and said background area are mixed in said mixed area of said predetermined image data,

50 wherein said significant information includes said mixture ratio, and
wherein said encoded data output means outputs said encoded data as said mixture ratio generated when said predetermined image is separated into said foreground component image and said background component image by said separating means on the basis of said requested information input by said requested information input means and the predetermined image data, in a way obtainable only to said user after the charge processing
55 by said charging means has finished.
10. The communication system as claimed in claim 7, wherein said separating means separates said predetermined image data that is obtained by the image pickup element having the predetermined number of pixels, each having

a time integration effect, and that is comprised of the pixel values determined every pixel in accordance with the amount of light forming a predetermined image integrated over time into said foreground component image having the foreground object components constituting the foreground object and said background component image having the background object components constituting the background object on the basis of said area information and said mixture ratio, and

wherein said significant information includes said foreground component image and said background component image, and

wherein said encoded data output means outputs said requested information input by said requested information input means and said encoded data as said foreground component image and said background component image generated when said predetermined image is separated into said foreground component image and said background component image by said separating means, in a way obtainable only to said user after the charge processing by said charging means has finished.

11. The communication system as claimed in claim 6, wherein said requested information input means inputs an image data ID for discerning said predetermined image data in addition to said requested information of said user, and wherein said encoded data output means outputs said encoded data as said significant information generated when said predetermined image is separated into said foreground component image and said background component image by said separating means on the basis of said requested information input by said requested information input means and the predetermined image data corresponding to said image data ID, in a way obtainable only to said user after the charge processing by said charging means has finished.

12. The communication system as claimed in claim 11, further comprising:

area information generating means for generating area information for discerning any of a foreground area having foreground object components constituting the foreground object of the predetermined image data corresponding to said image data ID, a background area having background object components constituting the background object of the predetermined image data corresponding to said image data ID, and a mixed area in which said foreground area and said background area are mixed,

wherein said significant information includes said area information, and

wherein said encoded data output means outputs said encoded data as said area information generated when said predetermined image is separated into said foreground component image and said background component image by said separating means on the basis of said requested information input by said requested information input means and said predetermined image data, in a way obtainable only to said user after the charge processing by said charging means has finished.

13. The communication system as claimed in claim 11, further comprising:

mixture ratio generating means for generating a mixture ratio of said mixed area in the predetermined image data corresponding to said image data ID,

wherein said significant information includes said mixture ratio, and

wherein said encoded data output means outputs said encoded data as said mixture ratio generated when said predetermined image is separated into said foreground component image and said background component image by said separating means on the basis of said requested information input by said requested information input means and the predetermined image data corresponding to said image data ID, in a way obtainable only to said user after the charge processing by said charging means has finished.

14. The communication system as claimed in claim 11, wherein said separating means separates the predetermined image data that is obtained by the image pickup element having the predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with the amount of light forming a predetermined image integrated over time into said foreground component image having the foreground object components constituting the foreground object and said background component image having the background object components constituting the background object on the basis of said area information and said mixture ratio,

wherein said significant information includes said foreground component image and said background component image, and

wherein said encoded data output means outputs said requested information input by said requested information input means and said encoded data as said foreground component image and said background component image generated when said predetermined image is separated into said foreground component image and said background component image by said separating means, in a way obtainable only to said user after the charge processing by said charging means has finished.

mation input means and said encoded data as said foreground component image and said background component image generated when said predetermined image is separated into said foreground component image and said background component image by said separating means, in a way obtainable only to said user after the charge processing by said charging means has finished.

15. A communication method comprising:

a separating step of separating image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object;
a requested information inputting step of inputting requested information of a user; and
an encoded data outputting step of outputting encoded data generated when said image is separated into said foreground component image and said background component image in said separating step on the basis of said requested information input in said requested information inputting step.

16. A recording medium having a computer-readable program, wherein the program comprises:

a separation controlling step of controlling the separation of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object;
a requested information input controlling step of controlling the input of requested information of a user; and
an encoded data output controlling step of controlling the output of encoded data generated when said image is separated into said foreground component image and said background component image in said separation controlling step on the basis of said requested information input in said requested information input controlling step.

17. A program for a computer comprises:

a separation controlling step of controlling the separation of image data that is obtained by an image pickup element having a predetermined number of pixels, each having a time integration effect, and that is comprised of pixel values determined every pixel in accordance with an amount of light forming an image integrated over time into a foreground component image having foreground object components constituting a foreground object and a background component image having background object components constituting a background object;
a requested information input controlling step of controlling the input of requested information of a user; and
an encoded data output controlling step of controlling the output of encoded data generated when said image is separated into said foreground component image and said background component image in said separation controlling step on the basis of said requested information input in said requested information input controlling step.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28





FIG. 29




FIG. 30




FIG. 31A




FIG. 31B




FIG. 32

AREA		DESCRIPTION
BACKGROUND AREA		STATIONARY PORTION
FOREGROUND AREA		MOVING PORTION
MIXED AREA	COVERED BACKGROUND AREA	PORTION CHANGING FROM BACKGROUND TO FOREGROUND
	UNCOVERED BACKGROUND AREA	PORTION CHANGING FROM FOREGROUND TO BACKGROUND

FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50

AREA DETERMINATION	STATIONARY/MOVING DETERMINATION BETWEEN FRAME #n 1 AND FRAME #n 2	STATIONARY/MOVING DETERMINATION BETWEEN FRAME #n AND FRAME #n 1	STATIONARY/MOVING DETERMINATION BETWEEN FRAME #n AND FRAME #n+1	STATIONARY/MOVING DETERMINATION BETWEEN FRAME #n+1 AND FRAME #n+2
COVERED BACKGROUND AREA DETERMINATION	STATIONARY	MOVING	—	—
STATIONARY AREA DETERMINATION	—	STATIONARY	STATIONARY	—
MOVING AREA DETERMINATION	—	MOVING	MOVING	—
UNCOVERED BACKGROUND AREA DETERMINATION	—	—	MOVING	STATIONARY

FIG. 51A



FIG. 51B



FIG. 51C




FIG. 51D




FIG. 52



FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58A

X_0	X_1	X_2
X_3	X_4	X_5
X_6	X_7	X_8

FIG. 58B

Y_0	Y_1	Y_2
Y_3	Y_4	Y_5
Y_6	Y_7	Y_8

FIG. 59A

X_0	X_1	X_2
X_3	X_4	X_5
X_6	X_7	X_8

FIG. 59B

Y_0	Y_1	Y_2
Y_3	Y_4	Y_5
Y_6	Y_7	Y_8

FIG. 60




FIG. 61




FIG. 62

	BACKGROUND AREA	FOREGROUND AREA	COVERED BACKGROUND AREA	UNCOVERED BACKGROUND AREA
FRAME #n-1	—	1	0	—
FRAME #n	0	1	1	1
FRAME #n+1	—	1	—	0

FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68




FIG. 69




FIG. 70




FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85




FIG. 86




FIG. 87




FIG. 88




FIG. 89






FIG. 90A



↓ SEPARATE FOREGROUND
AND BACKGROUND



FOREGROUND




FIG. 90B




FIG. 91




FIG. 92




FIG. 93




FIG. 94




FIG. 95A




FIG. 95B




FIG. 96




FIG. 97




FIG. 98




FIG. 99




FIG. 100




FIG. 101




FIG. 102




FIG. 103




FIG. 104




FIG. 105




FIG. 106




FIG. 107




FIG. 108




FIG. 109




FIG. 110




FIG. 111




FIG. 112




FIG. 113




FIG. 114




FIG. 115




FIG. 116




FIG. 117




FIG. 118




FIG. 119




FIG. 120




FIG. 121




FIG. 122




FIG. 123




FIG. 124




FIG. 125




FIG. 126




FIG. 127




FIG. 128




FIG. 129




FIG. 130




FIG. 131




FIG. 132




FIG. 133




FIG. 134




FIG. 135




FIG. 136




FIG. 137




FIG. 138





FIG. 139




A 5x5 grid of cells. The cells are labeled as follows:

a0	b0	c0	d0	e0
a1	b1	c1	d1	e1
a2	b2	c2	d2	e2
a3	b3	c3	d3	e3
a4	b4	c4	d4	e4

Below the grid is a coordinate system with a vertical axis labeled 't' and a horizontal axis labeled 'x'.

FIG. 140



A 5x5 grid of cells, shifted diagonally. The cells are labeled as follows:

a0	b0	c0	d0	e0				
	a1	b1	c1	d1	e1			
		a2	b2	c2	d2	e2		
			a3	b3	c3	d3	e3	
				a4	b4	c4	d4	e4

Below the grid is a coordinate system with a vertical axis labeled 't' and a horizontal axis labeled 'x'.

FIG. 141




FIG. 142




FIG. 143

ux	vx	wx	xx	yx	ux'	vx'	wx'	xx'
px	qx	rx	sx	tx	px'	qx'	rx'	sx'
kx	lx	mx	nx	ox	kx'	lx'	mx'	nx'
fx	gx	hx	ix	jx	fx'	gx'	hx'	ix'
ax	bx	cx	dx	ex	ax'	bx'	cx'	dx'




FIG. 144

ax	fx	kx	px	ux
----	----	----	----	----




FIG. 145

ax0	fx0	kx0	px0	ux0
ax1	fx1	kx1	px1	ux1
ax2	fx2	kx2	px2	ux2
ax3	fx3	kx3	px3	ux3
ax4	fx4	kx4	px4	ux4




FIG. 146

ax0	fx0	kx0	px0	ux0				
	ax1	fx1	kx1	px1	ux1			
		ax2	fx2	kx2	px2	ux2		
			ax3	fx3	kx3	px3	ux3	
				ax4	fx4	kx4	px4	ux4




FIG. 147

B0	B1	B2	B3	B4	B5	B6	B7	B8
----	----	----	----	----	----	----	----	----

FIG. 148

	ax0	fx0	kx0	px0	ux0	B0x1/5		
		ax1	fx1	kx1	px1	ux1	B5x2/5	
			ax2	fx2	kx2	px2	ux2	B7x3/5
				ax3	fx3	kx3	px3	ux3
			B2x2/5	B3x1/5	ax4	fx4	kx4	px4
								ux4
B0x4/5		B1x3/5						B8x4/5




FIG. 149




FIG. 150




FIG. 151




FIG. 152




FIG. 153A




FIG. 153B




FIG. 153C




FIG. 153D




FIG. 154




FIG. 155




FIG. 156




FIG. 157




FIG. 158




FIG. 159





FIG. 160



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP02/06386

A. CLASSIFICATION OF SUBJECT MATTER Int.Cl ⁷ G06T7/20, H04N7/16				
According to International Patent Classification (IPC) or to both national classification and IPC				
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) Int.Cl ⁷ G06T7/20, G06T1/00, G06T3/00, H04N5/14-5/28, H04N7/16, H04N7/18, H04N7/32-7/46				
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1926-1996 Toroku Jitsuyo Shinan Koho 1994-2002 Kokai Jitsuyo Shinan Koho 1971-2002 Jitsuyo Shinan Toroku Koho 1996-2002				
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) JICST FILE (STN)				
C. DOCUMENTS CONSIDERED TO BE RELEVANT				
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
X A	JP 6-319130 A (Fujitsu General Ltd.), 15 November, 1994 (15.11.94), Par. Nos. [0016] to [0030] (Family: none)	1, 15-17 2-14		
A	EP 933727 A2 (Canon Kabushiki Kaisha), 04 August, 1999 (04.08.99), & JP 2000-30040 A	1-17		
A	JP 10-164436 A (Sony Corp.), 19 June, 1998 (19.06.98), (Family: none)	1-17		
A	JP 6-113338 A (Fujitsu Ltd.), 22 April, 1994 (22.04.94), (Family: none)	2-14		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.				
<table border="0"> <tr> <td> * Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed </td> <td> "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family </td> </tr> </table>			* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family			
Date of the actual completion of the international search 19 July, 2002 (19.07.02)		Date of mailing of the international search report 30 July, 2002 (30.07.02)		
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer		
Facsimile No.		Telephone No.		

Form PCT/ISA/210 (second sheet) (July 1998)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP02/06386

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 7-336688 A (Nippon Hoso Kyokai), 22 December, 1995 (22.12.95), (Family: none)	1-17
P, A	JP 2001-250119 A (Sony Corp.), 14 September, 2001 (14.09.01), (Family: none)	1-17
E, A	JP 2002-190015 A (Sony Corp.), 05 July, 2002 (05.07.02), (Family: none)	1-17
E, A	JP 2002-190016 A (Sony Corp.), 05 July, 2002 (05.07.02), (Family: none)	1-17
E, A	JP 2002-190028 A (Sony Corp.), 05 July, 2002 (05.07.02), (Family: none)	1-17

Form PCT/ISA/210 (continuation of second sheet) (July 1998)

This Page is inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images
problems checked, please do not report the
problems to the IFW Image Problem Mailbox**